

SUPPORT F. STAND-ALONE INSTALLATION FOR  
3RU21/3RB30/3RB31 SZ. S2, STAND-ALONE  
INSTALLATION MAIN CIRCUIT: SCREW TERMINAL



Figure similar

General technical data:

product brand name		SIRIUS
Product designation		individual mount
Size of overload relay		S2
Ambient temperature		
• during storage	°C	-50 ... +80
• during operation	°C	-20 ... +70

Installation/ mounting/ dimensions:

Mounting type		screw and snap-on mounting onto 35 mm standard mounting rail
Width	mm	55
Height	mm	105
Depth	mm	111





Connections/ Terminals:

Type of connectable conductor cross-section		
• for main contacts		
— finely stranded		
— with core end processing		
		1x (1 ... 35 mm <sup>2</sup> )

- for AWG conductors
- for main contacts

1x (18 ... 1)

### Certificates/ approvals:

General Product Approval	Declaration of Conformity	Test Certificates	other
 CSA	 EAC	 UL	 EG-Konf.
		<a href="#">Typprüfbescheinigung/Werkszeugnis</a>	<a href="#">Umweltbestätigung</a>

### Further information

#### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

#### Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

#### Cax online generator


<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RU29363AA01>


#### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RU29363AA01>

#### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RU29363AA01&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RU29363AA01&lang=en)





last modified:

20.07.2015