



Residual current operated circuit breaker, 2-pole, Type A, In: 40A, 30mA, Un AC: 230V Residential

Model	
product brand name	SENTRON
product designation	RCCB
design of the product	Instantaneous
General technical data	
number of poles	2
size of installation devices / according to DIN 43880	1
mechanical service life (switching cycles) / typical	3 000
short-circuit current / of series fuse / maximum permissible	63 A
short-circuit current rating	6 kA
switching function / short-term delayed	No
overvoltage category	III
Supply voltage	
supply voltage / for testing equipment / minimum	195 V
value range / of the supply voltage frequency	50 Hz
value range / of the operating frequency	50 Hz
value range / of the supply voltage / at AC	230/400 V
Protection class	
protection class IP	IP20, if the distribution board is installed, with connected conductors
Switching capacity	
switching capacity current	
• according to IEC 61008-1 / rated value	0.5 kA
Dissipation	
power loss [W]	
• for rated value of the current / at AC / in hot operating state / per pole	4.2 W
• maximum	8.4 W
Current	
tripping fault current / rated value	30 mA
operational current	
• at 40 °C / rated value	40 A
• at AC / rated value	40 A
residual current type	A
let-through current / permissible	5 200 A
I _{2t} value / permissible	58 000 A ² ·s
surge current resistance / rated value	1 kA
Product details	
product feature / silicon-free	Yes
product extension / installable / supplementary devices	No

Connections		
connectable conductor cross-section / solid		
• minimum • maximum	0.75 mm ²	35 mm ²
connectable conductor cross-section / stranded		
• minimum • maximum	0.75 mm ²	35 mm ²
tightening torque / with screw-type terminals		
• minimum • maximum	2.5 N·m	3 N·m
position / of power supply cord	top or bottom	
Mechanical Design		
height	90 mm	
width	36 mm	
depth	70 mm	
installation depth	70 mm	
number of modular width units	2	
fastening method	DIN rail (REG)	
mounting position	any	
net weight	194 g	
Environmental conditions		
ambient temperature / during operation		
• minimum • maximum	-5 °C	45 °C
ambient temperature / during storage		
• minimum permissible • maximum permissible	-40 °C	75 °C
number of test cycles / for environmental testing / according to IEC 60068-2-30	28	
General Product Approval	other	Dangerous Good

[Confirmation](#)



[Miscellaneous](#)

[Transport Information](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SV5314-6>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SV5314-6>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SV5314-6

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



