

SIPLUS DP ET200M IM153-1 -40...+70 DGR C START UP  
TEMP -25 DGR C WITH CONFORMAL COATING  
CONFORMITY WITH EN50155 T1 CAT 1 CL A/B BASED  
ON 6ES7153-1AA03-0XB0 . INTERFACE FOR ET 200M,  
FOR MAX. 8 S7-300 MODULES

## Certificates/approvals:

### General Product Approval

[FM](#)

## Further information:

### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

### Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

### CAX-Online-Generator

<http://www.siemens.com/cax>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/6AG1153-1AA03-2XB0/all>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=6AG1153-1AA03-2XB0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=6AG1153-1AA03-2XB0)

last change: