

*** SPARE PART*** OPERATOR PANEL OP17/DP LC DISPLAY,
 BACKLIT LED 4X20/8X40 LINESXCHARACTERS SIMATIC S7, M7
 PROFIBUS-DP 1.5 MBAUD UL/CSA-LISTED



Display	
Design of display	LC display
Color type	Black/white
Line display	
• Number of lines	8
• Number of characters per line	40
Backlighting	
• MTBF backlighting (at 25 °C)	200 000 h
Control elements	
Control elements	Keys
Keyboard fonts	
• Membrane keyboard	Yes
— user-definable label membrane keys	Yes
• Function keys	
— Number of function keys	24
— Number of function keys with LEDs	16
• Numeric/alphabetical input	Yes / No
— hexadecimal keyboard	Yes

• Multi-key operation	No
Connection type	
• Connection for mouse/keyboard/barcode reader	- / - / -
Installation type/mounting	
Mounting position	vertical
maximum permissible angle of inclination without external ventilation	90°
Supply voltage	
Type of supply voltage	24 V DC
UPS connectable (serial)	No
Input current	
Current consumption (rated value)	0.34 A
Power	
Active power input, typ.	10 W
Processor	
Processor type	X86
Drives	
Diskette drive	No
CD-ROM	No
Hard disk	No
Memory	
Type of memory	Flash / RAM
Memory available for user data	256 kbyte
Battery	
Backup battery	
• Backup battery	optional 3.6 V
• Backup time, min.	4 y
Type of output	
Info LED	Yes
Power LED	No
Error LED	Yes
Time of day	
Clock	
• Type	Hardware clock, battery backup, synchronizable
• retentive	Yes
• synchronizable	Yes
Interfaces	

Interfaces/bus type	2 x RS232, 1 x RS422, 1 x RS485 (max. 1.5 Mbit/s)
Number of RS 485 interfaces	1
• Transmission rate, max.	1.5 Mbit/s
USB port	No
PC card slot	No
CF card slot	No
Special interfaces	No
Industrial Ethernet	
• Industrial Ethernet interface	No

Degree and class of protection

IP (at the front)	IP65
IP (rear)	IP20

Standards, approvals, certificates

Certifications	CE, PRS, FM Class I Div. 2, UL, EX Zone 2/22
----------------	--

Ambient conditions

Ambient temperature during storage/transportation	
• min.	-25 °C
• max.	70 °C
Relative humidity	
• Operation, max.	95 %

Operating systems

pre-installed operating system	Rmos
--------------------------------	------

Configuration

Configuration software	
• Configuration tool	ProTool / Lite Version 2.51 or higher (to be ordered separately)

Dimensions

Width of the housing front	240 mm
Height of housing front	204 mm
Overall depth	50 mm

Weights

Weight (without packaging)	0.96 kg
----------------------------	---------

Other

free hotline	Yes
Warranty period	1 y

last modified: 04/29/2017