

*** SPARE PART*** SIMATIC TOUCH PANEL TP170B MONO BLUE MODE STN DISPLAY MPI-/PROFIBUS-DP INTERFACE PRINTER/RS232 INTERFACE SLOT FOR CF-CARD CONFIGURABLE WITH PROTOOL/LITE FROM VERSION V5.2+SP2



Display	
Design of display	STN, 4 blue levels
Screen diagonal	5.7 in
Resolution (pixels)	
• Horizontal image resolution	320 Pixel
• Vertical image resolution	240 Pixel
Backlighting	
• MTBF backlighting (at 25 °C)	50 000 h
Control elements	
Control elements	Touch screen
Keyboard fonts	
• Numeric keyboard	Yes
• alphanumeric keyboard	Yes
• hexadecimal keyboard	Yes
• Multi-key operation	No
Touch operation	
• Design as touch screen	Yes; analog, resistive
Connection type	

- Connection for mouse/keyboard/barcode reader - / - / -

Installation type/mounting

Mounting position	vertical
maximum permissible angle of inclination without external ventilation	35°

Input current

Current consumption (rated value)	0.25 A
-----------------------------------	--------

Power

Active power input, typ.	6 W
--------------------------	-----

Processor

Processor type	RISC 32-bit, 66 MHz
----------------	---------------------

Drives

Diskette drive	No
CD-ROM	No
Hard disk	No

Memory

Type of memory	Flash / RAM
Memory available for user data	768 kbyte

Time of day

Clock	
• Type	Software clock, synchronizable, no battery backup
• retentive	No
• synchronizable	Yes

Interfaces

Interfaces/bus type	TTY optional, 2 x RS232, 1 x RS422, 1 x RS485 (max. 12 Mbit/s)
Number of RS 485 interfaces	1
• Transmission rate, max.	12 Mbit/s
CF card slot	1 x CF card slot

Degree and class of protection

IP (at the front)	IP65
IP (rear)	IP20

Standards, approvals, certificates

Certifications	CE, FM Class I Div. 2, UL, CSA
----------------	--------------------------------

Ambient conditions

Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	60 °C

Relative humidity	
• Operation, max.	85 %
Operating systems	
pre-installed operating system	Windows CE
Configuration	
Configuration software	
• Configuration tool	ProTool / Lite, Version 5.2 SP 1 or higher or WinCC flexible Compact Version 2004 or higher (to be ordered separately)
Languages	
Online languages	
• Number of online/runtime languages	5
Project languages	
• Languages per project	32
Functionality under WinCC (TIA Portal)	
Libraries	Yes
Task planner	Yes
Help system	Yes
• Number of characters per info text	70
• Number of tooltips	0
Message system	
• Number of alarm classes	32
• Number of messages	2 000
• Bit messages	Yes
— Number of bit messages	2 000
• Analog messages	Yes
— Number of analog messages	2 000
• Telegram message procedure Alarm S	No
• System messages HMI	Yes
• System messages PLC	No
• System messages, other (SIMATIC S7, Sinumerik, Simotion, etc.)	No
• Lines	1
• Number of characters per message	80
• Number of process values per message	8
• Acknowledgment groups	
— Number of acknowledgement groups	99
• Message indicator	Yes
• acoustic feedback	No
• First/last value	Yes
Recipe management	
• Number of recipes	100

• Data records per recipe	200
• Entries per data record	200
• Recipe memory	32 KB integrated Flash, expandable
Variables	
• Number of variables per device	1 000
• Number of variables per screen	50
• Number of variables	1 000
• Initial values	1 000
• Type Date & Time	1 000
• Limit values	Yes
• Multiplexing	Yes
• Structures	No
Images	
• Number of configurable images	100
• Permanent window/default	Yes
• Start screen configurable	Yes
• Image selection by PLC	Yes
• Image number in the PLC	Yes
Image objects	
• Text objects	2,000 text elements
• Number of I/O fields per image	0
• Number of date/time fields	30
• Index of screen context	No
• Return	Yes
• Graphics object	Bit maps, icons, icon (full-screen)
— Icons	500
— Icon (full screen)	50
Complex image objects	
• Status/control	Not possible
• dynamic objects	Diagrams, bar graphs, invisible buttons
— Number of objects per project	500
— Number of curve diagrams per image	5
• Methods	Trend
• Bar graphs	
— Number of bars per chart	5
• Sliders	
— Number of slides per image	0
• Pointer instruments	
— Number of analog indicators per image	0
• Limit value lines	Yes
• Number of alphanumerical fields	1 000

— alphanumeric fields per image	100
• Number of numerical fields	1 000
— numerical fields per image	100
• Number of password fields	1 000
• Number of visible switches per project	1 000
— visible switches per image	100
— hidden switches per image	100
• Number of status switches per project	1 000
— Number of status switches per image	100
• Number of selector switches per project	1 000
— Selector switches per image	100
• Number of decade switches per project	0
— Decade switches per image	0
• Number of signal lamps per project	1 000
— Signal lamps per image	100
Attributes for dynamic objects	
• Color change	Yes
• X/Y movement	Yes
• Hide	Yes
• Angle of rotation	No
Lists	
• Number of text lists per project	300
• Number of text lists per image	10
• Number of entries per text list	256
• Number of graphics lists per project	100
• Number of graphic lists per image	10
• Number of entries per graphics list	255
Security	
• Number of user groups	10
• Password export/import	Yes
Data carrier support	
• PC card	No
• CF card	Yes
• Diskette drive	No
• Hard disk	No
• CD-ROM	No
Logging through printer	
• Recording/Printing	Alarms, report (shift report)
Transfer (upload/download)	
• Transfer of configuration	MPI/PROFIBUS DP, serial, automatic transfer recognition
Process coupling	

- Connection to controller S5, S7-200, S7- 300/400, TI 505, Win AC, SINUMERIK, SIMOTION, Allen Bradley (DF1), Mitsubishi (FX), Telemecanique (ADJUST), Modicon (Modbus), for further non-Siemens drivers, see section on "System interfaces"
- S7-200
 - PPI (point-to-point) Yes
 - PPI network No
 - MPI Yes
 - PROFIBUS DP Yes
- S7-300/400
 - MPI Yes
 - PROFIBUS DP Yes
 - PROFINET No
- S5
 - serial Yes
 - PROFIBUS DP Yes
- TI 505 Yes
- Allen Bradley (DF1) Yes
- Allen Bradley (DF485) No
- Mitsubishi (FX) Yes
- Mitsubishi (MP4) Yes
- Telemecanique (ADJUST) Yes
- Telemecanique (Uni-Telway) Yes
- OMRON (LINK/Multilink) No
- Modicon (Modbus) Yes
- GE-Fanuc (SNP) Yes

Functions

- Key repeat No
- TAB sequence Yes
- Calculating functions Yes
- Animate Yes
- Menu tree editor No
- Unit switchover No

Service tools/configuration aids

- Clean screen Yes
- Touch calibration Yes
- Backup/Restore manually Yes
- Simulation Yes
- Device switchover Yes
- Delta transfer Yes
- Monitoring function for battery and memory Yes
- Trace (operation archive) No

Expandability/openness

- Open Platform Program Yes

Peripherals/Options

Peripherals	Printer
• SIMATIC HMI MM memory card: Multi Media Card	No
• SIMATIC HMI SD memory card: Secure Digital memory card	No
• USB memory	No

Dimensions

Width of the housing front	212 mm
Height of housing front	156 mm
Overall depth	45 mm

Weights

Weight (without packaging)	0.7 kg
----------------------------	--------

Other

free hotline	Yes
Warranty period	1 y

last modified: 08/12/2017