

SIMATIC HMI SMART 700 IE, SMART Panel, Touch operation, 7" widescreen TFT display, 65536 colors, RS422/485 interface, Ethernet (RJ45) interface, with CE certificate, configurable from WinCC flexible 2008 SP4 China; contains open-source software, which is provided free of charge see enclosed CD

### General information

Product type designation	700 IE
--------------------------	--------

### Display

Design of display	TFT
Screen diagonal	7 in
Display width	154.1 mm
Display height	85.9 mm
Number of colors	65 536

### Resolution (pixels)

- |                               |           |
|-------------------------------|-----------|
| • Horizontal image resolution | 800 Pixel |
| • Vertical image resolution   | 480 Pixel |

### Backlighting

- |                                |  |
|--------------------------------|--|
| • MTBF backlighting (at 25 °C) | 40 000 h; Half brightness life time (25°C), Max. |
|--------------------------------|--|

### Control elements

#### Keyboard fonts

- |                           |     |
|---------------------------|-----|
| • Function keys           |     |
| — Number of function keys | 0   |
| • Numeric keyboard        | Yes |
| • alphanumeric keyboard   | Yes |

#### Touch operation

- |                          |     |
|--------------------------|-----|
| • Design as touch screen | Yes |
|--------------------------|-----|

### Installation type/mounting

Mounting position	vertical
Mounting in portrait format possible	No
Mounting in landscape format possible	Yes
maximum permissible angle of inclination without external ventilation	35°

### Supply voltage

Type of supply voltage	DC
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V

Input current	
Current consumption (rated value)	0.35 A
Starting current inrush I <sup>2</sup> t	0.5 A <sup>2</sup> ·s
Processor	
Processor type	ARM
Memory	
Flash	Yes
RAM	Yes
Memory available for user data	2 048 kbyte
Type of output	
Acoustics	Sound signal
• Buzzer	Yes
Time of day	
Clock	
• Hardware clock (real-time)	No
• Software clock	Yes
• retentive	No
• synchronizable	Yes; do the synchronization via PLC-jobs
Interfaces	
Number of industrial Ethernet interfaces	1
Number of RS 485 interfaces	1
Number of RS 422 interfaces	1
Number of RS 232 interfaces	0
Number of USB interfaces	0
Number of 20 mA interfaces (TTY)	0
Number of parallel interfaces	0
Number of other interfaces	0
Number of SD card slots	0
Industrial Ethernet	
• Industrial Ethernet status LED	2
Protocols	
PROFINET	No
PROFIBUS	No
MPI	No
Protocols (Ethernet)	
• TCP/IP	Yes
• DHCP	Yes
• SNMP	No
• DCP	No
• LLDP	No

<b>Further protocols</b>	
• MODBUS	Yes
<b>Degree and class of protection</b>	
IP (at the front)	IP65
IP (rear)	IP20
<b>Standards, approvals, certificates</b>	
CE mark	Yes
<b>Marine approval</b>	
• Germanischer Lloyd (GL)	No
• American Bureau of Shipping (ABS)	No
• Bureau Veritas (BV)	No
• Det Norske Veritas (DNV)	No
• Lloyds Register of Shipping (LRS)	No
• Nippon Kaiji Kyokai (Class NK)	No
• Polski Rejestr Statkow (PRS)	No
<b>Ambient conditions</b>	
<b>Ambient temperature during operation</b>	
• Operation (vertical installation)	0 to +50 °C
— For vertical installation, min.	0 °C
— For vertical installation, max.	50 °C
• Operation (max. tilt angle)	0 to +40 °C
— At maximum tilt angle, min.	0 °C
— At maximum tilt angle, min.	40 °C
<b>Relative humidity</b>	
• Operation, max.	90 %
<b>Configuration</b>	
Message indicator	Yes
Alarm system (incl. buffer and acknowledgment)	Yes
Process value display (output)	Yes
Process value default (input) possible	Yes
Recipe management	Yes
<b>Configuration software</b>	
• WinCC flexible Standard	Yes; WinCC flexible 2008 SP4 CHINA
<b>Languages</b>	
<b>Online languages</b>	
• Number of online/runtime languages	5
<b>Project languages</b>	
• Languages per project	32
<b>Functionality under WinCC (TIA Portal)</b>	
Libraries	Yes

Task planner	Yes
• time-controlled	No
• task-controlled	Yes
Help system	Yes
• Number of characters per info text	320
<b>Message system</b>	
• Number of alarm classes	32
• Bit messages	
— Number of bit messages	200
• Analog messages	
— Number of analog messages	15
• System messages HMI	Yes
• Number of characters per message	80
• Number of process values per message	8
• Message indicator	Yes
• Message buffer	Ring buffer (n x 256 entries), retentive, maintenance-free
— Number of entries	256
— Circulating buffer	Yes
— retentive	Yes
<b>Recipe management</b>	
• Number of recipes	5
• Data records per recipe	20
• Entries per data record	20
• Size of internal recipe memory	40 kbyte
• Recipe memory expandable	No
<b>Variables</b>	
• Number of variables per device	800
• Number of variables per screen	100
• Limit values	Yes
• Multiplexing	Yes
• Structures	No
• Arrays	Yes
<b>Images</b>	
• Number of configurable images	100
• Permanent window/default	Yes; No permanent window can be configured
• Global image	Yes
• Image selection by PLC	Yes
• Image number in the PLC	Yes
<b>Image objects</b>	
• Text fields	Yes
• I/O fields	Yes

• Graphic I/O fields (graphics list)	Yes
• Symbolic I/O fields (text list)	Yes
• Date/time fields	Yes
• Switches	Yes
• Buttons	Yes
• Graphic display	Yes
<b>Complex image objects</b>	
• Number of complex objects per screen	5
• Alarm view	Yes
• Trend view	Yes
• User view	Yes
• Status/control	No
• Sm@rtClient view	No
• Recipe view	Yes
• f(x) trend view	No
• System diagnostics view	No
• Media Player	No
• Bar graphs	Yes
• Sliders	No
• Pointer instruments	No
• Analog/digital clock	No
<b>Lists</b>	
• Number of text lists per project	150
• Number of graphics lists per project	100
<b>Security</b>	
• Number of user groups	50
• Number of user rights	32
• Number of users	50
• Password export/import	No
<b>Character sets</b>	
• Keyboard fonts	US American (English)
— US English	Yes
<b>Transfer (upload/download)</b>	
• MPI/PROFIBUS DP	No
• USB	No
• Ethernet	Yes
• using external storage medium	No
<b>Process coupling</b>	
• S7-1200	No
• S7-200	Yes
• S7-300/400	No

- LOGO! Yes
- WinAC No
- SINUMERIK No
- SIMOTION No
- Allen Bradley (DF1) No
- Mitsubishi (FX) Yes
- OMRON (LINK/Multilink) Yes
- Modicon (Modbus) Yes

**Service tools/configuration aids**

- Backup/Restore manually Yes
- Simulation Yes
- Device switchover Yes

**Peripherals/Options**

- Peripherals none
- Printer No
  - SIMATIC HMI MM memory card: Multi Media Card No
  - SIMATIC HMI SD memory card: Secure Digital memory card No
  - USB memory No

**Mechanics/material**

- Enclosure material (front)
- Plastic Yes
  - Aluminum No

**Dimensions**

- Width of the housing front 213 mm
- Height of housing front 159 mm
- Overall depth 40.5 mm

**last modified:** 08/30/2018

