



SIMATIC ET 200SP HA, ET 200SP, Power module Ex-PM E, 24V 0.8A, WxH: 50mm x 117mm, suitable for BaseUnit type W0

General information	
Product type designation	Ex-PM-E
usable BaseUnits	BU type W0
Product function	
<ul style="list-style-type: none"> I&M data 	Yes; Asset data
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption, max.	1.4 A
from load voltage L+ (without load), max.	50 mA
output voltage / header	
Rated value (DC)	24 V
Overvoltage protection	Yes
Output current	
horizontal installation	
<ul style="list-style-type: none"> up to 60 °C, max. 	0.8 A
<ul style="list-style-type: none"> up to 70 °C, max. 	0.6 A
vertical installation	
<ul style="list-style-type: none"> up to 50 °C, max. 	0.8 A
<ul style="list-style-type: none"> up to 60 °C, max. 	0.6 A
Power	
Power available from the backplane bus	100 mW
Power loss	
Power loss, typ.	4.8 W
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Diagnoses	
<ul style="list-style-type: none"> Diagnostic information readable 	Yes
<ul style="list-style-type: none"> missing load voltage 	Yes
Diagnostics indication LED	
<ul style="list-style-type: none"> MAINT LED 	Yes; Yellow LED
<ul style="list-style-type: none"> Monitoring of the supply voltage (PWR-LED) 	Yes; green PWR LED
<ul style="list-style-type: none"> for module diagnostics 	Yes; green/red DIAG LED
Ex(i) characteristics	
Module for Ex(i) protection	Yes

maximum values for connecting terminals for gas group IIC	
<ul style="list-style-type: none"> Um (voltage at non-intrinsically safe connecting terminals), max. 	60 V; power supply and backplane bus
Potential separation	
primary/secondary	Yes
Isolation	
Isolation tested with	further information on insulation can be found in the "ET 200SP HA / ET 200SP modules for devices in hazardous areas" System Manual
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> min. max. 	-40 °C 70 °C; with derating
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> Installation altitude above sea level, max. 	2 000 m
Dimensions	
Width	50 mm
Height	114 mm
Depth	67.5 mm
Weights	
Weight, approx.	182 g
last modified:	6/1/2021 