



Figure similar

SIMATIC ET 200SP, digital input module, DI 8x 24 V DC High Feature, input type 3 (IEC 61131), sink input, (PNP, sink input) Packing unit: 1 unit, suitable for BU type A0, color code CC01, input delay 0.05..20 ms; Channel diagnostics for: Encoder power supply short circuit, wire break, supply voltage, channel fault LED

| General information | |
|---|--|
| Product type designation | DI 8x24 V DC HF |
| HW functional status | From FS07 |
| Firmware version | |
| • FW update possible | Yes |
| usable BaseUnits | BU type A0 |
| Color code for module-specific color identification plate | CC01 |
| Product function | |
| • I&M data | Yes; I&M0 to I&M3 |
| • Isochronous mode | Yes |
| Engineering with | |
| • STEP 7 TIA Portal configurable/integrated from version | V13 SP1 / - |
| • STEP 7 configurable/integrated from version | V5.5 / - |
| • PCS 7 configurable/integrated from version | V8.1 SP1 |
| • PROFIBUS from GSD version/GSD revision | One GSD file each, Revision 3 and 5 and higher |
| • PROFINET from GSD version/GSD revision | GSDML V2.3 |
| Operating mode | |
| • DI | Yes |
| • Counter | No |
| • Oversampling | No |
| • MSI | Yes |
| Supply voltage | |
| Rated value (DC) | 24 V |
| permissible range, lower limit (DC) | 19.2 V |
| permissible range, upper limit (DC) | 28.8 V |
| Reverse polarity protection | Yes |
| Input current | |
| Current consumption (rated value) | 20 mA |
| Current consumption, max. | 39 mA |
| Encoder supply | |
| Number of outputs | 8 |
| Output voltage, min. | 19.2 V |
| Short-circuit protection | Yes |
| 24 V encoder supply | |
| • 24 V | Yes |
| • Short-circuit protection | Yes; per channel, electronic |
| • Output current per channel, max. | 700 mA |
| • Output current per module, max. | 700 mA |
| Power loss | |

| | |
|---|---|
| Power loss, typ. | 1.5 W; 24 V, 8 inputs supplied via encoder supply |
| Address area | |
| Address space per module | |
| • Inputs | 1 byte; + 1 byte for QI information |
| Hardware configuration | |
| Automatic encoding | Yes |
| • Mechanical coding element | Yes |
| • Type of mechanical coding element | Type A |
| Submodules | |
| • Number of configurable submodules, max. | 4 |
| Selection of BaseUnit for connection variants | |
| • 1-wire connection | BU type A0 |
| • 2-wire connection | BU type A0 |
| • 3-wire connection | BU type A0 with AUX terminals or potential distributor module |
| • 4-wire connection | BU type A0 + Potential distributor module |
| Digital inputs | |
| Number of digital inputs | 8 |
| Digital inputs, parameterizable | Yes |
| Source/sink input | P-reading |
| Input characteristic curve in accordance with IEC 61131, type 3 | Yes |
| Pulse extension | Yes; Pulse duration from 4 µs |
| • Length | 2 s; 50 ms, 100 ms, 200 ms, 500 ms, 1 s, 2 s |
| Edge evaluation | Yes; rising edge, falling edge, edge change |
| Input voltage | |
| • Rated value (DC) | 24 V |
| • for signal "0" | -30 to +5 V |
| • for signal "1" | +11 to +30V |
| Input current | |
| • for signal "1", typ. | 2.5 mA |
| Input delay (for rated value of input voltage) | |
| for standard inputs | |
| — parameterizable | Yes; 0.05 / 0.1 / 0.4 / 0.8 / 1.6 / 3.2 / 12.8 / 20 ms (in each case + delay of 30 to 500 µs, depending on line length) |
| — at "0" to "1", min. | 0.05 ms |
| — at "0" to "1", max. | 20 ms |
| — at "1" to "0", min. | 0.05 ms |
| — at "1" to "0", max. | 20 ms |
| Cable length | |
| • shielded, max. | 1 000 m |
| • unshielded, max. | 600 m |
| Encoder | |
| Connectable encoders | |
| • 2-wire sensor | Yes |
| — permissible quiescent current (2-wire sensor), max. | 1.5 mA |
| Isochronous mode | |
| Filtering and processing time (TCI), min. | 420 µs |
| Bus cycle time (TDP), min. | 500 µs |
| Jitter, max. | 8 µs |
| Interrupts/diagnostics/status information | |
| Diagnostics function | Yes |
| Alarms | |
| • Diagnostic alarm | Yes; channel by channel |
| • Hardware interrupt | Yes; Parameterizable, channels 0 to 7 |
| Diagnoses | |
| • Diagnostic information readable | Yes |
| • Monitoring the supply voltage | Yes |
| — parameterizable | Yes |
| • Monitoring of encoder power supply | Yes; channel by channel |
| • Wire-break | Yes; Channel by channel, optional protective circuit for preventing wire-break diagnostics in the case of simple encoder contacts: 25 kOhm to 45 kOhm |
| • Short-circuit | Yes; channel by channel |

| | |
|--|--|
| Diagnostics indication LED | |
| <ul style="list-style-type: none"> Monitoring of the supply voltage (PWR-LED) Channel status display for channel diagnostics for module diagnostics | <p>Yes; green PWR LED</p> <p>Yes; green LED</p> <p>Yes; red LED</p> <p>Yes; green/red DIAG LED</p> |
| Potential separation | |
| Potential separation channels | |
| <ul style="list-style-type: none"> between the channels between the channels and backplane bus between the channels and the power supply of the electronics | <p>No</p> <p>Yes</p> <p>No</p> |
| Isolation | |
| Isolation tested with | 707 V DC (type test) |
| Standards, approvals, certificates | |
| Suitable for safety functions | No |
| Ambient conditions | |
| Ambient temperature during operation | |
| <ul style="list-style-type: none"> horizontal installation, min. horizontal installation, max. vertical installation, min. vertical installation, max. | <p>-30 °C; < 0 °C as of FS07</p> <p>60 °C</p> <p>-30 °C; < 0 °C as of FS07</p> <p>50 °C</p> |
| Altitude during operation relating to sea level | |
| <ul style="list-style-type: none"> Installation altitude above sea level, max. | 5 000 m; Restrictions for installation altitudes > 2 000 m, see manual |
| Dimensions | |
| Width | 15 mm |
| Height | 73 mm |
| Depth | 58 mm |
| Weights | |
| Weight, approx. | 28 g |

last modified:

10/13/2023 