



SIMATIC ET 200SP, Analog input module, AI 2x U/I 2-/4-wire High Speed, suitable for BU type A0, A1, Color code CC00, channel diagnostics, 16 bit, +/-0.3%

General information	
Product type designation	AI 2xU/I 2-/4-wire HS
HW functional status	From FS07
Firmware version	
• FW update possible	Yes
usable BaseUnits	BU type A0, A1
Color code for module-specific color identification plate	CC00
Product function	
• I&M data	Yes; I&M0 to I&M3
• Isochronous mode	Yes
• Measuring range scalable	No
• Scalable measured values	No
• Adjustment of measuring range	No
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	V13 SP1
• STEP 7 configurable/integrated from version	V5.5 SP3 / -
• PROFIBUS from GSD version/GSD revision	One GSD file each, Revision 3 and 5 and higher
• PROFINET from GSD version/GSD revision	GSDML V2.3
Operating mode	
• Oversampling	Yes; 2 channels per module
• MSI	No
CiR - Configuration in RUN	
Reparameterization possible in RUN	Yes
Calibration possible in RUN	No
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption (rated value)	39 mA; without sensor supply
Encoder supply	
24 V encoder supply	
• 24 V	Yes; For current measurement
• Short-circuit protection	Yes
• Output current, max.	20 mA; max. 50 mA per channel for a duration < 10 s
Power loss	
Power loss, typ.	0.95 W; without sensor supply
Address area	
Address space per module	

- Address space per module, max.

4 byte; + 1 byte for QI information (32 bytes in the oversampling operating mode)

### Hardware configuration

Automatic encoding	Yes
<ul style="list-style-type: none"> <li>• Mechanical coding element</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Type of mechanical coding element</li> </ul>	Type A

### Selection of BaseUnit for connection variants

<ul style="list-style-type: none"> <li>• 2-wire connection</li> </ul>	BU type A0, A1
<ul style="list-style-type: none"> <li>• 4-wire connection</li> </ul>	BU type A0, A1

### Analog inputs

Number of analog inputs	2; Differential inputs
<ul style="list-style-type: none"> <li>• For current measurement</li> </ul>	2
<ul style="list-style-type: none"> <li>• For voltage measurement</li> </ul>	2

permissible input voltage for voltage input (destruction limit), max. 30 V

permissible input current for current input (destruction limit), max. 50 mA

Cycle time (all channels), min. 125  $\mu$ s

Analog input with oversampling	Yes
<ul style="list-style-type: none"> <li>• Values per cycle, max.</li> </ul>	16
<ul style="list-style-type: none"> <li>• Resolution, min.</li> </ul>	50 $\mu$ s

### Input ranges (rated values), voltages

<ul style="list-style-type: none"> <li>• 0 to +10 V <ul style="list-style-type: none"> <li>— Input resistance (0 to 10 V)</li> </ul> </li> </ul>	Yes; 15 bit 75 k $\Omega$
<ul style="list-style-type: none"> <li>• 1 V to 5 V <ul style="list-style-type: none"> <li>— Input resistance (1 V to 5 V)</li> </ul> </li> </ul>	Yes; 13 bit 75 k $\Omega$
<ul style="list-style-type: none"> <li>• -10 V to +10 V <ul style="list-style-type: none"> <li>— Input resistance (-10 V to +10 V)</li> </ul> </li> </ul>	Yes; 16 bit incl. sign 75 k $\Omega$
<ul style="list-style-type: none"> <li>• -5 V to +5 V <ul style="list-style-type: none"> <li>— Input resistance (-5 V to +5 V)</li> </ul> </li> </ul>	Yes; 15 bit incl. sign 75 k $\Omega$

### Input ranges (rated values), currents

<ul style="list-style-type: none"> <li>• 0 to 20 mA <ul style="list-style-type: none"> <li>— Input resistance (0 to 20 mA)</li> </ul> </li> </ul>	Yes; 15 bit 130 $\Omega$
<ul style="list-style-type: none"> <li>• -20 mA to +20 mA <ul style="list-style-type: none"> <li>— Input resistance (-20 mA to +20 mA)</li> </ul> </li> </ul>	Yes; 16 bit incl. sign 130 $\Omega$
<ul style="list-style-type: none"> <li>• 4 mA to 20 mA <ul style="list-style-type: none"> <li>— Input resistance (4 mA to 20 mA)</li> </ul> </li> </ul>	Yes; 14 bit 130 $\Omega$

### Cable length

<ul style="list-style-type: none"> <li>• shielded, max.</li> </ul>	1 000 m; 200 m for voltage measurement
--------------------------------------------------------------------	----------------------------------------

### Analog value generation for the inputs

Measurement principle Actual value encryption (successive approximation)

### Integration and conversion time/resolution per channel

<ul style="list-style-type: none"> <li>• Resolution with overrange (bit including sign), max.</li> </ul>	16 bit
<ul style="list-style-type: none"> <li>• Interference voltage suppression for interference frequency <math>f_1</math> in Hz</li> </ul>	No
<ul style="list-style-type: none"> <li>• Conversion time (per channel)</li> </ul>	10 $\mu$ s

### Smoothing of measured values

<ul style="list-style-type: none"> <li>• Number of smoothing levels</li> </ul>	7; none; 2-/4-/8-/16-/32-/64-fold
<ul style="list-style-type: none"> <li>• parameterizable</li> </ul>	Yes

### Encoder

#### Connection of signal encoders

<ul style="list-style-type: none"> <li>• for voltage measurement</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• for current measurement as 2-wire transducer <ul style="list-style-type: none"> <li>— Burden of 2-wire transmitter, max.</li> </ul> </li> </ul>	Yes 650 $\Omega$
<ul style="list-style-type: none"> <li>• for current measurement as 4-wire transducer</li> </ul>	Yes

### Errors/accuracies

Linearity error (relative to input range), (+/-) 0.03 %

Temperature error (relative to input range), (+/-) 0.01 %/K

Crosstalk between the inputs, min. -50 dB

Repeat accuracy in steady state at 25 °C (relative to input range), (+/-) 0.1 %

Operational error limit in overall temperature range

• Voltage, relative to input range, (+/-)	0.3 %
• Current, relative to input range, (+/-)	0.3 %
<b>Basic error limit (operational limit at 25 °C)</b>	
• Voltage, relative to input range, (+/-)	0.2 %
• Current, relative to input range, (+/-)	0.2 %
<b>Interference voltage suppression for <math>f = n \times (f_1 \pm 1 \%)</math>, <math>f_1</math> = interference frequency</b>	
• Common mode voltage, max.	35 V
• Common mode interference, min.	90 dB
<b>Isochronous mode</b>	
Filtering and processing time (TCI), min.	80 $\mu$ s
Bus cycle time (TDP), min.	125 $\mu$ s; Starting from firmware Version V2.0.1
<b>Interrupts/diagnostics/status information</b>	
<b>Alarms</b>	
• Diagnostic alarm	Yes
• Limit value alarm	Yes; two upper and two lower limit values in each case
<b>Diagnoses</b>	
• Wire-break	Yes; channel-by-channel, at 4 to 20 mA only
• Short-circuit	Yes; channel-by-channel, at 1 to 5 V or for current measuring ranges short-circuit in encoder supply
• Group error	Yes
• Overflow/underflow	Yes
<b>Diagnostics indication LED</b>	
• Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
• Channel status display	Yes; green LED
• for channel diagnostics	Yes; red LED
• for module diagnostics	Yes; green/red DIAG LED
<b>Potential separation</b>	
<b>Potential separation channels</b>	
• between the channels	Yes
• between the channels and backplane bus	Yes
• between the channels and the power supply of the electronics	Yes
<b>Isolation</b>	
Isolation tested with	707 V DC (type test)
<b>Ambient conditions</b>	
<b>Ambient temperature during operation</b>	
• horizontal installation, min.	-30 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	-30 °C
• vertical installation, max.	50 °C
<b>Altitude during operation relating to sea level</b>	
• Installation altitude above sea level, max.	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
<b>Dimensions</b>	
Width	15 mm
Height	73 mm
Depth	58 mm
<b>Weights</b>	
Weight, approx.	32 g
<b>last modified:</b>	8/16/2023 