



SIMATIC DP, ELECTRONIC MODULE FOR ET 200S, 2 AO I 15 MM WIDE, +/-20 MA; 13 BIT + SIGN, 4 .. 20 MA; 13 BIT CYCLE TIME < 1 MS WITH LED SF (GROUP FAULT)

### Supply voltage

#### Load voltage L+

- Rated value (DC) 24 V; From power module
- Reverse polarity protection Yes

### Input current

|   |        |
|---|--------|
| from load voltage L+ (without load), max. | 150 mA |
| from backplane bus 3.3 V DC, max.         | 10 mA  |

### Power losses

|                  |     |
|------------------|-----|
| Power loss, max. | 2 W |
|------------------|-----|

### Address area

|                                  |        |
|----------------------------------|--------|
| Address space per module         |        |
| • Address space per module, max. | 4 byte |

### Analog outputs

|                                       |        |
|---------------------------------------|--------|
| Number of analog outputs              | 2      |
| Current output, no-load voltage, max. | 18 V   |
| Cycle time (all channels) max.        | 1.5 ms |

#### Output ranges, current

- -20 mA to +20 mA Yes
- 4 mA to 20 mA Yes

#### Connection of actuators

- for current output two-wire connection Yes
- for current output four-wire connection No

#### Load impedance (in rated range of output)

|   |  |
|---|--|
| • with current outputs, max.  | 500 Ω  |
| • with current outputs, inductive load, max.                              | 1 mH   |
| Destruction limits against externally applied voltages and currents       |  |
| • Voltages at the outputs towards MANA                                    | 15 V; max. 15 V continuous; 75 V for max. 1 s (mark to space ratio 1:20) |
| • Current, max.   | 50 mA; DC  |
| Cable length  |  |
| • shielded, max.  | 200 m  |
| Analog value generation for the outputs                                   |  |
| Integration and conversion time/resolution per channel                    |  |
| • Resolution with overrange (bit including sign), max.                    | 14 bit; 4 to 20 mA: 13 bits, +/-20 mA: 14 bits                           |
| Settling time   |  |
| • for resistive load  | 0.1 ms   |
| • for capacitive load   | 0.5 ms   |
| • for inductive load  | 0.5 ms   |
| Errors/accuracies   |  |
| Output ripple (based on output area, bandwidth 0 to 50 kHz), (+/-)        | 0.02 %   |
| Linearity error (relative to output range), (+/-)                         | 0.02 %   |
| Temperature error (relative to output range), (+/-)                       | 0.01 %/K   |
| Repeat accuracy in steady state at 25 °C (relative to output area), (+/-) | 0.05 %   |
| Operational limit in overall temperature range                            |  |
| • Current, relative to output area, (+/-)                                 | 0.5 %  |
| Basic error limit (operational limit at 25 °C)                            |  |
| • Current, relative to output area, (+/-)                                 | 0.3 %  |
| Interrupts/diagnostics/status information                                 |  |
| Substitute values connectable   | Yes; 0 to 65535 (range of values must be within the rated range)         |
| Diagnostic messages   |  |
| • Wire break  | Yes  |
| • Group error   | Yes  |
| Diagnostics indication LED  |  |
| • Group error SF (red)  | Yes  |
| Parameter   |  |
| Remark  | 7 byte   |
| Output type/range   | deactivated / +/-20 mA / 4 to 20 mA                                      |
| Diagnosis: wire break   | Disable / enable   |
| Group diagnostics   | Disable / enable   |
| Behavior on CPU/Master STOP   | Output current and de-energized/substitute a value/keep last value       |

|  |               |
|--|---------------|
| <b>Ex(i) characteristics</b>                   |               |
| Max. values of output circuits (per channel)   |               |
| • Uo (output no-load voltage), max.            | 18 V          |
| <b>Potential separation</b>                    |               |
| Galvanic isolation analog outputs              |               |
| • between the channels                         | No            |
| • between the channels and the backplane bus   | Yes           |
| • between the channels and the load voltage L+ | Yes           |
| <b>Permissible potential difference</b>        |               |
| between MANA and M internally (UISO)           | 75V DC/60V AC |
| <b>Dimensions</b>                              |               |
| Width  | 15 mm         |
| Height   | 81 mm         |
| Depth  | 52 mm         |
| <b>Weights</b>                                 |               |
| Weight, approx.                                | 40 g          |
| <b>last modified:</b>                          | 20.04.2015    |