

SIMATIC ET 200SP, TM timer DIDQ 10x 24V time-controlled digital inputs and outputs 4 DI, 6DQ with time stamp Count, PWM, oversampling



General information	
Product type designation	TM Timer DIDQ 10x24V
usable BaseUnits	BU type A0
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; I&M 0
<ul style="list-style-type: none"> <li>Isochronous mode</li> </ul>	Yes
Engineering with	
<ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated as of version</li> </ul>	V13 Update 3
<ul style="list-style-type: none"> <li>STEP 7 configurable/integrated as of version</li> </ul>	V5.5 SP3 / -
Supply voltage	
Load voltage L+	
<ul style="list-style-type: none"> <li>Rated value (DC)</li> </ul>	24 V
<ul style="list-style-type: none"> <li>permissible range, lower limit (DC)</li> </ul>	19.2 V
<ul style="list-style-type: none"> <li>permissible range, upper limit (DC)</li> </ul>	28.8 V
<ul style="list-style-type: none"> <li>Reverse polarity protection</li> </ul>	Yes; against destruction
Input current	
Current consumption, max.	50 mA; without load

Encoder supply	
Number of outputs	1
24 V encoder supply	
<ul style="list-style-type: none"> <li>• 24 V</li> </ul>	Yes; L+ (-0.8 V)
<ul style="list-style-type: none"> <li>• Short-circuit protection</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Output current, max.</li> </ul>	500 mA; Observe derating
Power loss	
Power loss, typ.	1.5 W
Address area	
Address space per module	
<ul style="list-style-type: none"> <li>• Inputs</li> </ul>	26 byte
<ul style="list-style-type: none"> <li>• Outputs</li> </ul>	32 byte
Digital inputs	
Number of digital inputs	4
Digital inputs, parameterizable	Yes
Input characteristic curve in accordance with IEC 61131, type 3	Yes
Digital input functions, parameterizable	
<ul style="list-style-type: none"> <li>• Digital input with time stamp <ul style="list-style-type: none"> <li>— Number, max.</li> </ul> </li> </ul>	Yes 4
<ul style="list-style-type: none"> <li>• Counter <ul style="list-style-type: none"> <li>— Number, max.</li> </ul> </li> </ul>	Yes 3
<ul style="list-style-type: none"> <li>• Counter for incremental encoder <ul style="list-style-type: none"> <li>— Number, max.</li> </ul> </li> </ul>	Yes 1
<ul style="list-style-type: none"> <li>• Digital input with oversampling <ul style="list-style-type: none"> <li>— Number, max.</li> </ul> </li> </ul>	Yes 4
<ul style="list-style-type: none"> <li>• HW enable for digital input <ul style="list-style-type: none"> <li>— Number, max.</li> </ul> </li> </ul>	Yes 1
<ul style="list-style-type: none"> <li>• HW enable for digital output <ul style="list-style-type: none"> <li>— Number, max.</li> </ul> </li> </ul>	Yes 3
Input voltage	
<ul style="list-style-type: none"> <li>• Type of input voltage</li> </ul>	DC
<ul style="list-style-type: none"> <li>• Rated value (DC)</li> </ul>	24 V
<ul style="list-style-type: none"> <li>• for signal "0"</li> </ul>	-5 ... +5 V
<ul style="list-style-type: none"> <li>• for signal "1"</li> </ul>	+11 to +30V
<ul style="list-style-type: none"> <li>• permissible voltage at input, min.</li> </ul>	-30 V; -5 V continuous, -30 V brief reverse polarity protection
<ul style="list-style-type: none"> <li>• permissible voltage at input, max.</li> </ul>	30 V
Input current	
<ul style="list-style-type: none"> <li>• for signal "1", typ.</li> </ul>	2.5 mA
Input delay (for rated value of input voltage)	
<ul style="list-style-type: none"> <li>• Minimum pulse width for program reactions</li> </ul>	3 µs for parameterization "none"

for standard inputs	
— parameterizable	Yes; none / 0.05 / 0.1 / 0.4 / 0.8 ms
— at "0" to "1", min.	4 $\mu$ s
— at "1" to "0", min.	4 $\mu$ s
Cable length	
• shielded, max.	1 000 m; Depending on sensor, cable quality and rate of change
• unshielded, max.	600 m; Depending on sensor, cable quality and rate of change
Digital outputs	
Type of digital output	Transistor
Number of digital outputs	6
Current-sinking	Yes; With High Speed output
Current-sourcing	Yes
Digital outputs, parameterizable	Yes
Short-circuit protection	Yes; electronic/thermal
• Response threshold, typ.	1.7 A with Standard output, 0.5 A with High Speed output
Limitation of inductive shutdown voltage to	-0.8 V
Digital output functions, parameterizable	
• Digital output with time stamp	Yes
— Number, max.	6
• PWM output	Yes
— Number, max.	6
• Digital output with oversampling	Yes
— Number, max.	6
Switching capacity of the outputs	
• with resistive load, max.	0.5 A; 0.1 A with High Speed output
• on lamp load, max.	5 W; 1 W with High Speed output
Load resistance range	
• lower limit	48 $\Omega$ ; 240 ohm with High Speed output
• upper limit	12 k $\Omega$
Output voltage	
• Type of output voltage	DC
• for signal "0", max.	1 V; With High Speed output
• for signal "1", min.	23.2 V; L+ (-0.8 V)
Output current	
• for signal "1" rated value	0.5 A; 0.1 A with High Speed output, observe derating
• for signal "1" permissible range, max.	0.6 A; 0.12 A with High Speed output, observe derating
• for signal "1" minimum load current	2 mA
• for signal "0" residual current, max.	0.5 mA
Output delay with resistive load	
• "0" to "1", max.	1 $\mu$ s; With High Speed output, 5 $\mu$ s with Standard output
• "1" to "0", max.	1 $\mu$ s; With High Speed output, 6 $\mu$ s with Standard output

<b>Switching frequency</b>	
• with resistive load, max.	10 kHz
• on lamp load, max.	10 Hz
<b>Total current of the outputs</b>	
• Current per module, max.	3.5 A; Observe derating
<b>Cable length</b>	
• shielded, max.	1 000 m; Depending on load and cable quality
• unshielded, max.	600 m; Depending on load and cable quality
<b>Encoder</b>	
<b>Connectable encoders</b>	
• Incremental encoder (asymmetrical)	Yes
• 24 V initiator	Yes
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA
<b>Encoder signals, incremental encoder (asymmetrical)</b>	
• Input voltage	24 V
• Input frequency, max.	50 kHz
• Counting frequency, max.	200 kHz; with quadruple evaluation
• Cable length, shielded, max.	600 m; Depending on input frequency, encoder and cable quality; max. 200 m at 50 kHz
• Incremental encoder with A/B tracks, 90° phase offset	Yes
• Pulse encoder	Yes
<b>Encoder signal 24 V</b>	
— permissible voltage at input, min.	-30 V
— permissible voltage at input, max.	30 V
<b>Interface types</b>	
• Input characteristic curve in accordance with IEC 61131, type 3	Yes
<b>Isochronous mode</b>	
Bus cycle time (TDP), min.	375 µs
Jitter, max.	1 µs
<b>Interrupts/diagnostics/status information</b>	
Diagnostics function	Yes
Substitute values connectable	Yes
<b>Alarms</b>	
• Diagnostic alarm	Yes
<b>Diagnostic messages</b>	
• Monitoring the supply voltage	Yes
• Short-circuit	Yes

Diagnostics indication LED	
• Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
• Channel status display	Yes
• for module diagnostics	Yes; green/red DIAG LED
Integrated Functions	
Number of counters	3
Counting frequency (counter) max.	200 kHz; with quadruple evaluation
Counting functions	
• Continuous counting	Yes
Potential separation	
Potential separation channels	
• between the channels and backplane bus	Yes
Isolation	
Isolation tested with	707 V DC (type test)
Ambient conditions	
Ambient temperature during operation	
• horizontal installation, min.	-30 °C
• horizontal installation, max.	60 °C; Observe derating
• vertical installation, min.	-30 °C
• vertical installation, max.	50 °C; Observe derating
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	2 000 m; On request: Installation altitudes greater than 2 000 m
Decentralized operation	
to SIMATIC S7-1500	Yes
Dimensions	
Width	15 mm
Height	73 mm
Depth	58 mm
Weights	
Weight, approx.	45 g
<b>last modified:</b>	05/13/2020