SIEMENS

Data sheet 6ES7155-6BA00-0CN0

*** Spare part *** SIMATIC ET 200SP, PROFIBUS IM bundle, IM 155-6DP HF, max. 32 I/O modules and 16 ET 200AL modules, multi hot swap, bundle consists of: Interface module (6ES7155-6BU00-0CN0), server module (6ES7193-6PA00-0AA0), PROFIBUS connector (6ES7972-0BB70-0XA0)

General information	
Product type designation	IM 155-6 DP HF
Firmware version	V3.1
Product function	
• I&M data	Yes; I&M0 to I&M3
• Module swapping during operation (hot swapping)	Yes; Multi-hot swapping
Engineering with	
• STEP 7 TIA Portal configurable/integrated as of version	V13 SP1
• STEP 7 configurable/integrated as of version	V5.5 SP4 and higher
• PROFIBUS as of GSD version/GSD revision	One GSD file each, Revision 3 and 5 and higher

Configuration control	
via dataset	Yes

Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V

Subject to change without notice
© Copyright Siemens

Reverse polarity protection	Yes
Mains buffering	
• Mains/voltage failure stored energy time	5 ms

Input current

Current consumption, max.	250 mA
Inrush current, max.	4.5 A

Power loss

Power loss, typ.	1.5 W

Address area

Address space per module	
• Address space per module, max.	32 byte; per input / output
Address space per station	
• Address space per station, max.	244 byte; per input / output

Hardware configuration

Rack	
• Modules per rack, max.	32; + 16 ET 200AL modules

Interfaces

Number of PROFIBUS interfaces	1

1. Interface

Interface types	
• RS 485	Yes
• Output current of the interface, max.	90 mA
Protocols	
• PROFIBUS DP slave	Yes

Interface types

RS 485	
• Transmission rate, max.	12 Mbit/s

Protocols

PROFIBUS DP	
Services	
— SYNC capability	Yes
— FREEZE capability	Yes
— DPV0	Yes
— DPV1	Yes

Isochronous mode

Isochronous operation (application synchronized up to terminal)	No

Interrupts/diagnostics/status information

Subject to change without notice
© Copyright Siemens

Status indicator	Yes
Alarms	Yes
Diagnostics function	Yes
Diagnostics indication LED	
• RUN LED	Yes; Green LED
• ERROR LED	Yes; Red LED
• MAINT LED	Yes; Yellow LED
• Monitoring of the supply voltage (PWR-LED)	Yes; Green PWR LED
• Connection display DP	Yes; Green DP LED

Potential separation	
between backplane bus and electronics	No
between PROFIBUS DP and all other circuit components	Yes
between supply and all other circuits	Yes

Permissible potential difference	
between different circuits	75 V DC/60 V AC (base isolation)

Isolation	
Isolation tested with	707 V DC (type test)

Ambient conditions	
Ambient temperature during operation	
• horizontal installation, min.	0 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	0 °C
• vertical installation, max.	50 °C

Connection method	
ET-Connection	
• via BU/BA Send	Yes; + 16 ET 200AL modules

Dimensions	
Width	50 mm
Height	117 mm
Depth	74 mm

Weights	
Weight, approx.	150 g

last modified: 08/10/2019

Subject to change without notice
© Copyright Siemens