

\*\*\* SPARE PART\*\*\* SIMATIC S7-1200, CPU 1212C, COMPACT CPU, DC/DC/RLY, ONBOARD I/O: 8 DI 24V DC; 6 DO RELAY 2A; 2 AI 0 - 10V DC, POWER SUPPLY: DC 20.4 - 28.8 V DC, PROGRAM/DATA MEMORY: 25 KB



| General information   |                        |
|---|------------------------|
| Product type designation  | CPU 1212C DC/DC/Relay  |
| Engineering with  |                        |
| <ul style="list-style-type: none"> <li>Programming package</li> </ul>                 | STEP 7 V10.5 or higher |
| Supply voltage  |                        |
| Rated value (DC)  |                        |
| <ul style="list-style-type: none"> <li>24 V DC</li> </ul>                             | Yes                    |
| permissible range, lower limit (DC)   | 20.4 V                 |
| permissible range, upper limit (DC)   | 28.8 V                 |
| Load voltage L+   |                        |
| <ul style="list-style-type: none"> <li>Rated value (DC)</li> </ul>                    | 24 V                   |
| <ul style="list-style-type: none"> <li>permissible range, lower limit (DC)</li> </ul> | 5 V                    |
| <ul style="list-style-type: none"> <li>permissible range, upper limit (DC)</li> </ul> | 250 V                  |
| Input current   |                        |
| Current consumption (rated value)   | 175 mA; Typical        |
| Current consumption, max.   | 1.2 A; 24 V DC         |
| Inrush current, max.  | 12 A; at 28.8 V DC     |

|   |   |
|---|---|
| <b>Output current</b>                                     |   |
| for backplane bus (5 V DC), max.                          | 1 000 mA; Max. 5 V DC for SM and CM   |
| <b>Encoder supply</b>                                     |   |
| 24 V encoder supply                                       |   |
| • 24 V  | Permissible range: 20.4V to 28.8V   |
| <b>Power loss</b>   |   |
| Power loss, typ.  | 9 W   |
| <b>Memory</b>   |   |
| Work memory   |   |
| • integrated  | 25 kbyte  |
| • expandable  | No  |
| Load memory   |   |
| • integrated  | 1 Mbyte   |
| • Plug-in (SIMATIC Memory Card), max.                     | 24 Mbyte; with SIMATIC memory card  |
| Backup  |   |
| • present   | Yes; Entire project maintenance-free in the integral EEPROM   |
| • without battery   | Yes   |
| <b>CPU processing times</b>                               |   |
| for bit operations, typ.                                  | 0.1 µs; / Operation   |
| for word operations, typ.                                 | 12 µs; / Operation  |
| for floating point arithmetic, typ.                       | 18 µs; / Operation  |
| <b>CPU-blocks</b>   |   |
| Number of blocks (total)                                  | DBs, FCs, FBs, counters and timers. The maximum number of addressable blocks ranges from 1 to 65535. There is no restriction, the entire working memory can be used |
| OB  |   |
| • Number, max.  | Limited only by RAM for code  |
| <b>Data areas and their retentivity</b>                   |   |
| Retentive data area (incl. timers, counters, flags), max. | 2 048 byte  |
| Flag  |   |
| • Number, max.  | 4 kbyte; Size of bit memory address area  |
| <b>Address area</b>                                       |   |
| I/O address area  |   |
| • Inputs  | 1 024 byte  |
| • Outputs   | 1 024 byte  |
| Process image   |   |
| • Inputs, adjustable                                      | 1 kbyte   |
| • Outputs, adjustable                                     | 1 kbyte   |

## Hardware configuration

Number of modules per system, max. 3 comm. modules, 1 signal board, 2 signal modules

## Time of day

### Clock

- Hardware clock (real-time) Yes
- Backup time 240 h; Typical
- Deviation per day, max. +/- 60 s/month at 25 °C

## Digital inputs

Number of digital inputs 8; Integrated

- of which inputs usable for technological functions 4; HSC (High Speed Counting)

Source/sink input Yes

### Input voltage

- Rated value (DC) 24 V
- for signal "0" 5 V DC at 1 mA
- for signal "1" 15 V DC at 2.5 mA

### Input current

- for signal "1", typ. 1 mA

### Input delay (for rated value of input voltage)

#### for standard inputs

- parameterizable 0.2 ms, 0.4 ms, 0.8 ms, 1.6 ms, 3.2 ms, 6.4 ms and 12.8 ms, selectable in groups of four
- at "0" to "1", min. 0.2 ms
- at "0" to "1", max. 12.8 ms

#### for interrupt inputs

- parameterizable Yes

#### for counter/technological functions

- parameterizable Single phase: 3 at 100 kHz & 1 at 30 kHz, differential: 3 at 80 kHz & 1 at 30 kHz

### Cable length

- shielded, max. 500 m; 50 m for technological functions
- unshielded, max. 300 m; For technological functions: No

## Digital outputs

Number of digital outputs 6; Relays

Short-circuit protection No; to be provided externally

### Switching capacity of the outputs

- with resistive load, max. 2 A
- on lamp load, max. 30 W with DC, 200 W with AC

### Output delay with resistive load

- "0" to "1", max. 10 ms; max.
- "1" to "0", max. 10 ms; max.

|   |  |
|---|--|
| <b>Switching frequency</b>                                    |  |
| • of the pulse outputs, with resistive load, max.             | 1 Hz   |
| <b>Relay outputs</b>  |  |
| • Number of relay outputs                                     | 6  |
| • Number of operating cycles, max.                            | mechanically 10 million, at rated load voltage 100 000 |
| <b>Cable length</b>   |  |
| • shielded, max.  | 500 m  |
| • unshielded, max.  | 150 m  |
| <b>Analog inputs</b>  |  |
| Number of analog inputs                                       | 2  |
| <b>Input ranges</b>   |  |
| • Voltage   | Yes  |
| <b>Input ranges (rated values), voltages</b>                  |  |
| • 0 to +10 V  | Yes  |
| • Input resistance (0 to 10 V)                                | ≥100k ohms   |
| <b>Cable length</b>   |  |
| • shielded, max.  | 100 m; twisted and shielded                            |
| <b>Analog outputs</b>   |  |
| Number of analog outputs                                      | 0  |
| <b>Cable length</b>   |  |
| • shielded, max.  | 100 m; shielded, twisted pair                          |
| <b>Analog value generation for the inputs</b>                 |  |
| <b>Integration and conversion time/resolution per channel</b> |  |
| • Resolution with overrange (bit including sign), max.        | 10 bit   |
| • Integration time, parameterizable                           | Yes  |
| • Conversion time (per channel)                               | 625 μs   |
| <b>Encoder</b>  |  |
| <b>Connectable encoders</b>                                   |  |
| • 2-wire sensor   | Yes  |
| <b>1. Interface</b>   |  |
| Interface type  | PROFINET   |
| Physics   | Ethernet   |
| Isolated  | Yes  |
| automatic detection of transmission rate                      | Yes  |
| Autonegotiation   | Yes  |
| Autocrossing  | Yes  |
| <b>Functionality</b>  |  |
| • PROFINET IO Controller                                      | Yes  |
| <b>Protocols</b>  |  |

|                                   |     |
|-----------------------------------|-----|
| Supports protocol for PROFINET IO | No  |
| PROFIBUS                          | No  |
| AS-Interface                      | No  |
| <b>Protocols (Ethernet)</b>       |     |
| • TCP/IP                          | Yes |
| <b>Further protocols</b>          |     |
| • MODBUS                          | No  |

|                                |                 |
|--------------------------------|-----------------|
| <b>Communication functions</b> |                 |
| <b>S7 communication</b>        |                 |
| • supported                    | Yes             |
| • as server                    | Yes             |
| <b>Open IE communication</b>   |                 |
| • TCP/IP                       | Yes             |
| • ISO-on-TCP (RFC1006)         | Yes             |
| <b>Web server</b>              |                 |
| • supported                    | Yes             |
| • User-defined websites        | Yes             |
| <b>Number of connections</b>   |                 |
| • overall                      | 15; dynamically |

|                                     |  |
|-------------------------------------|--|
| <b>Test commissioning functions</b> |  |
| <b>Status/control</b>               |  |
| • Status/control variable           | Yes  |
| • Variables                         | Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters |
| <b>Forcing</b>                      |  |
| • Forcing                           | Yes  |

|                                   |         |
|-----------------------------------|---------|
| <b>Integrated Functions</b>       |         |
| Number of counters                | 4       |
| Counting frequency (counter) max. | 100 kHz |
| Frequency meter                   | Yes     |
| controlled positioning            | Yes     |
| PID controller                    | Yes     |
| Number of alarm inputs            | 4       |

|   |        |
|---|--------|
| <b>Potential separation</b>                 |        |
| <b>Potential separation digital inputs</b>  |        |
| • Potential separation digital inputs       | No     |
| • between the channels, in groups of        | 1      |
| <b>Potential separation digital outputs</b> |        |
| • Potential separation digital outputs      | Relays |
| • between the channels                      | No     |
| • between the channels, in groups of        | 1      |

|  |  |
|--|--|
| <b>Permissible potential difference</b>  |  |
| between different circuits   | 500 V DC between 24 V DC and 5 V DC  |
| <b>EMC</b>   |  |
| <b>Interference immunity against discharge of static electricity</b>                                 |  |
| • Interference immunity against discharge of static electricity acc. to IEC 61000-4-2                | Yes  |
| — Test voltage at air discharge  | 8 kV   |
| — Test voltage at contact discharge  | 6 kV   |
| <b>Interference immunity to cable-borne interference</b>   |  |
| • Interference immunity on supply lines acc. to IEC 61000-4-4  | Yes  |
| • Interference immunity on signal cables acc. to IEC 61000-4-4                                       | Yes  |
| <b>Interference immunity against voltage surge</b>   |  |
| • on the supply lines acc. to IEC 61000-4-5  | Yes  |
| <b>Interference immunity against conducted variable disturbance induced by high-frequency fields</b> |  |
| • Interference immunity against high-frequency radiation acc. to IEC 61000-4-6                       | Yes  |
| <b>Emission of radio interference acc. to EN 55 011</b>  |  |
| • Limit class A, for use in industrial areas   | Yes; Group 1   |
| • Limit class B, for use in residential areas  | Yes; When appropriate measures are used to ensure compliance with the limits for Class B according to EN 55011 |
| <b>Degree and class of protection</b>  |  |
| Degree of protection acc. to EN 60529  |  |
| • IP20   | Yes  |
| <b>Standards, approvals, certificates</b>  |  |
| CE mark  | Yes  |
| cULus  | Yes  |
| FM approval  | Yes  |
| RCM (formerly C-TICK)  | Yes  |
| <b>Ambient conditions</b>  |  |
| <b>Free fall</b>   |  |
| • Fall height, max.  | 0.3 m; five times, in product package  |
| <b>Ambient temperature during operation</b>  |  |
| • min.   | 0 °C   |
| • max.   | 55 °C  |
| • horizontal installation, min.  | 0 °C   |
| • horizontal installation, max.  | 55 °C  |
| • vertical installation, min.  | 0 °C   |
| • vertical installation, max.  | 45 °C  |
| • permissible temperature change   | 5°C to 55°C, 3°C / minute  |

|  |   |
|--|---|
| <b>Ambient temperature during storage/transportation</b> |   |
| • min.   | -40 °C  |
| • max.   | 70 °C   |
| <b>Air pressure acc. to IEC 60068-2-13</b>               |   |
| • Operation, min.  | 795 hPa   |
| • Operation, max.  | 1 080 hPa   |
| • Storage/transport, min.                                | 660 hPa   |
| • Storage/transport, max.                                | 1 080 hPa   |
| • permissible operating height                           | -1000 to 2000 m   |
| <b>Relative humidity</b>                                 |   |
| • permissible range (without condensation) at 25 °C      | 95 %  |
| • Operation, max.  | 95 %; no condensation   |
| <b>Vibrations</b>  |   |
| • Vibrations   | 2 g (m/s <sup>2</sup> ) wall mounting, 1 g (m/s <sup>2</sup> ) DIN rail                   |
| • Operation, tested according to IEC 60068-2-6           | Yes   |
| <b>Shock test</b>  |   |
| • tested according to IEC 60068-2-27                     | Yes; IEC 68, Part 2-27 half-sine: strength of the shock 15 g (peak value), duration 11 ms |
| <b>Extended ambient conditions</b>                       |   |
| <b>Pollutant concentrations</b>                          |   |
| — SO <sub>2</sub> at RH < 60% without condensation       | SO <sub>2</sub> : < 0.5 ppm; H <sub>2</sub> S: < 0.1 ppm; RH < 60% condensation-free      |
| <b>Configuration</b>                                     |   |
| <b>Programming</b>                                       |   |
| <b>Programming language</b>                              |   |
| — LAD  | Yes   |
| — FBD  | Yes   |
| — SCL  | Yes   |
| <b>Cycle time monitoring</b>                             |   |
| • adjustable   | Yes   |
| <b>Dimensions</b>  |   |
| Width  | 90 mm   |
| Height   | 100 mm  |
| Depth  | 75 mm   |
| <b>Weights</b>   |   |
| Weight, approx.  | 385 g   |
| <b>last modified:</b>                                    | 03/16/2017  |