



SIMATIC S7-1200, Analog input, SB 1231, 1 AI, +/-10 V DC (12 bit resol.) or 0-20 mA

General information	
Product type designation	SB 1231, AI 1x12 bit
Supply voltage	
Rated value (DC)	24 V
Input current	
from backplane bus 5 V DC, typ.	55 mA
Power loss	
Power loss, typ.	0.4 W
Analog inputs	
Number of analog inputs	1; Current or voltage differential inputs
permissible input voltage for current input (destruction limit), max.	±35 V
permissible input voltage for voltage input (destruction limit), max.	35 V
permissible input current for voltage input (destruction limit), max.	40 mA
permissible input current for current input (destruction limit), max.	40 mA
Cycle time (all channels) max.	156.25 µs; 400 Hz suppression
Input ranges	
<ul style="list-style-type: none"> • Voltage 	Yes; ±10V, ±5V, ±2.5V
<ul style="list-style-type: none"> • Current 	Yes; 0 to 20 mA
<ul style="list-style-type: none"> • Thermocouple 	No
<ul style="list-style-type: none"> • Resistance thermometer 	No
<ul style="list-style-type: none"> • Resistance 	No
Input ranges (rated values), voltages	
<ul style="list-style-type: none"> • -10 V to +10 V — Input resistance (-10 V to +10 V) 	Yes ≥9 MOhm
<ul style="list-style-type: none"> • -2.5 V to +2.5 V — Input resistance (-2.5 V to +2.5 V) 	Yes ≥9 MOhm
<ul style="list-style-type: none"> • -5 V to +5 V — Input resistance (-5 V to +5 V) 	Yes ≥9 MOhm
Input ranges (rated values), currents	
<ul style="list-style-type: none"> • 0 to 20 mA — Input resistance (0 to 20 mA) 	Yes ≥ 250 Ohm
Analog outputs	
Number of analog outputs	0
Cable length	
<ul style="list-style-type: none"> • shielded, max. 	100 m; shielded, twisted pair
Analog value generation for the inputs	
conversion method / at the analog input	integrating

Integration and conversion time/resolution per channel	
<ul style="list-style-type: none"> Resolution with overrange (bit including sign), max. Integration time, parameterizable Interference voltage suppression for interference frequency f_1 in Hz 	11 bit; + sign Yes 40 dB, DC to 60 Hz
Smoothing of measured values	
<ul style="list-style-type: none"> parameterizable Step: None Step: low Step: Medium Step: High 	Yes Yes Yes Yes Yes
Errors/accuracies	
Temperature error (relative to input range), (+/-)	25 °C \pm 0.3%, to 55 °C \pm 0.6% total measurement range
Interrupts/diagnostics/status information	
Alarms	Yes
Diagnostics function	Yes
Alarms	
<ul style="list-style-type: none"> Diagnostic alarm 	Yes
Diagnoses	
<ul style="list-style-type: none"> Wire-break 	No
Diagnostics indication LED	
<ul style="list-style-type: none"> for status of the inputs for maintenance 	Yes Yes
Standards, approvals, certificates	
CE mark	Yes
CSA approval	Yes
UL approval	Yes
cULus	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
Marine approval	Yes
Ambient conditions	
Free fall	
<ul style="list-style-type: none"> Fall height, max. 	0.3 m; five times, in product package
Ambient temperature during operation	
<ul style="list-style-type: none"> min. max. horizontal installation, min. horizontal installation, max. vertical installation, min. vertical installation, max. 	-20 °C 60 °C -20 °C 60 °C -20 °C 50 °C
Ambient temperature during storage/transportation	
<ul style="list-style-type: none"> min. max. 	-40 °C 70 °C
Air pressure acc. to IEC 60068-2-13	
<ul style="list-style-type: none"> Operation, min. Operation, max. Storage/transport, min. Storage/transport, max. 	795 hPa 1 080 hPa 660 hPa 1 080 hPa
Relative humidity	
<ul style="list-style-type: none"> Operation at 25 °C without condensation, max. 	95 %
Pollutant concentrations	
<ul style="list-style-type: none"> SO₂ at RH < 60% without condensation 	SO ₂ : < 0.5 ppm; H ₂ S: < 0.1 ppm; RH < 60% condensation-free
connection method	
required front connector	Yes
Mechanics/material	
Enclosure material (front) <ul style="list-style-type: none"> Plastic 	Yes
Dimensions	

Width	38 mm
Height	62 mm
Depth	21 mm
Weights	
Weight, approx.	35 g

last modified: 4/25/2024 

