

\*\*\* SPARE PART\*\*\* SIMATIC S7-300, CPU 314 FOR EXPANDED  
TEMPERATURE RANGE INTEGRATED 24 V DC POWER SUPPLY  
24 KBYTE WORKING MEMORY

Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption (rated value)	1 000 mA
Inrush current, typ.	8 A
Power loss	
Power loss, max.	8 W
Memory	
Work memory	
• integrated	24 kbyte; 24 KB/8 K instructions RAM (integrated); 1 instruction means 3 bytes on average
Load memory	
• expandable FEPRM	Yes; Flash-EPRM
• expandable FEPRM, max.	4 Mbyte
• integrated RAM, max.	40 kbyte
Backup	
• present	Yes
• with battery	Yes; all blocks
• without battery	Yes; 4 KB: bit memory, counter, times and data
CPU processing times	
for bit operations, typ.	0.3 $\mu$ s
for bit operations, max.	0.6 $\mu$ s
for word operations, typ.	1 $\mu$ s
for fixed point arithmetic, typ.	2 $\mu$ s
for floating point arithmetic, typ.	50 $\mu$ s
for timer/counter operations, typ.	12 $\mu$ s
CPU-blocks	
DB	
• Number, max.	127
• Size, max.	8 kbyte
FB	

• Number, max.	128
• Size, max.	8 kbyte
FC	
• Number, max.	128
• Size, max.	8 kbyte
OB	
• Description	see instruction list
• Size, max.	8 kbyte
• Number of free cycle OBs	1; OB 1
• Number of time alarm OBs	1; OB 10
• Number of cyclic interrupt OBs	1; OB 35
• Number of process alarm OBs	1; OB 40
• Number of startup OBs	1; OB 100
Nesting depth	
• per priority class	8
Counters, timers and their retentivity	
S7 counter	
• Number	64
of which retentive with battery	
— can be set	Yes
— lower limit	0
— upper limit	63
of which retentive without battery	
— can be set	Yes
— lower limit	0
— upper limit	63
Counting range	
— lower limit	1
— upper limit	999
S7 times	
• Number	128
of which retentive with battery	
— adjustable	Yes
— lower limit	0
— upper limit	127
of which retentive without battery	
— adjustable	Yes
— lower limit	0
— upper limit	127
Time range	
— lower limit	10 ms

— upper limit

9 990 s

## Data areas and their retentivity

Flag	
• Number, max.	256 byte
• Retentivity available	Yes; MB 0 to MB 255
• of which retentive with battery	0 to 2 047 (M 0.0 to M 255.7, adjustable)
• of which retentive without battery	0 to 2 047 (M 0.0 to M 255.7, adjustable)

## Address area

I/O address area	
• Inputs	512 byte
• Outputs	512 byte
Process image	
• Inputs	128 byte
• Outputs	128 byte
Digital channels	
• Inputs	1 024
• Outputs	1 024
Analog channels	
• Inputs	256
• Outputs	128
Addressing volume	
• Inputs	122 byte
• Outputs	122 byte

## Hardware configuration

Number of expansion units, max.	3
connectable programming devices/PCs	PGs/PCs with STEP 7 connectable via MPI interface
Number of modules per DP slave interface, max.	16
Number of DP masters	
• integrated	0
• via CP	1; CP 342-5
Number of operable FMs and CPs (recommended)	
• FM	4
• CP, PtP	2
• CP, LAN	1
Rack	
• Modules per rack, max.	32
Time of day	
Clock	
• Hardware clock (real-time)	Yes

## Interfaces

<b>MPI</b>	
• Cable length, max.	9 100 m; without repeaters: 50 m; with 2 repeaters: 1100 m; with 10 repeaters in series: 9100 m; via fiber optic cable: 23.8 km (with 16 star hubs or OLMs)
<b>1. Interface</b>	
<b>Functionality</b>	
• MPI	Yes
<b>MPI</b>	
• Number of nodes, max.	32; 32 nodes on MPI bus; PG/PC, OP, additional S7-300/400, C7; per CPU max. 4 static and 4 dynamic connections
• Transmission rate, max.	187.5 kbit/s
<b>Services</b>	
— PG/OP communication	Yes
— Global data communication	Yes
— S7 basic communication	Yes
— S7 communication	Yes
<b>Communication functions</b>	
PG/OP communication	Yes
<b>Global data communication</b>	
• supported	Yes
<b>S7 basic communication</b>	
• supported	Yes
<b>S7 communication</b>	
• supported	Yes
• as server	Yes
<b>S5 compatible communication</b>	
• supported	Yes; via loadable blocks
<b>Standard communication (FMS)</b>	
• supported	Yes; via loadable blocks
<b>Number of connections</b>	
• overall	
— of which dynamic	8
— of which static	4
<b>Configuration</b>	
<b>Configuration software</b>	
• STEP 7	Yes; V5.0, V5.0 SP1
<b>Programming</b>	
• Command set	Binary logic operations, bracketed operations, result allocation, saving, counting, loading, transferring, comparing, shifting, rotating, complementation, calling blocks, fixed point arithmetic, floating point arithmetic, jump functions
• Nesting levels	8

<ul style="list-style-type: none"> <li>• Program organization</li> <li>• System functions (SFC)</li> </ul>	Linear, structured Interrupt and error processing, copy data, clock functions, diagnostic functions, module parameterization, operating mode transitions
<ul style="list-style-type: none"> <li>• System function blocks (SFB)</li> </ul>	1
<b>Programming language</b>	
— LAD	Yes
— FBD	Yes
— STL	Yes
— SCL	Yes
— GRAPH	Yes
<b>Software libraries</b>	
— Process diagnostics	Yes
— Software controller	Yes; depending on the required memory space and the resulting execution time
<b>Know-how protection</b>	
<ul style="list-style-type: none"> <li>• User program protection/password protection</li> </ul>	Yes
<b>Cycle time monitoring</b>	
<ul style="list-style-type: none"> <li>• lower limit</li> <li>• upper limit</li> <li>• adjustable</li> <li>• preset</li> </ul>	1 ms 6 000 ms Yes 150 ms
<b>Dimensions</b>	
Width	80 mm
Height	125 mm
Depth	130 mm
<b>Weights</b>	
Weight, approx.	530 g; Memory card 16 g
<b>last modified:</b>	03/23/2017