

SIMATIC S7-300, CPU 314C-2 PTP COMPACT CPU WITH MPI, 24 DI/16 DO, 4AI, 2AO, 1 PT100, 4 FAST COUNTERS (60 KHZ), INTEGRATED INTERFACE RS485, INTEGRATED 24V DC POWER SUPPLY, 48 KBYTE WORKING MEMORY, FRONT CONNECTOR (2 X 40PIN) AND MICRO MEMORY CARD REQUIRED

General information	
Hardware product version	01
Firmware version	V2.0.0
Engineering with	
<ul style="list-style-type: none"> <li>Programming package</li> </ul>	STEP 7 V5.2 SP1 or higher (with STEP 7 V5.1 SP3 or higher, please use predecessor CPU)
Supply voltage	
Rated value (DC)	
<ul style="list-style-type: none"> <li>24 V DC</li> </ul>	Yes
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Load voltage L+	
<ul style="list-style-type: none"> <li>Rated value (DC)</li> <li>permissible range, lower limit (DC)</li> <li>permissible range, upper limit (DC)</li> </ul>	24 V 20.4 V 28.8 V
Input current	
Current consumption (rated value)	800 mA
Current consumption (in no-load operation), typ.	150 mA
Inrush current, typ.	11 A
Power loss	
Power loss, typ.	14 W
Memory	
Work memory	
<ul style="list-style-type: none"> <li>integrated</li> <li>expandable</li> </ul>	48 kbyte; For program and data No
Load memory	
<ul style="list-style-type: none"> <li>Plug-in (MMC)</li> <li>Plug-in (MMC), max.</li> <li>Data management on MMC (after last programming), min.</li> </ul>	Yes 8 Mbyte 10 y
Backup	
<ul style="list-style-type: none"> <li>present</li> </ul>	Yes; Guaranteed by MMC (maintenance-free)

- without battery

Yes; Program and data

## CPU processing times

for bit operations, typ.	0.1 µs
for bit operations, max.	0.2 µs
for word operations, typ.	0.2 µs
for fixed point arithmetic, typ.	2 µs
for floating point arithmetic, typ.	3 µs

## CPU-blocks

Number of blocks (total)	1 024
<b>DB</b>	
• Number, max.	511; DB 0 reserved
• Size, max.	16 kbyte
<b>FB</b>	
• Number, max.	512; From FB 0 to FB 511
• Size, max.	16 kbyte
<b>FC</b>	
• Number, max.	512; from FC 0 to FC 511
• Size, max.	16 kbyte
<b>OB</b>	
• Number, max.	see instruction list
• Size, max.	16 kbyte
• Number of time alarm OBs	1
• Number of delay alarm OBs	1
• Number of cyclic interrupt OBs	1
• Number of process alarm OBs	1
<b>Nesting depth</b>	
• per priority class	8
• additional within an error OB	4

## Counters, timers and their retentivity

<b>S7 counter</b>	
• Number	256
<b>Retentivity</b>	
— adjustable	Yes
— lower limit	0
— upper limit	256
<b>Counting range</b>	
— lower limit	0
— upper limit	999
<b>S7 times</b>	
• Number	256
<b>Retentivity</b>	

— adjustable	Yes
— lower limit	0
— upper limit	256
— preset	No retentivity
<b>Time range</b>	
— lower limit	10 ms
— upper limit	9 990 s
<b>IEC timer</b>	
• present	Yes
• Type	SFB
<b>Data areas and their retentivity</b>	
<b>Flag</b>	
• Number, max.	256 byte
• Retentivity available	Yes; MB 0 to MB 255
• Retentivity preset	MB 0 to MB 15
• Number of clock memories	8
<b>Data blocks</b>	
• Number, max.	511; from DB1 to DB511
• Size, max.	16 kbyte
<b>Local data</b>	
• per priority class, max.	510 byte
<b>Address area</b>	
<b>I/O address area</b>	
• Inputs	1 kbyte
• Outputs	1 kbyte
<b>Process image</b>	
• Inputs	128 byte
• Outputs	128 byte
<b>Default addresses of the integrated channels</b>	
— Digital inputs	124.0 to 126.7
— Digital outputs	124.0 to 125.7
— Analog inputs	752 to 761
— Analog outputs	752 to 755
<b>Digital channels</b>	
• Inputs	992
— of which central	992
• Outputs	992
— of which central	992
<b>Analog channels</b>	
• Inputs	253
— of which central	248

• Outputs	124
— of which central	248
<b>Hardware configuration</b>	
Number of expansion units, max.	3
<b>Number of DP masters</b>	
• via CP	4
<b>Number of operable FMs and CPs (recommended)</b>	
• FM	8
• CP, PtP	8
• CP, LAN	10
<b>Rack</b>	
• Racks, max.	4
• Modules per rack, max.	8; In rack 3 max. 7
<b>Time of day</b>	
<b>Clock</b>	
• Hardware clock (real-time)	Yes
• retentive and synchronizable	Yes
• Backup time	6 wk
• Deviation per day, max.	10 s
<b>Operating hours counter</b>	
• Number	1
• Number/Number range	0
• Range of values	0 to 2 <sup>31</sup> hours (when using SFC 101)
• Granularity	1 hour
• retentive	Yes
<b>Clock synchronization</b>	
• supported	Yes
• to MPI, master	Yes
• to MPI, slave	Yes
• in AS, master	Yes
<b>Digital inputs</b>	
Number of digital inputs	24
integrated channels (DI)	24
<b>Input voltage</b>	
• Rated value (DC)	24 V
• for signal "0"	-3 to +5V
• for signal "1"	+15 to +30V
<b>Input current</b>	
• for signal "1", typ.	8 mA
<b>Input delay (for rated value of input voltage)</b>	
for standard inputs	

— parameterizable	Yes; 0.1 / 0.3 / 3 / 15 ms
for counter/technological functions	
— at "0" to "1", max.	8 $\mu$ s
Cable length	
• shielded, max.	1 000 m; 100 m for technological functions
• unshielded, max.	600 m
<b>Digital outputs</b>	
Number of digital outputs	16
integrated channels (DO)	16
Short-circuit protection	Yes; Clocked electronically
Limitation of inductive shutdown voltage to	L+ (-48 V)
Output voltage	
• for signal "1", min.	L+ (-0.8 V)
Output current	
• for signal "1" permissible range, max.	500 mA
• for signal "1" permissible range for 0 to 60 °C, max.	500 mA
• for signal "1" minimum load current	5 mA
• for signal "0" residual current, max.	0.5 mA
Switching frequency	
• with resistive load, max.	100 Hz
• with inductive load, max.	0.5 Hz
Total current of the outputs (per group)	
all mounting positions	
— up to 40 °C, max.	8 A
— up to 60 °C, max.	4 A
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
<b>Analog inputs</b>	
Number of analog inputs	
• For voltage/current measurement	4
• For resistance/resistance thermometer measurement	1
integrated channels (AI)	4+1
permissible input voltage for current input (destruction limit), max.	5 V; Permanent
permissible input current for voltage input (destruction limit), max.	0.5 mA; Permanent
Technical unit for temperature measurement adjustable	Yes; Degrees Celsius / degrees Fahrenheit / Kelvin
Input ranges	

• Current	Yes
• Resistance thermometer	Yes
• Resistance	Yes
Input ranges (rated values), voltages	
• 0 to +10 V	Yes
• Input resistance (0 to 10 V)	100 k $\Omega$
Input ranges (rated values), currents	
• 0 to 20 mA	Yes
• Input resistance (0 to 20 mA)	100 $\Omega$
• -20 mA to +20 mA	Yes
• Input resistance (-20 mA to +20 mA)	100 $\Omega$
• 4 mA to 20 mA	Yes
• Input resistance (4 mA to 20 mA)	100 $\Omega$
Input ranges (rated values), resistance thermometer	
• Pt 100	Yes
• Input resistance (Pt 100)	10 M $\Omega$
Input ranges (rated values), resistors	
• 0 to 600 ohms	Yes
• Input resistance (0 to 600 ohms)	10 M $\Omega$
Cable length	
• shielded, max.	100 m
Analog outputs	
Number of analog outputs	2
integrated channels (AO)	2
Output ranges, voltage	
• 0 to 10 V	Yes
• -10 V to +10 V	Yes
Output ranges, current	
• 0 to 20 mA	Yes
• -20 mA to +20 mA	Yes
• 4 mA to 20 mA	Yes
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	12 bit
• Integration time, parameterizable	Yes; 2,5 / 16,6 / 20 ms
Analog value generation for the outputs	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	12 bit
• Conversion time (per channel)	1 ms

<b>Encoder</b>	
<b>Connectable encoders</b>	
<ul style="list-style-type: none"> <li>• 2-wire sensor</li> </ul>	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA
<b>Errors/accuracies</b>	
<b>Basic error limit (operational limit at 25 °C)</b>	
• Voltage, relative to input range, (+/-)	0.7 %
• Current, relative to input range, (+/-)	0.7 %
• Resistance, relative to input range, (+/-)	3 %
• Resistance thermometer, relative to input range, (+/-)	3 %
• Voltage, relative to output range, (+/-)	0.7 %
• Current, relative to output range, (+/-)	0.7 %
<b>Interfaces</b>	
<b>MPI</b>	
• Cable length, max.	50 m; without repeater
<b>Point-to-point</b>	
• Cable length, max.	1 200 m
<b>Integrated protocol driver</b>	
— 3964 (R)	Yes
— ASCII	Yes
— RK512	Yes
<b>Transmission rate, RS 422/485</b>	
— with 3964 (R) protocol, max.	19.2 kbit/s
— with ASCII protocol, max.	19.2 kbit/s
— with RK 512 protocol, max.	19.2 kbit/s
<b>1. Interface</b>	
Interface type	Integrated RS 485 interface
Physics	RS 485
Isolated	No
Power supply to interface (15 to 30 V DC), max.	200 mA
<b>Functionality</b>	
• MPI	Yes
• PROFIBUS DP master	No
• PROFIBUS DP slave	No
• Point-to-point connection	No
<b>MPI</b>	
• Number of connections	12
• Transmission rate, max.	187.5 kbit/s
<b>Services</b>	

— PG/OP communication	Yes
— Routing	No
— Global data communication	Yes
— S7 basic communication	Yes
— S7 communication	Yes
— S7 communication, as client	No
— S7 communication, as server	Yes

## 2. Interface

Interface type	Integrated RS 422/ 485 interface
Physics	RS 422/RS 485 (X.27)
Isolated	Yes
Number of connection resources	none
<b>Functionality</b>	
• MPI	No
• PROFIBUS DP master	No
• PROFIBUS DP slave	No
• Point-to-point connection	Yes
<b>Point-to-point connection</b>	
• Transmission rate, max.	38.4 kbit/s
• Interface controllable from the user program	Yes
• Interface can trigger alarm/interrupt in the user program	Yes

## Communication functions

PG/OP communication	Yes
<b>Global data communication</b>	
• supported	Yes
• Number of GD loops, max.	4
• Number of GD packets, max.	4
• Number of GD packets, transmitter, max.	4
• Number of GD packets, receiver, max.	4
• Size of GD packets, max.	22 byte
• Size of GD packet (of which consistent), max.	22 byte
<b>S7 basic communication</b>	
• supported	Yes
• User data per job, max.	76 byte
• User data per job (of which consistent), max.	76 byte
<b>S7 communication</b>	
• supported	Yes
• as server	Yes
• as client	Yes
• User data per job, max.	180 kbyte



• User data per job (of which consistent), max.	64 byte
<b>S5 compatible communication</b>	
• supported	Yes
<b>Number of connections</b>	
• overall	12
• usable for PG communication	11
— reserved for PG communication	1
— adjustable for PG communication, min.	1
— adjustable for PG communication, max.	11
• usable for OP communication	11
— reserved for OP communication	1
— adjustable for OP communication, min.	1
— adjustable for OP communication, max.	11
• usable for S7 basic communication	8
— reserved for S7 basic communication	8
— adjustable for S7 basic communication, min.	0
— adjustable for S7 basic communication, max.	8
<b>S7 message functions</b>	
Number of login stations for message functions, max.	12
Process diagnostic messages	Yes
simultaneously active Alarm-S blocks, max.	40
<b>Test commissioning functions</b>	
Status block	Yes
Single step	Yes
Number of breakpoints	2
<b>Status/control</b>	
• Status/control variable	Yes
• Variables	Inputs, outputs, memory bits, DB, times, counters
• Number of variables, max.	30
— of which status variables, max.	30
— of which control variables, max.	14
<b>Forcing</b>	
• Forcing	Yes
• Forcing, variables	Inputs, outputs
• Number of variables, max.	10
<b>Integrated Functions</b>	
Number of counters	4
Counting frequency (counter) max.	60 kHz
Frequency measurement	Yes

Number of frequency meters	4
controlled positioning	Yes
PID controller	Yes
Number of pulse outputs	4
Limit frequency (pulse)	2.5 kHz

## Potential separation

### Potential separation digital inputs

- Potential separation digital inputs Yes
- between the channels, in groups of 16
- between the channels and backplane bus Yes

### Potential separation digital outputs

- Potential separation digital outputs Yes
- between the channels, in groups of 8
- between the channels and backplane bus Yes

### Potential separation analog inputs

- Potential separation analog inputs Yes; common for analog I/O
- between the channels and backplane bus Yes

### Potential separation analog outputs

- Potential separation analog outputs Yes; common for analog I/O
- between the channels and backplane bus Yes

## Configuration

### Configuration software

- STEP 7 Yes; V5.1 SP2

### Programming

- Command set see instruction list
- Nesting levels 8
- System functions (SFC) see instruction list
- System function blocks (SFB) see instruction list

### Programming language

- LAD Yes
- FBD Yes
- STL Yes
- SCL Yes
- CFC Yes
- GRAPH Yes
- HiGraph® Yes

### Know-how protection

- User program protection/password protection Yes

## Dimensions

Width	120 mm
Height	125 mm

Depth	130 mm
Weights	
Weight, approx.	676 g
last modified:	08/28/2017