

SIMATIC S7-300 CPU315F-2 PN/DP, CENTRAL PROCESSING UNIT WITH 192 KBYTE WORKING MEMORY, 1. INTERFACE MPI/DP 12MBIT/S, 2. INTERFACE ETHERNET PROFINET, MICRO MEMORY CARD NECESSARY USEABLE WITH SOFTWARE OPTION S7 DISTRIBUTED SAFETY V5.4 OR HIGHER

General information	
HW functional status	01
Firmware version	V2.3.3
Engineering with	
<ul style="list-style-type: none"> Programming package 	STEP 7 V5.3 SP3
Supply voltage	
Rated value (DC)	24 V
<ul style="list-style-type: none"> 24 V DC 	Yes
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
external protection for power supply lines (recommendation)	2 A min.
Input current	
Current consumption (in no-load operation), typ.	100 mA
Inrush current, typ.	2.5 A
I^2t	1 A ² ·s
Power loss	
Power loss, typ.	3.5 W
Memory	
Work memory	
<ul style="list-style-type: none"> integrated 	192 kbyte
<ul style="list-style-type: none"> expandable 	No
Load memory	
<ul style="list-style-type: none"> Plug-in (MMC) 	Yes
<ul style="list-style-type: none"> Plug-in (MMC), max. 	8 Mbyte
<ul style="list-style-type: none"> Data management on MMC (after last programming), min. 	10 y
<ul style="list-style-type: none"> expandable FEPROM 	can be plugged in as MMC
Backup	
<ul style="list-style-type: none"> present 	Yes; maintenance-free
CPU processing times	
for bit operations, typ.	0.1 μs

for bit operations, max.	0.1 μ s
for word operations, typ.	0.2 μ s
for fixed point arithmetic, typ.	2 μ s

CPU-blocks

Number of blocks (total)	1 024
--------------------------	-------

DB

• Number, max.	1 023; From DB 1 to DB 1023
• Size, max.	16 kbyte

FB

• Number, max.	2 048; from FB 0 to FB 2047
• Size, max.	16 kbyte

FC

• Number, max.	2 048; from FC 0 to FC 2047
• Size, max.	16 kbyte

OB

• Number, max.	see instruction list
• Size, max.	16 kbyte
• Number of free cycle OBs	1; OB 1
• Number of time alarm OBs	1; OB 10
• Number of delay alarm OBs	1; OB 20
• Number of cyclic interrupt OBs	1; OB 35
• Number of process alarm OBs	1; OB 40
• Number of startup OBs	1; OB 100
• Number of asynchronous error OBs	1; OB 80
• Number of synchronous error OBs	2; OB 121, 122

Nesting depth

• per priority class	8
• additional within an error OB	4

Counters, timers and their retentivity

S7 counter

• Number	256
----------	-----

Retentivity

— adjustable	Yes
— preset	Z 0 to Z 7

Counting range

— adjustable	Yes
— lower limit	0
— upper limit	999

IEC counter

• present	Yes
• Type	SFB

• Number	Unlimited (limited only by RAM capacity)
S7 times	
• Number	256
Retentivity	
— adjustable	Yes
— preset	No retentivity
Time range	
— lower limit	10 ms
— upper limit	9 990 s
IEC timer	
• present	Yes
• Type	SFB
• Number	Unlimited (limited only by RAM capacity)
Data areas and their retentivity	
retentive data area in total	up to 128 KB
Flag	
• Number, max.	2 048 byte
• Retentivity available	Yes; MB 0 to MB 2 047
• Retentivity preset	MB 0 to MB 15
• Number of clock memories	8; 1 memory byte
Local data	
• per priority class, max.	1 024 byte; max. 510 bytes per block
Address area	
I/O address area	
• Inputs	2 048 byte
• Outputs	2 048 byte
of which distributed	
— Inputs	2 kbyte
— Outputs	2 kbyte
Process image	
• Inputs	384 byte
• Outputs	384 byte
Digital channels	
• Inputs	16 384
— of which central	1 024; max.
• Outputs	16 384
— of which central	1 024; max.
Analog channels	
• Inputs	1 024
— of which central	256
• Outputs	1 024

Hardware configuration

Number of DP masters	
• integrated	1
• via CP	4
Number of operable FMs and CPs (recommended)	
• FM	8
• CP, PtP	8
• CP, LAN	10
Rack	
• Racks, max.	4
• Modules per rack, max.	8

Time of day

Clock	
• Hardware clock (real-time)	Yes
• retentive and synchronizable	Yes
• Backup time	6 wk; At 40 °C ambient temperature
• Deviation per day, max.	10 s
Operating hours counter	
• Number	1
• Range of values	0 to 2 ³¹ hours (when using SFC 101)
• Granularity	1 h
• retentive	Yes; Must be restarted at each restart
Clock synchronization	
• supported	Yes
• to MPI, master	Yes
• to MPI, slave	Yes
• in AS, master	Yes
• in AS, slave	Yes

1. Interface

Interface type	Integrated RS 485 interface
Physics	RS 485
Isolated	Yes
Power supply to interface (15 to 30 V DC), max.	200 mA
Protocols	
• MPI	Yes
• PROFIBUS DP master	Yes
• PROFIBUS DP slave	Yes
• Point-to-point connection	No
MPI	
• Number of connections	16

• Transmission rate, max.	12 Mbit/s
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	Yes
— S7 basic communication	Yes
— S7 communication	Yes
— S7 communication, as client	No
— S7 communication, as server	Yes
PROFIBUS DP master	
• Transmission rate, max.	12 Mbit/s
• Number of DP slaves, max.	124
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	No
— S7 basic communication	Yes
— S7 communication	Yes
— S7 communication, as client	No
— S7 communication, as server	Yes
— Equidistance	Yes
— SYNC/FREEZE	Yes
— DPV1	Yes
PROFIBUS DP slave	
• Transmission rate, max.	12 Mbit/s
• Address area, max.	32; With max. 32 bytes each
Services	
— Routing	Yes; Only with active interface
— Global data communication	No
— S7 basic communication	Yes
— S7 communication	Yes
— S7 communication, as client	No
— S7 communication, as server	Yes
— Direct data exchange (slave-to-slave communication)	Yes
— DPV1	No
Transfer memory	
— Inputs	244 byte
— Outputs	244 byte
2. Interface	
Interface type	PROFINET

Physics	Ethernet
Isolated	Yes
Power supply to interface (15 to 30 V DC), max.	0 mA
automatic detection of transmission rate	Yes; 10/100 Mbit/s
Protocols	
• MPI	No
• PROFINET IO Controller	Yes
• PROFINET CBA	Yes
• PROFIBUS DP master	No
• PROFIBUS DP slave	No
• Open IE communication	Yes; via TCP/IP
• Point-to-point connection	No
PROFINET IO Controller	
• Transmission rate, max.	100 Mbit/s
Services	
— PG/OP communication	Yes
— Routing	Yes
— S7 communication	Yes; with loadable FBs, max. configurable connections: 16
— Number of connectable IO Devices, max.	128
— Updating time	1 to 512 ms (minimum value depends on communication share set for PROFINET I/O, on the number of I/O devices, and on the volume of configured user data)
Address area	
— Inputs, max.	2 kbyte
— Outputs, max.	2 kbyte
— User data consistency, max.	256 byte
PROFINET CBA	
• acyclic transmission	Yes
• cyclic transmission	Yes
Protocols	
Open IE communication	
• TCP/IP	Yes; via integrated PROFINET interface and loadable FBs
— Number of connections, max.	8
— Data length, max.	1 460 byte
Communication functions	
PG/OP communication	Yes
Global data communication	
• supported	Yes
• Number of GD loops, max.	8
• Number of GD packets, max.	8
• Number of GD packets, transmitter, max.	8

• Number of GD packets, receiver, max.	8
• Size of GD packets, max.	22 byte
• Size of GD packet (of which consistent), max.	22 byte
S7 basic communication	
• supported	Yes
• User data per job, max.	76 byte
• User data per job (of which consistent), max.	76 byte; 76 bytes (with X_SEND or X_RCV); 64 bytes (with X_PUT or X_GET as server)
S7 communication	
• supported	Yes
• as server	Yes
• as client	Yes; via integrated PROFINET interface and loadable FB or via CP and loadable FB
S5 compatible communication	
• supported	Yes; Via CP and loadable FB
PROFINET CBA (at set setpoint communication load)	
• Setpoint for the CPU communication load	50 %
• Number of remote interconnection partners	32
• Number of functions, master/slave	17
• Total of all master/slave connections	1 000
• Data length of all incoming connections master/slave, max.	4 000 byte
• Data length of all outgoing connections master/slave, max.	4 000 byte
• Number of device-internal and PROFIBUS interconnections	500
• Data length of device-internal und PROFIBUS interconnections, max.	4 000 byte
• Data length per connection, max.	1 400 byte
Remote interconnections with acyclic transmission	
— Sampling frequency: Sampling time, min.	500 ms
— Number of incoming interconnections	100
— Number of outgoing interconnections	100
— Data length of all incoming interconnections, max.	2 000 byte
— Data length of all outgoing interconnections, max.	2 000 byte
— Data length per connection, max.	1 400 byte
Remote interconnections with cyclic transmission	
— Transmission frequency: Transmission interval, min.	10 ms
— Number of incoming interconnections	200
— Number of outgoing interconnections	200

— Data length of all incoming interconnections, max.	2 000 byte
— Data length of all outgoing interconnections, max.	2 000 byte
— Data length per connection, max.	450 byte
HMI variables via PROFINET (acyclic)	
— Number of stations that can log on for HMI variables (PN OPC/iMap)	3; 2x PN OPC/1x iMap
— HMI variable updating	500 ms
— Number of HMI variables	200
— Data length of all HMI variables, max.	2 000 byte
PROFIBUS proxy functionality	
— supported	Yes
— Number of linked PROFIBUS devices	16
— Data length per connection, max.	240 byte; Slave-dependent
Number of connections	
• overall	16
• usable for PG communication	15; max.
— reserved for PG communication	1
— adjustable for PG communication, min.	1
— adjustable for PG communication, max.	15; 1 to 15
• usable for OP communication	15
— reserved for OP communication	1
— adjustable for OP communication, min.	1
— adjustable for OP communication, max.	15; 1 to 15
• usable for S7 basic communication	14
— reserved for S7 basic communication	0
— adjustable for S7 basic communication, min.	0
— adjustable for S7 basic communication, max.	14; 0 to 14
S7 message functions	
Number of login stations for message functions, max.	16; Depending on the configured connections for PG/OP and S7 basic communication
Process diagnostic messages	Yes
simultaneously active Alarm-S blocks, max.	40
Test commissioning functions	
Status block	Yes
Single step	Yes
Number of breakpoints	2
Status/control	
• Status/control variable	Yes

• Variables	Inputs, outputs, memory bits, DB, times, counters
• Number of variables, max.	30
— of which status variables, max.	30
— of which control variables, max.	14
Forcing	
• Forcing	Yes
• Forcing, variables	Inputs, outputs
• Number of variables, max.	10
Diagnostic buffer	
• present	Yes
• Number of entries, max.	100
— adjustable	No
Configuration	
Configuration software	
• STEP 7	Yes; With HSP 88, otherwise with SP3
Programming	
• Command set	see instruction list
• Nesting levels	8
• System functions (SFC)	see instruction list
• System function blocks (SFB)	see instruction list
Programming language	
— LAD	Yes
— FBD	Yes
— STL	Yes
— SCL	Yes
— CFC	Yes
— GRAPH	Yes
— HiGraph®	Yes
Know-how protection	
• User program protection/password protection	Yes
Dimensions	
Width	80 mm
Height	125 mm
Depth	130 mm
last modified:	05/28/2020