



SIMATIC S7-300, ANALOG INPUT SM 331,  
GALVANICALLY ISOLATED, 8 AI, 14 BIT,  
0.052MS/CHANNEL, CURRENT, VOLTAGE,  
INTERRUPTS, DIAGNOSTICS, 1 X 20 PIN,  
FIT FOR ISOCHRON MODE IMPROVED DP-CYCLE TIME  
FOR ISOCHRON MODE

Supply voltage	
Load voltage L+	
Rated value (DC)	24 V
Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	50 mA
from backplane bus 5 V DC, max.	60 mA
Power loss	
Power loss, typ.	1.5 W
Analog inputs	
Number of analog inputs	8
permissible input voltage for voltage input (destruction limit), max.	20 V ; 20 V DC permanent, 75 V DC for max. 1 s (duty factor 1:20)
permissible input current for current input (destruction limit), max.	40 mA
Input ranges	
Voltage	Yes
Current	Yes
Thermocouple	No
Resistance thermometer	No
Resistance	No

Input ranges (rated values), voltages	
0 to +10 V	No
1 to 5 V	Yes
<b>Input resistance (1 to 5 V)</b>	100 kΩ
-1 V to +1 V	Yes
<b>Input resistance (-1 V to +1 V)</b>	10 MΩ
-10 V to +10 V	Yes
<b>Input resistance (-10 V to +10 V)</b>	100 kΩ
-5 V to +5 V	Yes
<b>Input resistance (-5 V to +5 V)</b>	100 kΩ
-500 mV to +500 mV	Yes
-80 mV to +80 mV	Yes
Input ranges (rated values), currents	
0 to 20 mA	Yes
<b>Input resistance (0 to 20 mA)</b>	50 Ω
-20 to +20 mA	Yes
<b>Input resistance (-20 to +20 mA)</b>	50 Ω
4 to 20 mA	Yes
<b>Input resistance (4 to 20 mA)</b>	50 Ω
Cable length	
Cable length, shielded, max.	200 m
Analog value generation	
Measurement principle	Actual value encryption
Integration and conversion time/resolution per channel	
Resolution with overrange (bit including sign), max.	14 bit ; Unipolar: 14 bits; bipolar: 13 bits + sign
Integration time, parameterizable	Yes
Basic conversion time, ms	52 µs per channel
Interference voltage suppression for interference frequency f1 in Hz	none / 400 / 60 / 50 Hz
Encoder	
Connection of signal encoders	
for current measurement as 2-wire transducer	Yes
for current measurement as 4-wire transducer	Yes
Errors/accuracies	
Operational error limit in overall temperature range	
Voltage, relative to input area, (+/-)	0.4 %
Current, relative to input area, (+/-)	0.3 %
Basic error limit (operational limit at 25 °C)	
Voltage, relative to input area, (+/-)	0.25 %

<b>Current, relative to input area, (+/-)</b>	0.2 %
<b>Isochronous mode</b>	
<b>Isochronous mode (application synchronized up to terminal)</b>	Yes
<b>Interrupts/diagnostics/status information</b>	
<b>Alarms</b>	
<b>Diagnostic alarm</b>	Yes ; Parameterizable
<b>Limit value alarm</b>	Yes ; Parameterizable, channels 0 and 2
<b>Diagnostic messages</b>	
<b>Diagnostic functions</b>	Yes
<b>Diagnostic information readable</b>	Yes
<b>Diagnostics</b>	Yes
<b>Diagnostics indication LED</b>	
<b>Group error SF (red)</b>	Yes
<b>Galvanic isolation</b>	
<b>Galvanic isolation analog inputs</b>	
<b>between the channels</b>	No
<b>between the channels and the backplane bus</b>	Yes
<b>Isolation</b>	
<b>Isolation tested with</b>	500 V DC
<b>Connection method</b>	
<b>required front connector</b>	20-pin
<b>Dimensions</b>	
<b>Width</b>	40 mm
<b>Height</b>	125 mm
<b>Depth</b>	120 mm
<b>Weights</b>	
<b>Weight, approx.</b>	200 g
Status	Jul 14, 2014