



SIMATIC S7-400,
POWER SUPPLY PS 405: 10A, WIDE RANGE,
24/48/60V DC, DC, 5V DC/10A,
FOR REDUNDANT USE ATEX
APPROBATION IDENTIFICATION

Supply voltage

Rated value, 24 V DC	Yes
Rated value, 48 V DC	Yes
Rated value, 60 V DC	Yes
permissible range, lower limit (DC)	19.2 V ; Dynamic 18.5 V
permissible range, upper limit (DC)	72 V ; dynamic 75.5 V

Mains buffering

Mains/voltage failure stored energy time	20 ms
Mains buffering according to NAMUR recommendation	Yes

Input current

Rated value at 24 V DC	4 A
Rated value at 48 V DC	2 A
Rated value at 60 V DC	1.6 A
Inrush current, max.	18 A ; Full width at half maximum 20 ms

Output voltage

Rated value, 5 V DC	Yes
Rated value, 24 V DC	Yes

Output current

for backplane bus (5 V DC), max.	10 A ; no base load required
----------------------------------	------------------------------

for backplane bus (24 V DC), max.	1 A ; idling-proof
Short-circuit protection	Yes
Power	
Power consumption, typ.	95 W
Power losses	
Power loss, typ.	20 W
Battery	
Backup battery	
Backup battery	
Backup battery (optional)	Yes ; 2 x lithium AA; 3.6 V/2.3 Ah
Galvanic isolation	
primary/secondary	Yes
Degree and class of protection	
Protection class	1 ; with protective conductor
Standards, approvals, certificates	
FM approval	Yes ; Ta: 0 °C to 60 °C T4
Connection method	
Connecting cables/cross sections	3 x 1.5 mm ² , solid or stranded wire with end sleeve, external diameter 3 to 9 mm
Dimensions	
Width	50 mm
Height	290 mm
Depth	217 mm
Required slots	2
Weights	
Weight, approx.	1200 g
Status	Oct 22, 2013