



SIMATIC S7-400H, CPU 416-5H, central processing unit for S7-400H and S7-400F/FH, 5 interfaces: 1x MPI/DP, 1x DP, 1x PN and 2 for sync modules, 16 MB memory (10 MB data/6 MB program)

| General information                         |                                      |
|---|--------------------------------------|
| Product type designation                    | CPU 416-5H PN/DP                     |
| HW functional status                        | 1                                    |
| Firmware version                            | V6.0                                 |
| Product function                            |                                      |
| • Isochronous mode                          | No                                   |
| Engineering with                            |                                      |
| • Programming package                       | As of STEP 7 V5.5 SP2 with HF1       |
| CiR - Configuration in RUN                  |                                      |
| CiR synchronization time, basic load        | 100 ms                               |
| CiR synchronization time, time per I/O byte | 0 µs                                 |
| Supply voltage                              |                                      |
| Rated value (DC)                            | Power supply via system power supply |
| Input current                               |                                      |
| from backplane bus 5 V DC, typ.             | 1.6 A                                |
| from backplane bus 5 V DC, max.             | 1.9 A                                |
| from backplane bus 24 V DC, max.            | 150 mA; 150 mA per DP interface      |
| from interface 5 V DC, max.                 | 90 mA; At each DP interface          |
| Power loss                                  |                                      |
| Power loss, typ.                            | 7.5 W                                |
| Memory                                      |                                      |
| Type of memory                              | RAM                                  |
| Work memory                                 |                                      |
| • integrated                                | 16 Mbyte                             |
| • integrated (for program)                  | 6 Mbyte                              |
| • integrated (for data)                     | 10 Mbyte                             |
| • expandable                                | No                                   |
| Load memory                                 |                                      |
| • expandable FEPR0M                         | Yes; with Memory Card (FLASH)        |
| • expandable FEPR0M, max.                   | 64 Mbyte                             |
| • integrated RAM, max.                      | 1 Mbyte                              |
| • expandable RAM                            | Yes                                  |
| • expandable RAM, max.                      | 64 Mbyte                             |
| Backup                                      |                                      |
| • present                                   | Yes                                  |
| • with battery                              | Yes; all data                        |
| • without battery                           | No                                   |
| Battery                                     |                                      |
| Backup battery                              |                                      |
| • Backup current, typ.                      | 180 µA; Valid up to 40°C             |

|   |   |
|---|---|
| • Backup current, max.                      | 1 000 µA  |
| • Backup time, max.                         | Dealt with in the module data manual with the secondary conditions and the factors of influence |
| • Feeding of external backup voltage to CPU | 5 V DC to 15 V DC   |

#### CPU processing times

|                                     |         |
|-------------------------------------|---------|
| for bit operations, typ.            | 12.5 ns |
| for word operations, typ.           | 12.5 ns |
| for fixed point arithmetic, typ.    | 12.5 ns |
| for floating point arithmetic, typ. | 25 ns   |

#### CPU-blocks

|                                    |                                  |
|------------------------------------|----------------------------------|
| <b>DB</b>                          |                                  |
| • Number, max.                     | 16 000; Number range: 1 to 16000 |
| • Size, max.                       | 64 kbyte                         |
| <b>FB</b>                          |                                  |
| • Number, max.                     | 8 000; Number range: 0 to 7999   |
| • Size, max.                       | 64 kbyte                         |
| <b>FC</b>                          |                                  |
| • Number, max.                     | 8 000; Number range: 0 to 7999   |
| • Size, max.                       | 64 kbyte                         |
| <b>OB</b>                          |                                  |
| • Number, max.                     | see instruction list             |
| • Size, max.                       | 64 kbyte                         |
| • Number of free cycle OBs         | 1; OB 1                          |
| • Number of time alarm OBs         | 8; OB 10-17                      |
| • Number of delay alarm OBs        | 4; OB 20-23                      |
| • Number of cyclic interrupt OBs   | 9; OB 30-38                      |
| • Number of process alarm OBs      | 8; OB 40-47                      |
| • Number of DPV1 alarm OBs         | 3; OB 55-57                      |
| • Number of startup OBs            | 2; OB 100, 102                   |
| • Number of asynchronous error OBs | 9; OB 80-88                      |
| • Number of synchronous error OBs  | 2; OB 121, 122                   |
| <b>Nesting depth</b>               |                                  |
| • per priority class               | 24                               |
| • additional within an error OB    | 2                                |

#### Counters, timers and their retentivity

|                       |  |
|-----------------------|--|
| <b>S7 counter</b>     |  |
| • Number              | 2 048                                    |
| <b>Retentivity</b>    |  |
| — adjustable          | Yes                                      |
| — preset              | Z 0 to Z 7                               |
| <b>Counting range</b> |  |
| — lower limit         | 0  |
| — upper limit         | 999                                      |
| <b>IEC counter</b>    |  |
| • present             | Yes                                      |
| • Type                | SFB                                      |
| • Number              | Unlimited (limited only by RAM capacity) |
| <b>S7 times</b>       |  |
| • Number              | 2 048                                    |
| <b>Retentivity</b>    |  |
| — adjustable          | Yes                                      |
| — preset              | No times retentive                       |
| <b>Time range</b>     |  |
| — lower limit         | 10 ms                                    |
| — upper limit         | 9 990 s                                  |
| <b>IEC timer</b>      |  |
| • present             | Yes                                      |
| • Type                | SFB                                      |
| • Number              | Unlimited (limited only by RAM capacity) |

#### Data areas and their retentivity

|   |   |
|---|---|
| Retentive data area (incl. timers, counters, flags), max. | Total working and load memory (with backup battery) |
|---|---|

|   |  |
|---|--|
| <b>Flag</b>   |  |
| <ul style="list-style-type: none"> <li>• Size, max.</li> <li>• Retentivity available</li> <li>• Retentivity preset</li> <li>• Number of clock memories</li> </ul>   | 16 384 byte<br>Yes<br>MB 0 to MB 15<br>8; in 1 memory byte   |
| <b>Local data</b>   |  |
| <ul style="list-style-type: none"> <li>• adjustable, max.</li> <li>• preset</li> </ul>  | 64 kbyte<br>32 kbyte   |
| <b>Address area</b>   |  |
| <b>I/O address area</b>   |  |
| <ul style="list-style-type: none"> <li>• Inputs</li> <li>• Outputs</li> </ul>   | 16 kbyte<br>16 kbyte   |
| <b>Process image</b>  |  |
| <ul style="list-style-type: none"> <li>• Inputs, adjustable</li> <li>• Outputs, adjustable</li> <li>• Inputs, default</li> <li>• Outputs, default</li> <li>• consistent data, max.</li> <li>• Access to consistent data in process image</li> </ul>   | 16 kbyte<br>16 kbyte<br>1 024 byte<br>1 024 byte<br>244 byte<br>Yes  |
| <b>Subprocess images</b>  |  |
| <ul style="list-style-type: none"> <li>• Number of subprocess images, max.</li> </ul>   | 15   |
| <b>Digital channels</b>   |  |
| <ul style="list-style-type: none"> <li>• Inputs               <ul style="list-style-type: none"> <li>— of which central</li> </ul> </li> <li>• Outputs               <ul style="list-style-type: none"> <li>— of which central</li> </ul> </li> </ul> | 131 072<br>131 072<br>131 072<br>131 072   |
| <b>Analog channels</b>  |  |
| <ul style="list-style-type: none"> <li>• Inputs               <ul style="list-style-type: none"> <li>— of which central</li> </ul> </li> <li>• Outputs               <ul style="list-style-type: none"> <li>— of which central</li> </ul> </li> </ul> | 8 192<br>8 192<br>8 192<br>8 192   |
| <b>Hardware configuration</b>   |  |
| Number of expansion units, max.   | 21   |
| connectable OPs   | 95   |
| Multicomputing  | No   |
| <b>Interface modules</b>  |  |
| <ul style="list-style-type: none"> <li>• Number of connectable IMs (total), max.</li> <li>• Number of connectable IM 460s, max.</li> <li>• Number of connectable IM 463s, max.</li> </ul>   | 6<br>6<br>4; Single mode only  |
| <b>Number of DP masters</b>   |  |
| <ul style="list-style-type: none"> <li>• integrated</li> <li>• via CP</li> <li>• Mixed mode IM + CP permitted</li> <li>• via interface module</li> </ul>  | 2<br>10; CP 443-5 Extended<br>No<br>0  |
| <b>Number of IO Controllers</b>   |  |
| <ul style="list-style-type: none"> <li>• integrated</li> <li>• via CP</li> </ul>  | 1<br>0   |
| <b>Number of operable FMs and CPs (recommended)</b>   |  |
| <ul style="list-style-type: none"> <li>• FM</li> <li>• CP, PtP</li> <li>• PROFIBUS and Ethernet CPs</li> </ul>  | See manual Automation System S7-400H fault-tolerant systems. Limited by number of slots and number of connections<br>See manual Automation System S7-400H fault-tolerant systems. Limited by number of slots and number of connections<br>14; Of which max. 10 CP as DP master |
| <b>Slots</b>  |  |
| <ul style="list-style-type: none"> <li>• required slots</li> </ul>  | 2  |
| <b>Time of day</b>  |  |
| <b>Clock</b>  |  |
| <ul style="list-style-type: none"> <li>• Hardware clock (real-time)</li> <li>• retentive and synchronizable</li> <li>• Resolution</li> <li>• Deviation per day (buffered), max.</li> </ul>  | Yes<br>Yes<br>1 ms<br>1.7 s; Power off   |

|  |  |
|--|--|
| <ul style="list-style-type: none"> <li>• Deviation per day (unbuffered), max.</li> </ul>   | 8.6 s; Power on  |
| <b>Operating hours counter</b>   |  |
| <ul style="list-style-type: none"> <li>• Number</li> <li>• Number/Number range</li> <li>• Range of values</li> <li>• Granularity</li> <li>• retentive</li> </ul>   | 16<br>0 to 15<br>SFCs 2, 3 and 4: 0 to 32767 hours SFC 101: 0 to 2 <sup>31</sup> - 1 hours<br>1 h<br>Yes                             |
| <b>Clock synchronization</b>   |  |
| <ul style="list-style-type: none"> <li>• supported</li> <li>• to MPI, master</li> <li>• to MPI, slave</li> <li>• to DP, master</li> <li>• to DP, slave</li> <li>• in AS, master</li> <li>• in AS, slave</li> <li>• on Ethernet via NTP</li> </ul>  | Yes<br>Yes<br>Yes<br>Yes<br>Yes<br>Yes<br>Yes<br>Yes; As client  |
| <b>Time difference in system when synchronizing via</b>  |  |
| <ul style="list-style-type: none"> <li>• Ethernet, max.</li> <li>• MPI, max.</li> </ul>  | 10 ms; Via NTP<br>200 ms   |
| <b>Interfaces</b>  |  |
| Number of RS 485 interfaces  | 2  |
| Number of other interfaces   | 2; Fiber-optic interface   |
| Optical interface  | No   |
| <b>1. Interface</b>  |  |
| Interface type   | MPI/PROFIBUS DP  |
| Isolated   | Yes  |
| <b>Interface types</b>   |  |
| <ul style="list-style-type: none"> <li>• RS 485</li> <li>• Output current of the interface, max.</li> </ul>  | Yes<br>150 mA  |
| <b>Protocols</b>   |  |
| <ul style="list-style-type: none"> <li>• MPI</li> <li>• PROFIBUS DP master</li> <li>• PROFIBUS DP slave</li> </ul>   | Yes<br>Yes<br>No   |
| <b>MPI</b>   |  |
| <ul style="list-style-type: none"> <li>• Number of connections</li> <li>• Transmission rate, max.</li> </ul>   | 44; If a diagnostics repeater is used on the line, the number of connection resources on the line is reduced by 1<br>12 Mbit/s       |
| <b>Services</b>  |  |
| <ul style="list-style-type: none"> <li>— PG/OP communication</li> <li>— Routing</li> <li>— Global data communication</li> <li>— S7 basic communication</li> <li>— S7 communication</li> <li>— S7 communication, as client</li> <li>— S7 communication, as server</li> </ul>  | Yes<br>Yes<br>No<br>No<br>Yes<br>Yes<br>Yes  |
| <b>PROFIBUS DP master</b>  |  |
| <ul style="list-style-type: none"> <li>• Number of connections, max.</li> <li>• Transmission rate, max.</li> <li>• Number of DP slaves, max.</li> </ul>  | 32; If a diagnostics repeater is used on the line, the number of connection resources on the line is reduced by 1<br>12 Mbit/s<br>32 |
| <b>Services</b>  |  |
| <ul style="list-style-type: none"> <li>— PG/OP communication</li> <li>— Routing</li> <li>— Global data communication</li> <li>— S7 basic communication</li> <li>— S7 communication</li> <li>— S7 communication, as client</li> <li>— S7 communication, as server</li> <li>— Equidistance</li> <li>— Isochronous mode</li> <li>— SYNC/FREEZE</li> </ul> | Yes<br>Yes<br>No<br>No<br>Yes<br>Yes<br>Yes<br>No<br>No<br>No  |

|   |   |
|---|---|
| — Activation/deactivation of DP slaves                            | No  |
| — Direct data exchange (slave-to-slave communication)             | No  |
| — DPV1  | Yes   |
| <b>Address area</b>   |   |
| — Inputs, max.  | 2 kbyte   |
| — Outputs, max.   | 2 kbyte   |
| <b>User data per DP slave</b>                                     |   |
| — User data per DP slave, max.                                    | 244 byte  |
| — Inputs, max.  | 244 byte  |
| — Outputs, max.   | 244 byte  |
| — Slots, max.   | 244   |
| — per slot, max.  | 128 byte  |
| <b>PROFIBUS DP slave</b>  |   |
| • Number of connections   | No configuration of CPU as DP slave   |
| <b>2. Interface</b>   |   |
| Interface type  | PROFINET  |
| Isolated  | Yes   |
| automatic detection of transmission rate                          | Yes; Autosensing  |
| Autonegotiation   | Yes   |
| Autocrossing  | Yes   |
| Change of IP address at runtime, supported                        | No  |
| <b>Interface types</b>  |   |
| • RJ 45 (Ethernet)  | Yes   |
| • Number of ports   | 2   |
| • integrated switch   | Yes   |
| <b>Protocols</b>  |   |
| • PROFINET IO Controller  | Yes   |
| • PROFINET IO Device  | No  |
| • PROFINET CBA  | No  |
| • PROFIBUS DP master  | No  |
| • PROFIBUS DP slave   | No  |
| • Open IE communication   | Yes   |
| • Web server  | No  |
| • Point-to-point connection                                       | No  |
| • Media redundancy  | Yes   |
| <b>PROFINET IO Controller</b>                                     |   |
| • Transmission rate, max.   | 100 Mbit/s  |
| <b>Services</b>   |   |
| — PG/OP communication   | Yes   |
| — S7 communication  | Yes   |
| — Isochronous mode  | No  |
| — Shared device   | Yes; Single mode only   |
| — Prioritized startup   | No  |
| — Number of connectable IO Devices, max.                          | 256; In redundant mode via both interfaces  |
| — Number of connectable IO Devices for RT, max.                   | 256   |
| — of which in line, max.  | 256   |
| — Activation/deactivation of IO Devices                           | No  |
| — IO Devices changing during operation (partner ports), supported | No  |
| — Device replacement without swap medium                          | Yes   |
| — Send cycles   | 250 µs, 500 µs, 1 ms, 2 ms, 4 ms  |
| — Updating time   | 250 µs to 512 ms, minimum value depends on the number of configured user data and the configured single or redundant mode |
| <b>Address area</b>   |   |
| — Inputs, max.  | 8 kbyte   |
| — Outputs, max.   | 8 kbyte   |
| — User data consistency, max.                                     | 1 024 byte  |
| <b>Open IE communication</b>                                      |   |
| • Number of connections, max.                                     | 94  |
| • Local port numbers used at the system end                       | 0, 20, 21, 25, 102, 135, 161, 34962, 34963, 34964, 65532, 65533, 65534, 65535   |

|   |   |
|---|---|
| • Keep-alive function, supported                      | Yes   |
| <b>3. Interface</b>                                   |   |
| Interface type  | PROFIBUS DP   |
| <b>Interface types</b>                                |   |
| • RS 485  | Yes   |
| • Output current of the interface, max.               | 150 mA  |
| <b>Protocols</b>                                      |   |
| • PROFIBUS DP master                                  | Yes   |
| • PROFIBUS DP slave                                   | No  |
| <b>PROFIBUS DP master</b>                             |   |
| • Number of connections, max.                         | 32  |
| • Transmission rate, max.                             | 12 Mbit/s   |
| • Number of DP slaves, max.                           | 125   |
| <b>Services</b>                                       |   |
| — PG/OP communication                                 | Yes   |
| — Routing   | Yes   |
| — Global data communication                           | No  |
| — S7 basic communication                              | No  |
| — S7 communication                                    | Yes   |
| — S7 communication, as client                         | Yes   |
| — S7 communication, as server                         | Yes   |
| — Equidistance  | No  |
| — Isochronous mode                                    | No  |
| — SYNC/FREEZE   | No  |
| — Activation/deactivation of DP slaves                | No  |
| — Direct data exchange (slave-to-slave communication) | No  |
| — DPV0  | Yes   |
| — DPV1  | Yes   |
| <b>Address area</b>                                   |   |
| — Inputs, max.  | 8 kbyte   |
| — Outputs, max.                                       | 8 kbyte   |
| <b>User data per DP slave</b>                         |   |
| — User data per DP slave, max.                        | 244 byte  |
| — Inputs, max.  | 244 byte  |
| — Outputs, max.                                       | 244 byte  |
| — Slots, max.   | 244   |
| — per slot, max.                                      | 128 byte  |
| <b>4. Interface</b>                                   |   |
| Interface type  | Pluggable synchronization submodule (FO)                            |
| Plug-in interface modules                             | Synchronization modules 6ES7960-1AA06-0XA0 or 6ES7960-1AB06-0XA0    |
| <b>5. Interface</b>                                   |   |
| Interface type  | Pluggable synchronization submodule (FO)                            |
| Plug-in interface modules                             | Synchronization modules 6ES7960-1AA06-0XA0 or 6ES7960-1AB06-0XA0    |
| <b>Protocols</b>                                      |   |
| <b>Redundancy mode</b>                                |   |
| <b>Media redundancy</b>                               |   |
| — Switchover time on line break, typ.                 | 200 ms  |
| — Number of stations in the ring, max.                | 50  |
| <b>SIMATIC communication</b>                          |   |
| • S7 routing  | Yes   |
| <b>Open IE communication</b>                          |   |
| • TCP/IP  | Yes; via integrated PROFINET interface and loadable FBs             |
| — Number of connections, max.                         | 94  |
| — Data length, max.                                   | 32 kbyte  |
| — several passive connections per port, supported     | Yes   |
| • ISO-on-TCP (RFC1006)                                | Yes; Via integrated PROFINET interface or CP 443-1 and loadable FBs |
| — Number of connections, max.                         | 94  |
| — Data length, max.                                   | 32 kbyte; 1 452 bytes via CP 443-1 Adv.                             |
| • UDP   | Yes; via integrated PROFINET interface and loadable FBs             |
| — Number of connections, max.                         | 94  |

|   |   |
|---|---|
| — Data length, max.   | 1 472 byte  |
| <b>Web server</b>   |   |
| • supported   | No  |
| <b>Isochronous mode</b>   |   |
| Equidistance  | No  |
| <b>communication functions / header</b>                             |   |
| PG/OP communication   | Yes   |
| • Number of connectable OPs without message processing              | 95  |
| • Number of connectable OPs with message processing                 | 95; When using Alarm_S/SQ and Alarm_D/DQ  |
| Data record routing   | Yes   |
| <b>Global data communication</b>                                    |   |
| • supported   | No  |
| <b>S7 basic communication</b>                                       |   |
| • communication function / S7 basic communication                   | No  |
| <b>S7 communication</b>   |   |
| • supported   | Yes   |
| • as server   | Yes   |
| • as client   | Yes   |
| • User data per job, max.   | 64 kbyte  |
| • User data per job (of which consistent), max.                     | 462 byte; 1 variable  |
| <b>S5 compatible communication</b>                                  |   |
| • supported   | Yes; (via CP max. 10 and FC AG_SEND and FC AG_RECV)   |
| • User data per job, max.   | 8 kbyte   |
| • User data per job (of which consistent), max.                     | 240 byte  |
| • Number of simultaneous AG-SEND/AG-RECV orders per CPU, max.       | 64/64   |
| <b>Standard communication (FMS)</b>                                 |   |
| • supported   | Yes; Via CP and loadable FB   |
| <b>Number of connections</b>  |   |
| • overall   | 96  |
| • usable for PG communication                                       |   |
| — reserved for PG communication                                     | 1   |
| — adjustable for PG communication, max.                             | 0   |
| • usable for OP communication                                       |   |
| — reserved for OP communication                                     | 1   |
| — adjustable for OP communication, max.                             | 0   |
| • usable for S7 basic communication                                 |   |
| — reserved for S7 basic communication                               | 0   |
| — adjustable for S7 basic communication, max.                       | 0   |
| • usable for S7 communication                                       |   |
| — reserved for S7 communication                                     | 0   |
| — adjustable for S7 communication, max.                             | 0   |
| • usable for routing  |   |
| — reserved for routing  | 0   |
| — adjustable for routing, max.                                      | 0   |
| <b>S7 message functions</b>   |   |
| Number of login stations for message functions, max.                | 95; Max. 95 with Alarm_S/SQ and Alarm_D/DQ (OPs); max. 16 with Alarm, Alarm_8, Alarm_8P, Notify and Notify_8 (e.g. WinCC) |
| Symbol-related messages   | No  |
| SCAN procedure  | No  |
| Program alarms  | Yes   |
| Process diagnostic messages   | Yes   |
| simultaneously active Alarm-S blocks, max.                          | 1 000; Simultaneously active alarm_S/SQ blocks or alarm_D/DQ blocks   |
| Alarm 8-blocks  | Yes   |
| • Number of instances for alarm 8 and S7 communication blocks, max. | 10 000  |
| • preset, max.  | 1 200   |
| Process control messages  | Yes   |
| Number of archives that can log on simultaneously (SFB 37 AR_SEND)  | 64  |
| <b>Test commissioning functions</b>                                 |   |
| Status block  | Yes   |

|  |  |
|--|--|
| Single step  | Yes  |
| Number of breakpoints  | 16   |
| <b>Status/control</b>  |  |
| • Status/control variable  | Yes; Up to 16 variable tables  |
| • Variables  | Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters |
| • Number of variables, max.  | 70   |
| <b>Forcing</b>   |  |
| • Forcing  | Yes  |
| • Forcing, variables   | Inputs/outputs, bit memories, distributed I/Os                       |
| • Number of variables, max.  | 512  |
| <b>Diagnostic buffer</b>   |  |
| • present  | Yes  |
| • Number of entries, max.  | 3 200  |
| — adjustable   | Yes  |
| — preset   | 120  |
| <b>Service data</b>  |  |
| • can be read out  | Yes  |
| <b>EMC</b>   |  |
| Emission of radio interference acc. to EN 55 011                           |  |
| • Limit class A, for use in industrial areas                               | Yes  |
| • Limit class B, for use in residential areas                              | No   |
| <b>configuration / header</b>  |  |
| Configuration software   |  |
| • STEP 7   | Yes  |
| configuration / programming / header                                       |  |
| • Command set  | see instruction list   |
| • Nesting levels   | 7  |
| • Access to consistent data in process image                               | Yes  |
| • System functions (SFC)   | see instruction list   |
| • System function blocks (SFB)   | see instruction list   |
| Programming language   |  |
| — LAD  | Yes  |
| — FBD  | Yes  |
| — STL  | Yes  |
| — SCL  | Yes  |
| — CFC  | Yes  |
| — GRAPH  | Yes  |
| — HiGraph®   | Yes  |
| configuration / programming / number of simultaneously active SFC / header |  |
| — RD_REC   | 8  |
| — WR_REC   | 8  |
| — WR_PARM  | 8  |
| — PARM_MOD   | 1  |
| — WR_DPARM   | 2  |
| — DPNRM_DG   | 8  |
| — RDSYSST  | 8  |
| — DP_TOPOL   | 1  |
| configuration / programming / number of simultaneously active SFB / header |  |
| — RDREC  | 8  |
| — WRREC  | 8  |
| <b>Know-how protection</b>   |  |
| • User program protection/password protection                              | Yes  |
| • Block encryption   | Yes; With S7 block Privacy   |
| <b>Dimensions</b>  |  |
| Width  | 50 mm  |
| Height   | 290 mm   |
| Depth  | 219 mm   |
| <b>Weights</b>   |  |
| Weight, approx.  | 995 g  |

last modified:

9/7/2023 



