

SIMATIC S7-400, CPU 417-4 CENTRAL PROCESSING UNIT WITH:
 20MB WORKING MEMORY, (10 MB CODE; 10 MB DATA) 1.
 INTERFACE MPI 12 MBIT/S, 2. INTERFACE PROFIBUS DP, 3./4.
 IF IFM MODULES PLUGGABLE



Figure similar

General information	
Product type designation	CPU 417-4
Firmware version	V4.0
Engineering with	
<ul style="list-style-type: none"> Programming package 	STEP 7 V5.2 SP1 HF3 or higher with HW update
CiR – Configuration in RUN	
CiR synchronization time, basic load	100 ms
CiR synchronization time, time per I/O byte	40 µs
Supply voltage	
Rated value (DC)	
<ul style="list-style-type: none"> 24 V DC 	Yes
Input current	
from backplane bus 5 V DC, max.	1.7 A
from backplane bus 24 V DC, max.	Total current consumption of the components connected to the MPI/DP interfaces, but no more than 150 mA per interface
Power loss	

Power loss, typ.	6 W
Memory	
Work memory	
<ul style="list-style-type: none"> integrated (for program) 	10 Mbyte
<ul style="list-style-type: none"> integrated (for data) 	10 Mbyte
<ul style="list-style-type: none"> expandable 	No
Load memory	
<ul style="list-style-type: none"> expandable FEPRM 	Yes; with Memory Card (FLASH)
<ul style="list-style-type: none"> expandable FEPRM, max. 	64 Mbyte
<ul style="list-style-type: none"> integrated RAM, max. 	256 kbyte
<ul style="list-style-type: none"> expandable RAM 	Yes; with Memory Card (RAM)
<ul style="list-style-type: none"> expandable RAM, max. 	16 Mbyte
Backup	
<ul style="list-style-type: none"> present 	Yes
<ul style="list-style-type: none"> with battery 	Yes; all data
<ul style="list-style-type: none"> without battery 	No
Battery	
Backup battery	
<ul style="list-style-type: none"> Backup current, typ. 	600 μ A
<ul style="list-style-type: none"> Backup current, max. 	1 810 μ A
<ul style="list-style-type: none"> Feeding of external backup voltage to CPU 	5 V DC to 15 V DC
CPU processing times	
for bit operations, typ.	0.03 μ s
for word operations, typ.	0.03 μ s
for fixed point arithmetic, typ.	0.03 μ s
for floating point arithmetic, typ.	0.09 μ s
CPU-blocks	
DB	
<ul style="list-style-type: none"> Number, max. 	8 192; DB 0 reserved
<ul style="list-style-type: none"> Size, max. 	64 kbyte
FB	
<ul style="list-style-type: none"> Number, max. 	6 144
<ul style="list-style-type: none"> Size, max. 	64 kbyte
FC	
<ul style="list-style-type: none"> Number, max. 	6 144
<ul style="list-style-type: none"> Size, max. 	64 kbyte
OB	
<ul style="list-style-type: none"> Number, max. 	see instruction list
<ul style="list-style-type: none"> Size, max. 	64 kbyte
<ul style="list-style-type: none"> Number of time alarm OBs 	8

• Number of delay alarm OBs	4
• Number of cyclic interrupt OBs	9
• Number of process alarm OBs	8
• Number of multicomputing OBs	1
Nesting depth	
• per priority class	24
• additional within an error OB	2

Counters, timers and their retentivity

S7 counter

• Number	2 048
Retentivity	
— adjustable	Yes
— lower limit	0
— upper limit	2 047
— preset	Z 0 to Z 7
Counting range	
— lower limit	0
— upper limit	999

S7 times

• Number	2 048
Retentivity	
— adjustable	Yes
— lower limit	0
— upper limit	2 047
— preset	No times retentive
Time range	
— lower limit	10 ms
— upper limit	9 990 s

IEC timer

• present	Yes
• Type	SFB

Data areas and their retentivity

retentive data area in total	Total working and load memory (with backup battery)
Flag	
• Number, max.	16 kbyte
• Retentivity available	Yes; MB 0 to MB 16383
• Retentivity preset	MB 0 to MB 15
• Number of clock memories	8; 1 memory byte

Address area

I/O address area

• Inputs	16 kbyte
• Outputs	16 kbyte
of which distributed	
— MPI/DP interface, inputs	2 kbyte
— MPI/DP interface, outputs	2 kbyte
— DP interface, inputs	8 kbyte; for each line that is operated in isochronous mode, i.e. to which an OB61 to 64 has been assigned, the distributed IO address areas are halved
— DP interface, outputs	8 kbyte; for each line that is operated in isochronous mode, i.e. to which an OB61 to 64 has been assigned, the distributed IO address areas are halved
Process image	
• Inputs, adjustable	16 kbyte
• Outputs, adjustable	16 kbyte
• Inputs, default	1 024 byte
• Outputs, default	1 024 byte
• consistent data, max.	244 byte
• Access to consistent data in process image	Yes
Subprocess images	
• Number of subprocess images, max.	15
Digital channels	
• Inputs	131 072
— of which central	131 072
• Outputs	131 072
— of which central	131 072
Analog channels	
• Inputs	8 192
— of which central	8 192
• Outputs	8 192
— of which central	8 192
Hardware configuration	
Number of expansion units, max.	21; of which 6 ER with K-bus
connectable OPs	63 without message processing, 16 with message processing
Multicomputing	Yes; 4 CPUs max. (with UR1 or UR2)
Interface modules	
• Number of connectable IMs (total), max.	6
• Number of connectable IM 460s, max.	6
• Number of connectable IM 463s, max.	4; IM 463-2
Number of DP masters	
• integrated	2
• via CP	10; via CP 443-5 Ext.
• via IM 467	4

<ul style="list-style-type: none"> Mixed mode IM + CP permitted via interface module Number of pluggable S5 modules (via adapter capsule in central device), max. 	<p>No; IM 467 cannot be used with CP 443-5 Ext., IM 467 cannot be used with CP 443-1 EX40 in PROFINET IO mode</p> <p>2; IF 964-DP</p> <p>6</p>
Number of operable FMs and CPs (recommended)	
<ul style="list-style-type: none"> FM CP, PtP 	<p>Limited by number of slots and number of connections</p> <p>CP 440: Limited by number of slots; CP 441: limited by number of connections</p>
<ul style="list-style-type: none"> CP, LAN PROFIBUS and Ethernet CPs 	<p>Limited by number of slots and number of connections</p> <p>14; incl. CP 443-5 Ext. and IM 467</p>
Slots	
<ul style="list-style-type: none"> required slots 	2
Time of day	
Clock	
<ul style="list-style-type: none"> Hardware clock (real-time) retentive and synchronizable Resolution Deviation per day (buffered), max. Deviation per day (unbuffered), max. 	<p>Yes</p> <p>Yes</p> <p>1 ms</p> <p>Power off</p> <p>Power on</p>
Operating hours counter	
<ul style="list-style-type: none"> Number 	8
Clock synchronization	
<ul style="list-style-type: none"> supported to MPI, master to MPI, slave to DP, master to DP, slave in AS, master in AS, slave to IF 964 DP 	<p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes; as Master or Slave</p>
1. Interface	
Physics	RS 485 / PROFIBUS
Isolated	Yes
Number of connection resources	MPI: 44, DP: 32
Functionality	
<ul style="list-style-type: none"> MPI PROFIBUS DP master PROFIBUS DP slave 	<p>Yes</p> <p>Yes</p> <p>Yes</p>
MPI	
<ul style="list-style-type: none"> Number of connections Transmission rate, max. 	<p>44</p> <p>12 Mbit/s</p>

Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	Yes
— S7 basic communication	Yes
— S7 communication	Yes
DP master	
• Number of connections, max.	32; If a diagnostics repeater is used on the line, the number of connection resources on the line is reduced by 1
• Transmission rate, max.	12 Mbit/s
• Number of DP slaves, max.	32
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	Yes
— S7 basic communication	Yes
— S7 communication	Yes
— Equidistance	Yes
— SYNC/FREEZE	Yes
— Activation/deactivation of DP slaves	Yes
— Direct data exchange (slave-to-slave communication)	Yes
Address area	
— Inputs, max.	2 kbyte
— Outputs, max.	2 kbyte
User data per DP slave	
— Inputs, max.	244 byte
— Outputs, max.	244 byte
— Slots, max.	244
— per slot, max.	128 byte
DP slave	
• Transmission rate, max.	12 Mbit/s
• Address area, max.	32
• User data per address area, max.	32 byte
— of which consistent, max.	32 byte
Services	
— PG/OP communication	Yes
— Routing	Yes
Transfer memory	
— Inputs	244 byte
— Outputs	244 byte

2. Interface

Physics	RS 485 / PROFIBUS
Isolated	Yes
Number of connection resources	32
Functionality	
• PROFIBUS DP master	Yes
• PROFIBUS DP slave	Yes
DP master	
• Number of connections, max.	32; If a diagnostics repeater is used on the line, the number of connection resources on the line is reduced by 1
• Transmission rate, max.	12 Mbit/s
• Number of DP slaves, max.	125
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	Yes
— S7 basic communication	Yes
— S7 communication	Yes
— Equidistance	Yes
— SYNC/FREEZE	Yes
— Activation/deactivation of DP slaves	Yes
— Direct data exchange (slave-to-slave communication)	Yes
Address area	
— Inputs, max.	8 kbyte
— Outputs, max.	8 kbyte
User data per DP slave	
— Inputs, max.	244 byte
— Outputs, max.	244 byte
— Slots, max.	244
— per slot, max.	128 byte
DP slave	
• Transmission rate, max.	12 Mbit/s
• Address area, max.	32
• User data per address area, max.	32 byte
— of which consistent, max.	32 byte
Services	
— Routing	Yes
Transfer memory	
— Inputs	244 byte
— Outputs	244 byte

3. Interface

Interface type	Pluggable interface module (IF), technical data as for 2nd interface
Plug-in interface modules	IF 964-DP

4. Interface

Interface type	Pluggable interface module (IF), technical data as for 2nd interface
Plug-in interface modules	IF 964-DP

Isochronous mode

Isochronous operation (application synchronized up to terminal)	Yes
Equidistance	Yes
User data per isochronous slave, max.	244 byte
shortest clock pulse	1 ms

Communication functions

PG/OP communication	Yes
Global data communication	
<ul style="list-style-type: none">supported	Yes
<ul style="list-style-type: none">Number of GD packets, transmitter, max.	16
<ul style="list-style-type: none">Number of GD packets, receiver, max.	32
<ul style="list-style-type: none">Size of GD packets, max.	64 byte
<ul style="list-style-type: none">Size of GD packet (of which consistent), max.	1 variable
S7 basic communication	
<ul style="list-style-type: none">supported	Yes; in MPI mode via: SFC X_SEND, X_RCV, X_GET and X_PUT; in DP master mode via: SFC I_GET and I_PUT
<ul style="list-style-type: none">User data per job, max.	76 byte
<ul style="list-style-type: none">User data per job (of which consistent), max.	1 variable
S7 communication	
<ul style="list-style-type: none">supported	Yes
<ul style="list-style-type: none">as server	Yes
<ul style="list-style-type: none">as client	Yes
<ul style="list-style-type: none">User data per job, max.	64 kbyte
<ul style="list-style-type: none">User data per job (of which consistent), max.	1 variable
S5 compatible communication	
<ul style="list-style-type: none">supported	Yes; Via FC AG_SEND and AG_RECV, max. via 10 CP 443-1 or 443-5
<ul style="list-style-type: none">User data per job, max.	8 kbyte
Standard communication (FMS)	
<ul style="list-style-type: none">supported	Yes; Via CP and loadable FB
Number of connections	
<ul style="list-style-type: none">overall	64
<ul style="list-style-type: none">usable for PG communication	

— reserved for PG communication	1
• usable for OP communication	
— reserved for OP communication	1

S7 message functions

Number of login stations for message functions, max.	16
Symbol-related messages	Yes
Program alarms	Yes
simultaneously active Alarm-S blocks, max.	ALARM_S/SQ blocks or ALARM_D/DQ blocks
Alarm 8-blocks	Yes
• Number of instances for alarm 8 and S7 communication blocks, max.	Number of communication jobs for Alarm_8 blocks and for blocks for S7 Communication
Process control messages	Yes

Number of messages

• overall, max.	1 024
• in 100 ms grid, max.	128
• in 500 ms grid, max.	512
• in 1000 ms grid, max.	1 024

Number of additional values

• with 100 ms grid, max.	1
• with 500, 1000 ms grid, max.	10

Test commissioning functions

Status block	Yes
Single step	Yes
Number of breakpoints	4

Status/control

• Status/control variable	Yes
---------------------------	-----

Forcing

• Forcing	Yes
-----------	-----

Diagnostic buffer

• present	Yes
• Number of entries, max.	3 200
— adjustable	Yes
— preset	120

Configuration

Configuration software

• STEP 7	Yes
----------	-----

Programming

• Nesting levels	8
------------------	---

Programming language

— LAD	Yes
— FBD	Yes

- STL Yes
- SCL Yes
- CFC Yes
- GRAPH Yes
- HiGraph® Yes

Number of simultaneously active SFCs

- RDSYSST 1 to 8

Know-how protection

- User program protection/password protection Yes

Dimensions

Width	50 mm
Height	290 mm
Depth	219 mm

Weights

Weight, approx. 1 070 g

last modified: 03/16/2018