

SIMATIC S7-400, ANALOG INPUT SM 431, NON-ISOLATED 16 AI,  
RESOLUTION 13 BITS, +/-10V, +/-20MA, 4 - 20MA 20 MS MODULE  
UPDATE



Figure similar

### Supply voltage

#### Load voltage L+

- Rated value (DC) 24 V; Only required for supplying 2-wire transmitters
- Reverse polarity protection Yes

### Input current

|   |  |
|---|--|
| from load voltage L+ (without load), max. | 400 mA; for 16 connected, fully controlled 2-wire transmitters |
| from backplane bus 5 V DC, max.           | 100 mA   |

### Power loss

|                  |     |
|------------------|-----|
| Power loss, typ. | 2 W |
|------------------|-----|

### Analog inputs

|  |  |
|--|--|
| Number of analog inputs  | 16   |
| • For voltage/current measurement  | 16   |
| permissible input voltage for voltage input<br>(destruction limit), max. | 20 V; 20 V DC permanent, 75 V DC for max. 1 s (duty factor 1:20) |
| permissible input current for current input (destruction<br>limit), max. | 40 mA  |

|  |  |
|--|--|
| <b>Input ranges</b>  |  |
| • Voltage  | Yes  |
| • Current  | Yes  |
| • Thermocouple   | No   |
| • Resistance thermometer   | No   |
| • Resistance   | No   |
| <b>Input ranges (rated values), voltages</b>                           |  |
| • 1 V to 5 V   | Yes  |
| • Input resistance (1 V to 5 V)  | 100 kΩ   |
| • -1 V to +1 V   | Yes  |
| • Input resistance (-1 V to +1 V)                                      | 10 MΩ  |
| • -10 V to +10 V   | Yes  |
| • Input resistance (-10 V to +10 V)                                    | 100 kΩ   |
| <b>Input ranges (rated values), currents</b>                           |  |
| • -20 mA to +20 mA   | Yes  |
| • Input resistance (-20 mA to +20 mA)                                  | 50 Ω   |
| • 4 mA to 20 mA  | Yes  |
| • Input resistance (4 mA to 20 mA)                                     | 50 Ω   |
| <b>Cable length</b>  |  |
| • shielded, max.   | 200 m  |
| <b>Analog value generation for the inputs</b>                          |  |
| Integration and conversion time/resolution per channel                 |  |
| • Resolution with overrange (bit including sign), max.                 | 13 bit   |
| • Integration time, parameterizable                                    | Yes  |
| • Basic conversion time (ms)   | 55 / 65 ms   |
| • Integration time (ms)  | 50 / 60 ms   |
| • Interference voltage suppression for interference frequency f1 in Hz | 50 / 60 Hz   |
| <b>Encoder</b>   |  |
| Connection of signal encoders  |  |
| • for voltage measurement  | Yes; possible                                      |
| • for current measurement as 4-wire transducer                         | Yes  |
| <b>Errors/accuracies</b>   |  |
| Operational error limit in overall temperature range                   |  |
| • Voltage, relative to input range, (+/-)                              | 0.65 %; 1.0% at 1 to 5 V; 0.65% at +/-1 V, +/-10 V |
| • Current, relative to input range, (+/-)                              | 0.65 %   |
| Basic error limit (operational limit at 25 °C)                         |  |
| • Voltage, relative to input range, (+/-)                              | 0.25 %; 0.5% at 1 to 5 V; 0.25% at +/-1 V, +/-10 V |
| • Current, relative to input range, (+/-)                              | 0.25 %; at +/-20 mA, 4 to 20 mA                    |

## Potential separation

Potential separation analog inputs

- Potential separation analog inputs No
- between the channels No

## Isolation

Isolation tested with 500 V AC/707 V DC, type test

## Dimensions

|        |        |
|--------|--------|
| Width  | 25 mm  |
| Height | 290 mm |
| Depth  | 210 mm |

## Weights

Weight, approx. 500 g

**last modified:** 03/24/2017