



SIMATIC S7-400, analog input SM 431, isolated 8 AI, resolution 13 bit, U/I/Resistor

Figure similar

Supply voltage	
Load voltage L+	
<ul style="list-style-type: none"> <li>Rated value (DC)</li> </ul>	not necessary
Input current	
from backplane bus 5 V DC, max.	350 mA
Power loss	
Power loss, typ.	1.8 W
Analog inputs	
Number of analog inputs	8
<ul style="list-style-type: none"> <li>For voltage/current measurement</li> </ul>	8
<ul style="list-style-type: none"> <li>For resistance measurement</li> </ul>	4
permissible input voltage for voltage input (destruction limit), max.	50 V
permissible input current for current input (destruction limit), max.	50 mA; 40 mA continuous
Constant measurement current for resistance-type transmitter, typ.	1.67 mA
Input ranges	
<ul style="list-style-type: none"> <li>Voltage</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Current</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Thermocouple</li> </ul>	No
<ul style="list-style-type: none"> <li>Resistance thermometer</li> </ul>	No
<ul style="list-style-type: none"> <li>Resistance</li> </ul>	Yes
Input ranges (rated values), voltages	
<ul style="list-style-type: none"> <li>1 V to 5 V</li> <li>— Input resistance (1 V to 5 V)</li> </ul>	Yes 200 kΩ
<ul style="list-style-type: none"> <li>-1 V to +1 V</li> <li>— Input resistance (-1 V to +1 V)</li> </ul>	Yes 200 kΩ
<ul style="list-style-type: none"> <li>-10 V to +10 V</li> <li>— Input resistance (-10 V to +10 V)</li> </ul>	Yes 200 kΩ
Input ranges (rated values), currents	
<ul style="list-style-type: none"> <li>-20 mA to +20 mA</li> <li>— Input resistance (-20 mA to +20 mA)</li> </ul>	Yes 80 Ω
<ul style="list-style-type: none"> <li>4 mA to 20 mA</li> <li>— Input resistance (4 mA to 20 mA)</li> </ul>	Yes 80 Ω
Input ranges (rated values), resistors	
<ul style="list-style-type: none"> <li>0 to 600 ohms</li> <li>— Input resistance (0 to 600 ohms)</li> </ul>	Yes usable up to 500 ohms
Cable length	
<ul style="list-style-type: none"> <li>shielded, max.</li> </ul>	200 m

Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
<ul style="list-style-type: none"> <li>Resolution with overrange (bit including sign), max.</li> <li>Integration time, parameterizable</li> <li>Basic conversion time (ms)</li> <li>Integration time (ms)</li> <li>Interference voltage suppression for interference frequency <math>f_1</math> in Hz</li> <li>Basic execution time of the module (all channels released)</li> </ul>	13 bit Yes 23 / 25 ms 16,7 / 20 ms 50 / 60 Hz 200 ms; 184 / 200 ms
Encoder	
Connection of signal encoders	
<ul style="list-style-type: none"> <li>for voltage measurement</li> <li>for current measurement as 2-wire transducer</li> <li>for current measurement as 4-wire transducer</li> <li>for resistance measurement with two-wire connection</li> <li>for resistance measurement with three-wire connection</li> <li>for resistance measurement with four-wire connection</li> </ul>	Yes; possible Yes; with external transmitter supply Yes Yes; Line resistances are also measured Yes; Line resistances are also measured Yes
Errors/accuracies	
Temperature error (relative to input range), (+/-)	0.02 %/K; $\pm 0.02$ %/K in impedance measuring range; $\pm 0.007$ % in all other measuring ranges
Operational error limit in overall temperature range	
<ul style="list-style-type: none"> <li>Voltage, relative to input range, (+/-)</li> <li>Current, relative to input range, (+/-)</li> <li>Resistance, relative to input range, (+/-)</li> </ul>	1 %; $\pm 1.0$ % at $\pm 1$ V; $\pm 0.6$ % at $\pm 10$ V; $\pm 0.7$ % at 1 to 5 V 1 %; at $\pm 20$ mA, 4 to 20 mA 1.25 %; 0 to 500 ohms (4-conductor measurement, in range of 600 ohms)
Basic error limit (operational limit at 25 °C)	
<ul style="list-style-type: none"> <li>Voltage, relative to input range, (+/-)</li> <li>Current, relative to input range, (+/-)</li> <li>Resistance, relative to input range, (+/-)</li> </ul>	0.7 %; 0.7% at $\pm 1$ V; 0.4% at $\pm 10$ V; 0.5% at 1 to 5 V 0.7 %; at $\pm 20$ mA, 4 to 20 mA 0.8 %; 0 to 500 ohms (4-conductor measurement, in range of 600 ohms)
Interrupts/diagnostics/status information	
Diagnostics function	No
Potential separation	
Potential separation analog inputs	
<ul style="list-style-type: none"> <li>Potential separation analog inputs</li> <li>between the channels</li> <li>between the channels and backplane bus</li> </ul>	Yes; internal/external No Yes
Isolation	
Isolation tested with	2 120 V DC between bus and analog part; 500 V DC between bus and local ground; 2 120 V DC between analog part and local ground
Dimensions	
Width	25 mm
Height	290 mm
Depth	210 mm
Weights	
Weight, approx.	500 g

last modified: 8/7/2023 