

SIMATIC S7-400, CP 441-1 COMMUNICATIONS MODULE FOR POINT TO POINT CONNECTIONS 1 CHANNEL INCL. CONFIG. PACKAGE ON CD

Supply voltage

Rated value (DC)

- | | |
|-----------|-----|
| • 5 V DC | Yes |
| • 24 V DC | Yes |

Input current

from backplane bus 5 V DC, max.	700 mA; Without interface module
---------------------------------	----------------------------------

Interface modules

- | | |
|---|------------------------------|
| • 20 mA (TTY), power consumption from 5 V/24 V, max. | 300 mA at 5 V, 45 mA at 24 V |
| • RS 422/485 (X.27), power consumption from 5 V, max. | 300 mA |
| • RS 232C (V.24), power consumption from 5 V, max. | 300 mA |

Memory

Memory requirements per interface in memory card of S7-CPU	1 to 5 KB for parameters; 0 to 55 KB for message texts
--	--

Interfaces

Number of interfaces	1; variable
Interface physics, 20 mA (TTY)	Yes
Interface physics, RS 232C (V.24)	Yes
Interface (physical) RS 422/485 (X.27)	Yes
20 mA (TTY), cable length shielded, max.	1 000 m
RS 232, cable length shielded, max.	10 m
RS 422/RS 485, cable length shielded, max.	1 200 m

Point-to-point

- | | |
|---------------------------|---|
| • Transmission rate, max. | 38.4 kbit/s |
| • supported printers | HP-Deskjet, HP-Laserjet, IBM-Proprinter, user-defined |

Integrated protocol driver

- | | |
|------------|-----|
| — 3964 (R) | Yes |
| — ASCII | Yes |
| — Printer | Yes |

Transmission rate, 20 mA (TTY)

- | | |
|--------------------------------|-------------|
| — with 3964 (R) protocol, max. | 19.2 kbit/s |
| — with ASCII protocol, max. | 19.2 kbit/s |

— with printer driver, max.	19.2 kbit/s
Transmission rate, RS 422/485	
— with 3964 (R) protocol, max.	38.4 kbit/s
— with ASCII protocol, max.	38.4 kbit/s
— with printer driver, max.	38.4 kbit/s
Transmission speed, RS 232	
— with 3964 (R) protocol, max.	38.4 kbit/s
— with ASCII protocol, max.	38.4 kbit/s
— with printer driver, max.	38.4 kbit/s

Communication functions

S7 communication	
• S7 extended communication	Yes
Number of connections	
• overall	8

Configuration

Configuration software	
• STEP 7	Yes; own parameter assignment forms

Dimensions

Width	25 mm
Height	290 mm
Depth	210 mm

Weights

Weight, approx.	720 g; Interface module: 100 g
last modified:	03/15/2018