

SIMATIC S7-1500, Front connector in push-in design, 40-pole, for 35 mm wide modules incl. 4 potential bridges and cable ties



General information

Product type designation Front connector

Connection method

Connection I/O signals

- | | |
|---|--|
| <ul style="list-style-type: none"> • Connection method • Number of lines per connection | <p>Push-in terminal</p> <p>1; or combination of 2 conductors of up to 1.5 mm² (total) in a shared ferrule</p> |
|---|--|

Conductor cross-section in mm²

- | | |
|--|--|
| <ul style="list-style-type: none"> — Connectable cable cross-sections for massive cables, min. — Connectable cable cross-sections for massive cables, min. — Connectable cable cross-sections for flexible cables without end sleeve, min. — Connectable cable cross-sections for flexible cables without end sleeve, max. — Connectable cable cross-sections for flexible cables with end sleeve, min. | <p>0.25 mm²</p> <p>1.5 mm²</p> <p>0.25 mm²</p> <p>1.5 mm²</p> <p>0.25 mm²</p> |
|--|--|

— Connectable cable cross-sections for flexible cables with end sleeve, max.	1.5 mm ²
Conductor cross-section acc. to AWG	
— Connectable cable cross-sections for massive cables, min.	24
— Connectable cable cross-sections for massive cables, min.	16
— Connectable cable cross-sections for flexible cables without end sleeve, min.	24
— Connectable cable cross-sections for flexible cables without end sleeve, max.	16
— Connectable cable cross-sections for flexible cables with end sleeve, min.	24
— Connectable cable cross-sections for flexible cables with end sleeve, max.	16
Wire end processing	
— Stripped length of cables, min.	8 mm
— Stripped length of cables, max.	11 mm
— End sleeve acc. to DIN 46228 without plastic sleeve	Form A, 10 mm long
— End sleeve acc. to DIN 46228 with plastic sleeve	Form E, 8 mm and 10 mm long
Mounting	
— Tool	Screwdriver, conical design, 3 mm to 3.5 mm
Dimensions	
Width	29.8 mm
Height	130.5 mm
Depth	46 mm
Weights	
Weight, approx.	123 g
last modified:	09/27/2019