Data sheet

6ES7922-3BD01-0AM0

S7-300 FF	CONTSTECK	FR 20 TO	DR25F	3M NFU

Cable with front connector for SIMATIC S7-300 20 pole (6ES7392-1AJ00-0AA0) on 25 pole D-SUB socket for ET200M: 0.14 mm2 Length = 3 m

	25 pole D-SUB socket for ET200M; 0.14 mm2 Length = 3 m
target system	SIMATIC S7-300 PCS7 MTA
product type designation	MTA
product designation	Pre-assembled front connector MTA
Product properties, functions, components / general	/ header
wire length	3 m
design of cable	Round cable
material / of the connection cable sheath	PVC
color / of cable sheath	Black
outer diameter / of cable sheath	7.6 mm; bundled single cores
conductor cross section / rated value	0.5 mm ²
number of channels	20
number of poles	20; of the front connector
Operating data / header	
operating voltage / at DC	
rated value	24 V
• maximum	30 V
ambient temperature	
 during storage 	-30 +70 °C
 during operation 	0 60 °C
General data / header	
certificate of suitability / cULus approval	No
suitability for interaction	
input card PLC	Yes
PLC output card	Yes
suitability for use	
 digital signal transmission 	Yes
analog signal transmission	Yes
type of electrical connection	
• in the field	Connector strip
• on enclosure	Screw-type terminal
reference code / according to IEC 81346-2	WG
net weight	0.42 kg

