

Product type designation

PROFIBUS bus connector, RS485, Fast Connect, with PG socket, 35°

Product description

PROFIBUS bus connector, RS485, Fast Connect, with PG socket, 35°
SIMATIC DP, BUS CONNECTOR FOR PROFIBUS UP TO 12 MBIT/S 35 DEGREE ANGLE CABLE OUTLET, IPCD TECHNOLOGY FAST CONNECT, WITH PG SOCKET 15,8 X 54 X 39,5 MM (WXHXD),



Suitability for use

For connecting PROFIBUS nodes to the PROFIBUS bus cable

Transmission rate

Transfer rate / with PROFIBUS DP

9.6 kbit/s ... 12 Mbit/s

Interfaces

Number of electrical connections

- for PROFIBUS cables
- for network components or terminal equipment

2

1

Type of electrical connection / FastConnect

Yes

Mechanical data

Design of terminating resistor

Integrated resistor combination that can be selected with slide switch

Material / of the enclosure

plastic

Design, dimensions and weight

Width

15.8 mm

Height

54 mm

Depth

39.5 mm

Net weight

34 g

Permitted ambient conditions

Ambient temperature

- during storage

-40 ... +70 °C

| | |
|--|----------------|
| <ul style="list-style-type: none"> • during transport | -40 ... +70 °C |
| Protection class IP | IP20 |
| Product properties, functions, components / general | |
| Product property | |
| <ul style="list-style-type: none"> • silicon-free | Yes |
| Product component | |
| <ul style="list-style-type: none"> • PG connection socket | Yes |
| <ul style="list-style-type: none"> • strain relief | Yes |
| Standards, specifications, approvals | |
| Certificate of suitability | |
| <ul style="list-style-type: none"> • RoHS conformity | Yes |
| <ul style="list-style-type: none"> • UL approval | Yes |
| last modified: | 24.04.2015 |