

SIMATIC NET,
REPEATER FOR AS-INTERFACE FOR CABLE
PROLONGATION IN K45 HOUSING



General technical data:

Design of the slave type		no slave integrated
Voltage supply / using AS-Interface		Yes

Operating voltage

<ul style="list-style-type: none"> according to AS Interface specification 	V	26.5 ... 31.6
---	---	---------------

Connections:


AS interface		
<ul style="list-style-type: none"> Connection / Polarity reversal protection 		yes
<ul style="list-style-type: none"> total current input / max 	mA	20

Ambient conditions:

Ambient temperature		
<ul style="list-style-type: none"> during operating 	°C	-25 ... +60
Protection class IP		IP67

Certificates/approvals:

AS-Interface certificate		requested
---------------------------------	--	-----------

General Product Approval	Test Certificates	other
ROSTEST	other	Manufacturer
		

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/6GK1210-0SA01/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=6GK1210-0SA01

last change:

Feb 11, 2012