

Product type designation

CP 5611 A2

COMMUNICATION PROCESSOR CP 5611 A2 PCI-CARD (32 BIT; 3.3/5V;33/ 66 MHZ) FOR CONNECTION TO PG OR PC WITH PCI-BUS TO PROFIBUS OR MPI (NO WIN9X-SUPPORT!) CURRENTLY ONLY 32BIT SUPPORT IN CONNECTION WITH SIMATIC NET V8.2 SW! ONLY FOR EXIST. APPLIC.; FOR WIN XP OR HIGHER 6GK1561-2AA00 RECOMMENDED SEE [HTTP://SUPPORT.AUTOMATION.SIEMENS.COM/WW/VIEW/ EN/84138725](http://support.automation.siemens.com/ww/view/EN/84138725)



Transmission rate

Transfer rate	
<ul style="list-style-type: none"> at the 1st interface / acc. to PROFIBUS 	9.6 kbit/s ... 12 Mbit/s

Interfaces

Number of electrical connections	
<ul style="list-style-type: none"> at the 1st interface / acc. to PROFIBUS 	1
Type of electrical connection	
<ul style="list-style-type: none"> at the 1st interface / acc. to PROFIBUS 	9-pin Sub-D socket (RS 485)

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage	DC
Supply voltage	
<ul style="list-style-type: none"> 1 / from backplane bus 	5 V
Relative symmetrical tolerance / at DC	
<ul style="list-style-type: none"> at 5 V 	5 %
Consumed current	
<ul style="list-style-type: none"> 1 / from backplane bus / at DC / maximum 	0.5 A
Active power loss	2.5 W

Permitted ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> during operation during storage during transport 	5 ... 55 °C -20 ... +60 °C -20 ... +60 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP00

Design, dimensions and weight

Module format	PCI
Width	18 mm
Height	102 mm
Depth	130 mm
Net weight	100 g
Number of plug-in cards of same design / plug-in / per PC station	1
Number of units / Note	-

Performance data

Performance data / open communication

Software / for open communication / by means of SEND/RECEIVE / required	Yes, SOFTNET-PB DP / SOFTNET-PB DP Slave / SOFTNET-PB S7
Number of possible connections / for open communication / by means of SEND/RECEIVE / maximum	50

Performance data / PROFIBUS DP

Software / for DP master function / required	Yes, SOFTNET-PB DP
Service / as DP master	
<ul style="list-style-type: none"> DPV0 DPV1 DPV2 	Yes Yes No
Number of DP slaves / on DP master / usable	64
Amount of data	
<ul style="list-style-type: none"> of the address area of the inputs / as DP master / total of the address area of the outputs / as DP master / total of the address area of the inputs / per DP slave of the address area of the outputs / per DP slave of the address area of the diagnostic data / per DP slave 	14640 byte 14640 byte 244 byte 244 byte 244 byte
Software / for DP slave function / required	Yes, SOFTNET-PB DP slave

Service / as DP slave	
• DPV0	Yes
• DPV1	No
Amount of data	
• of the address area of the inputs / as DP slave / total	122 byte
• of the address area of the outputs / as DP slave / total	122 byte

Performance data / S7 communication

Software / for S7 communication / required	Yes, SOFTNET-PB S7
Number of possible connections / for S7/PG communication / maximum	8

Performance data / multi-protocol mode

Number of configurable connections / per PC station	207
---	-----

Product functions / management, configuration

Configuration software / required	Included in the scope of delivery of the required software product
-----------------------------------	--

Product functions / Diagnosis

Product function	
• Port diagnostics	Yes

Standards, specifications, approvals

Standard	
• for EMC	89/336/EEC
• for safety / from CSA and UL	CAN/CSA C22.2 & UL 60950-1, UL 1950
• for emitted interference	EN 61000-6-3
• for interference immunity	EN 61000-6-2
Certificate of suitability	
• CE marking	Yes
• C-Tick	Yes

Accessories

accessories	optional: MPI cable
-------------	---------------------

Further Information / Internet Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	http://www.siemens.com/industrial-controls/mall
• to website: Information and Download Center	http://www.siemens.com/automation/net/catalog
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

20.07.2015