

product type designation

CP 5623

Communications processor CP 5623 PCI Express X1 (3, 3V) for connection to PROFIBUS; incl. DP-Base software, NCM PC: DP-RAM interface for DP master incl. PG and FDL protocol, Single license for 1 installation, Runtime software, Class A; software and electr. manual on CD-ROM, 2 languages (de, en) ; Operating system support see SIMATIC NET software



transfer rate

transfer rate

- at the 1st interface / acc. to PROFIBUS 9.6 kbit/s ... 12 Mbit/s

interfaces

number of electrical connections

- at the 1st interface / acc. to PROFIBUS 1

type of electrical connection

- at the 1st interface / acc. to PROFIBUS 9-pin Sub-D socket (RS 485)

supply voltage, current consumption, power loss

type of voltage / of the supply voltage

DC

supply voltage

- 1 / from backplane bus 3.3 V
- 2 / from backplane bus 12 V

relative symmetrical tolerance / at DC

- at 3.3 V 9 %
- at 12 V 8 %

consumed current

• 1 / from backplane bus / at DC / maximum	0.72 A
• 2 / from backplane bus / at DC / maximum	0.25 A
power loss [W]	5.4 W

ambient conditions

ambient temperature	
• during operation	5 ... 60 °C
• during storage	-20 ... +60 °C
• during transport	-20 ... +60 °C
relative humidity / at 25 °C / without condensation / during operation / maximum	85 %
protection class IP	IP00

design, dimensions and weights

module format	PCI Express x1 (half length)
width	21.6 mm
height	126.3 mm
depth	180.5 mm
net weight	102 g

product features, product functions, product components / general

number of plug-in cards of same design / plug-in / per PC station	4
number of units / note	FMS-5613 supports up to two CP 5603 / CP 5613 A2 / CP 5614 A2 / CP 5623 / CP 5624 processors

performance data

performance data / open communication

software / for open communication / by means of SEND/RECEIVE / required	FDL driver included in scope of delivery of the CP
number of possible connections / for open communication / by means of SEND/RECEIVE / maximum	80

performance data / PROFIBUS DP

software / for DP master function / required	No
service / as DP master	
• DPV0	Yes
• DPV1	Yes
• DPV2	Yes
number of DP slaves / on DP master / usable	124
amount of data	
• of the address area of the inputs / as DP master / total	30256 byte
• of the address area of the outputs / as DP master / total	30256 byte

<ul style="list-style-type: none"> • of the address area of the inputs / per DP slave 	244 byte
<ul style="list-style-type: none"> • of the address area of the outputs / per DP slave 	244 byte
<ul style="list-style-type: none"> • of the address area of the diagnostic data / per DP slave 	244 byte
software / for DP slave function / required	No
service / as DP slave	
<ul style="list-style-type: none"> • DPV0 	Yes
<ul style="list-style-type: none"> • DPV1 	Yes
amount of data	
<ul style="list-style-type: none"> • of the address area of the inputs / as DP slave / total 	244 byte
<ul style="list-style-type: none"> • of the address area of the outputs / as DP slave / total 	244 byte

performance data / FMS functions

software / for FMS communication / required	Yes, FMS-5613
number of possible connections / for FMS connection / maximum	40

performance data / S7 communication

software / for S7 communication / required	Yes, HARDNET-PB S7 (S7-5613)
number of possible connections / for S7/PG communication / maximum	50

performance data / multi-protocol mode

number of active connections / with multi-protocol mode	50
number of configurable connections / per PC station	207

product functions / management, configuration, engineering

configuration software / required	Included in scope of supply
-----------------------------------	-----------------------------

product functions / diagnostics

product function	
<ul style="list-style-type: none"> • port diagnostics 	Yes

standards, specifications, approvals

standard	
<ul style="list-style-type: none"> • for EMC 	2004/108/EC
<ul style="list-style-type: none"> • for safety / from CSA and UL 	CAN/CSA C22.2 & UL 60950-1
<ul style="list-style-type: none"> • for emitted interference 	EN 61000-6-3, EN 61000-6-4
<ul style="list-style-type: none"> • for interference immunity 	EN 61000-6-1, EN 61000-6-2
certificate of suitability	
<ul style="list-style-type: none"> • CE marking 	Yes
<ul style="list-style-type: none"> • C-Tick 	Yes

further information / internet-Links

Internet-Link

- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/snst>

<http://www.siemens.com/simatic-net>

<http://www.siemens.com/industrial-controls/mall>

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

security information

security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

09/11/2020