

IE FC RJ45 PLUG 180 4X2,
RJ45 CONNECTOR (10/100/1000MBIT/S) WITH ROBUST
METAL HOUSING AND FC CONNECTING METHOD,
FOR IE FC CABLE 4X2 (AWG24),
180 DGR OUTGOING CABLE 1 PACKAGE = 10 PIECES



Transfer rate

- | | |
|-------------------------------|-------------|
| • 1 / for Industrial Ethernet | 10 Mbit/s |
| • 2 / for Industrial Ethernet | 100 Mbit/s |
| • 3 / for Industrial Ethernet | 1000 Mbit/s |

Interfaces

Number of electrical connections	
• for Industrial Ethernet FC TP cables	8
• for network components and terminal equipment	1
Design of the electrical connection / FastConnect	Yes

Mechanical data

material / of the housing	metal
---------------------------	-------

Design, dimensions and weight

Width	13.7 mm
Height	16 mm
Depth	55 mm
Net weight	35 g

Permitted ambient conditions

Ambient temperature	
• during operating	-40 ... +70 °C
• during storage	-40 ... +80 °C
• during transport	-40 ... +80 °C

Relative humidity	
<ul style="list-style-type: none"> • at 25 °C / without condensation / during operating / maximum 	95 %
Protection class IP	IP20
Product properties, functions, components / general	
Product feature / [not supplied - silicon-free]	Yes
Composant produit	
<ul style="list-style-type: none"> • décharge de traction 	Yes
Standards, specifications, approvals	
Verification of suitability	
<ul style="list-style-type: none"> • RoHS conformity 	Yes
<ul style="list-style-type: none"> • UL-registration 	Yes
letzte Änderung:	May 14, 2012