SIEMENS

Data sheet 6GK1906-0EB00

Product type designation

Power M12 Cable Connector PRO

Power M12 cable connector PRO axial cable outlet for field assembly, socket insert L-coded (socket) 1 pack = 1 unit



Suitability for use	For 24 V DC power supply of devices with L-coded M12 interface
Interfaces	
Number of electrical connections	
• for network components or terminal equipment	1
Type of electrical connection	
 for network components or terminal equipment 	M12 connector (female contact insert, 4-pole, L-coded)
Type of electrical connection / FastConnect	No
Electrical data	
Ampacity / up to 70 °C / maximum	12 A
Mechanical data	
Material / of the enclosure	metal
Locking mechanism design	Screw
Connector coding / of the M12 circular connector	L
Design, dimensions and weight	
Type of cable outlet	180° cable outlet
Width	23 mm
Height	23 mm

Depth	66.1 mm
Net weight	96 g
Connectable cable cross-section	7 9 mm
 finely stranded / with core end processing 	1.5 mm²
• finely stranded / without core end processing	1.5 mm²

Ambient conditions	
Ambient temperature	
during operation	-40 +105 °C
during storage	-40 +105 °C
 during transport 	-40 +105 °C
Chemical resistance	
• to water	resistant
Protection class IP	IP67

Product features, product functions, product components / general		
Product feature		
• silicon-free	Yes	
Product component		
• strain relief	Yes	

Standards, specifications, approvais	
Certificate of suitability	

RoHS conformity
 UL approval
 Railway application in accordance with EN
 No

Further information / Internet-Links

Internet-Link	
• to website: Selector SIMATIC NET	

SELECTION TOOL

• to website: Industrial communication

• to website: Industry Mall

• to website: Information and Download Center

• to website: Image database

• to website: CAx Download Manager

• to website: Industry Online Support

• to website: Industry Online Support

• to website: Industry Online Support

last modified: 01/20/2020

http://www.siemens.com/snst