

SCALANCE XC106-2, Unmanaged IE switch, 6x 10/100 Mbit/s RJ45 ports, 2x 100 Mbit/s Multimode BFOC, LED diagnostics, error-signaling contact with set button, redundant Power supply Manual available as a download



| | |
|--|--|
| Product type designation | SCALANCE XC106-2 |
| Transmission rate | |
| Transfer rate | 10 Mbit/s, 100 Mbit/s |
| Interfaces / for communication / integrated | |
| Number of electrical connections | |
| • for network components or terminal equipment | 6; RJ45 |
| Number of 100 Mbit/s ST(BFOC) ports | |
| • for multimode | 2 |
| Interfaces / others | |
| Number of electrical connections | |
| • for signaling contact | 1 |
| • for power supply | 1 |
| • for redundant voltage supply | 1 |
| Type of electrical connection | |
| • for signaling contact | 2-pole terminal block |
| • for power supply | 3-pole terminal block, permanently installed |
| Signal-Inputs/outputs | |

| | |
|---|-------|
| Operating voltage / of the signaling contacts | |
| <ul style="list-style-type: none"> • at DC / Rated value | 24 V |
| Operating current / of the signaling contacts | |
| <ul style="list-style-type: none"> • at DC / maximum | 0.1 A |

Supply voltage, current consumption, power loss

| | |
|--|----------------|
| Type of voltage / of the supply voltage | DC |
| Supply voltage | |
| <ul style="list-style-type: none"> • external | 24 V |
| <ul style="list-style-type: none"> • external / minimum | 9.6 V |
| <ul style="list-style-type: none"> • external / maximum | 31.2 V |
| Supply voltage / 1 / Rated value | 12 V |
| <ul style="list-style-type: none"> • Supply voltage / 1 / rated value | 9.6 ... 31.2 V |
| <ul style="list-style-type: none"> • Type of voltage / 1 / of the supply voltage | DC |
| <ul style="list-style-type: none"> • Consumed current / 1 / at rated supply voltage / maximum | 0.4 A |
| Supply voltage / 2 / Rated value | 24 V |
| <ul style="list-style-type: none"> • Supply voltage / 2 / rated value | 9.6 ... 31.2 V |
| <ul style="list-style-type: none"> • Type of voltage / 2 / of the supply voltage | DC |
| <ul style="list-style-type: none"> • Consumed current / 2 / at rated supply voltage / maximum | 0.2 A |
| <ul style="list-style-type: none"> • Power loss [W] / 2 / Rated value | 4.8 W |
| Product component / fusing at power supply input | Yes |
| Fuse protection type / at input for supply voltage | 2.5 A / 125 V |
| Power loss [W] | |
| <ul style="list-style-type: none"> • at DC / at 24 V | 4.8 W |

Permitted ambient conditions

| | |
|--|----------------|
| Ambient temperature | |
| <ul style="list-style-type: none"> • during operation | -40 ... +70 °C |
| <ul style="list-style-type: none"> • during storage | -40 ... +85 °C |
| <ul style="list-style-type: none"> • during transport | -40 ... +85 °C |
| Relative humidity | |
| <ul style="list-style-type: none"> • at 25 °C / without condensation / during operation / maximum | 95 % |
| Protection class IP | IP20 |

Design, dimensions and weight

| | |
|-----------------------------|-------------------------|
| Design | compact |
| Width | 60 mm |
| Height | 147 mm |
| Depth | 125 mm |
| Net weight | 0.85 kg |
| Material / of the enclosure | Polycarbonate (PC-GF10) |
| Mounting type | |

| | |
|---------------------------|-----|
| • 35 mm DIN rail mounting | Yes |
| • wall mounting | Yes |
| • S7-300 rail mounting | Yes |
| • S7-1500 rail mounting | Yes |

Product properties, functions, components / general

| | |
|---|------|
| Number of automatically learnable MAC addresses | 2048 |
|---|------|

Product functions / management, configuration

| | |
|-----------------------------------|-----|
| Product function | |
| • multiport mirroring | No |
| • CoS | Yes |
| Product function / switch-managed | No |

Product functions / Redundancy

| | |
|---|-----|
| Product function | |
| • Parallel Redundancy Protocol (PRP)/operation in the PRP-network | Yes |
| • Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA) | No |

Standards, specifications, approvals

| | |
|--|--|
| Standard | |
| • for hazardous zone | EN 60079-0:2012 + A11:2013, EN60079-15:2010, II 3 G Ex nA IIC T4 Gc, KEMA 07ATEX0145 X, IEC 6079-0:2011, IEC 6079-0-15:2010 |
| • for safety / from CSA and UL | UL 60950-1, CSA C22.2 No. 60950-1 |
| • for hazardous zone / from CSA and UL | UL 1604 and UL 2279-15 (Hazardous Location), Class 1 / Division 2 / Group A, B, C, D / T.., Class 1 / Zone 2 / Group IIC / T.. |
| • for emitted interference | EN 61000-6-4 (Class A) |

Standards, specifications, approvals / CE

| | |
|---|-----|
| Certificate of suitability / CE marking | Yes |
|---|-----|

Standards, specifications, approvals / miscellaneous

| | |
|---|----------------------------|
| Laser protection class | LED Class 1 |
| Certificate of suitability | EN 61000-6-2, EN 61000-6-4 |
| • C-Tick | Yes |
| • E1 approval | No |
| • EC declaration of conformity EN 61010, IEC 61010-1, UL 61010A-1 | Yes |
| • KC approval | Yes |

Standards, specifications, approvals / ship classification

| | |
|---|-----|
| Marine classification association | |
| • American Bureau of Shipping Europe Ltd. (ABS) | Yes |

- Bureau Veritas (BV)
- DNV GL
- Lloyds Register of Shipping (LRS)
- Polski Rejestr Statkow (PRS)
- Royal Institution of Naval Architects (RINA)

Yes
Yes
Yes
Yes
Yes

Further Information / Internet Links

Internet-Link

- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/snst>
<http://www.siemens.com/simatic-net>
<https://mall.industry.siemens.com>
<http://www.siemens.com/industry/infocenter>
<http://automation.siemens.com/bilddb>
<http://www.siemens.com/cax>
<https://support.industry.siemens.com>

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

10/30/2018