## SIEMENS

## Data sheet

## 6GK5106-2BD00-2AC2



SCALANCE XC106-2, Unmanaged IE switch, 6x 10/100 Mbit/s RJ45 ports, 2x 100 Mbit/s Multimode SC, LED diagnostics, error-signaling contact with set button, redundant Power supply Manual available as a download

product type designation	SCALANCE XC106-2
transfer rate	
transfer rate	10 Mbit/s, 100 Mbit/s
interfaces / for communication / integrated	
number of electrical connections	
<ul> <li>for network components or terminal equipment</li> </ul>	6; RJ45
number of 100 Mbit/s SC ports	
<ul> <li>for multimode</li> </ul>	2
interfaces / other	
number of electrical connections	
<ul> <li>for signaling contact</li> </ul>	1
for power supply	1
type of electrical connection	
<ul> <li>for signaling contact</li> </ul>	2-pole terminal block
<ul> <li>for power supply</li> </ul>	4-pole terminal block
signal inputs/outputs	
operating voltage / of the signaling contacts	
at DC / rated value	24 V
operational current / of the signaling contacts	
• at DC / maximum	0.1 A
supply voltage, current consumption, power loss	
product component / connection for redundant voltage supply	Yes
type of voltage / 1 / of the supply voltage	DC
<ul> <li>supply voltage / 1 / rated value</li> </ul>	24 V
<ul> <li>power loss [W] / 1 / rated value</li> </ul>	4.8 W
<ul> <li>consumed current / 1 / at rated supply voltage / maximum</li> </ul>	0.4 A
<ul> <li>supply voltage / 1 / rated value</li> </ul>	9.6 31.2 V
<ul> <li>type of electrical connection / 1 / for power supply</li> </ul>	4-pole terminal block
<ul> <li>product component / 1 / fusing at power supply input</li> </ul>	Yes
ambient conditions	
ambient temperature	
<ul> <li>during operation</li> </ul>	-40 +70 °C
<ul> <li>during storage</li> </ul>	-40 +85 °C
during transport	-40 +85 °C
relative humidity	
<ul> <li>at 25 °C / without condensation / during operation /</li> </ul>	95 %



maximum	
protection class IP	IP20
design, dimensions and weights	
design	compact
width	60 mm
height	147 mm
depth	125 mm
net weight	0.85 kg
material / of the enclosure	Polycarbonate (PC-GF10)
fastening method	
<ul> <li>35 mm top hat DIN rail mounting</li> </ul>	Yes
wall mounting	Yes
• S7-300 rail mounting	Yes
S7-1500 rail mounting	Yes
product features, product functions, product components	/ general
number of automatically learnable MAC addresses	2048
product functions / management, configuration, engineeri	
product function	No
multiport mirroring	No
• CoS	Yes
product function / switch-managed	No
product functions / redundancy	
product function	
<ul> <li>Parallel Redundancy Protocol (PRP)/operation in the PRP-network</li> </ul>	Yes
<ul> <li>Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)</li> </ul>	No
standards, specifications, approvals	
standard	
<ul> <li>for hazardous zone</li> </ul>	EN 60079-0:2012 + A11:2013, EN60079-15:2010, II 3 G Ex nA IIC T4 Gc, KEMA 07ATEX0145 X, IEC 6079-0:2011, IEC 6079-0-15:2010
<ul> <li>for safety / from CSA and UL</li> </ul>	UL 60950-1, CSA C22.2 No. 60950-1
<ul> <li>for bazardous zone / from CSA and UL</li> </ul>	UL 1604 and UL 2279-15 (Hazardous Location), Class 1 / Division 2 /
for emitted interference	Group A, B, C, D / T, Class 1 / Zone 2 / Group IIC / T EN 61000-6-4 (Class A)
standards, specifications, approvals / CE	
certificate of suitability / CE marking	Yes
standards, specifications, approvals / other	
laser protection class	LED Class 1
certificate of suitability	EN 61000-6-2, EN 61000-6-4
• C-Tick	Yes
• E1 approval	No
<ul> <li>EC Declaration of Conformity EN 61010, IEC 61010-1, UL 61010A-1</li> </ul>	Yes
KC approval	Yes
standards, specifications, approvals / marine classification	
Marine classification association	
American Bureau of Shipping Europe Ltd. (ABS)	Yes
<ul> <li>French marine classification society (BV)</li> </ul>	Yes
DNV GL	Yes
Korean Register of Shipping (KRS)	Yes
Lloyds Register of Shipping (IRS)	Yes
Polski Rejestr Statkow (PRS)	Yes
Royal Institution of Naval Architects (RINA)	Yes
further information / internet-Links	
Internet-Link	
<ul> <li>to web page: selection aid TIA Selection Tool</li> </ul>	http://www.siemens.com/snst
<ul> <li>to website: Industrial communication</li> </ul>	http://www.siemens.com/simatic-net



• to website: Industry Mall	https://mall.industry.siemens.com
<ul> <li>to website: Information and Download Center</li> </ul>	http://www.siemens.com/industry/infocenter
<ul> <li>to website: Image database</li> </ul>	http://automation.siemens.com/bilddb
<ul> <li>to website: CAx-Download-Manager</li> </ul>	http://www.siemens.com/cax
<ul> <li>to website: Industry Online Support</li> </ul>	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)

12/18/2020 🖸

