Data sheet



SCALANCE XB108-2 unmanaged IE switch, 8x 10/100 Mbit/s Ports, 2x 100 Mbit/s multimode SC, for setting up small star and line topologies; LED diagnostics,IP20, redundant power supply, 24 V AC/DC Manual available as a download

SCALANCE XB108-2	
10 Mbit/s, 100 Mbit/s	
8; RJ45	
2	
1	
1	
Supply voltage, current consumption, power loss	
AC/DC	
24 V	
19.2 V	

• external / maximum	28.8 V
• at AC	24 V
Product component / fusing at power supply input	Yes
Fuse protection type / at input for supply voltage	0.6 A / 60 V
Consumed current / maximum	0.3 A
Power loss [W]	
• at DC / at 24 V	7.2 W

Permitted ambient conditions	
Ambient temperature	
during operation	0 60 °C
during storage	-40 +80 °C
during transport	-40 +80 °C
Relative humidity	
 at 25 °C / without condensation / during operation / maximum 	95 %
Protection class IP	IP20

Design, dimensions and weight	
Design	compact
Width	80 mm
Height	117 mm
Depth	109 mm
Net weight	0.34 kg
Mounting type	
• 35 mm DIN rail mounting	Yes
wall mounting	No
S7-300 rail mounting	No
• S7-1500 rail mounting	No

Product functions / management, configuration		
Product function		
 multiport mirroring 	No	
• CoS	Yes	
PROFINET conformity class	A	
Product function / switch-managed	No	

Product functions / Redundancy	
Product function	
 Parallel Redundancy Protocol (PRP)/operation in the PRP-network 	Yes
 Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA) 	No

Standards, specifications, approvals	
Standard	



• for FM FM3611: Class 1, Divison 2, Group A, B, C, D / T4, CL.1, Zone 2,

GP. IIC, T4

• for hazardous zone EN 60079-0:2009, EN60079-15:2010, II 3 G Ex nA IIC T4 Gc,

KEMA 07ATEX0145 X

• for safety / from CSA and UL UL 60950-1, CSA C22.2 No. 60950-1

• for emitted interference EN 61000-6-4 (Class B)

• for interference immunity 61000-6-2

Standards, specifications, approvals / CE

Certificate of suitability / CE marking Yes

Standards, specifications, approvals / hazardous environments

Certificate of suitability

● IECEx Yes; IEC 60079-0, IEC 60079-15, IECEx DEK 14.0025X, Ex nA

IIC T4 Gc

Standards, specifications, approvals / miscellaneous

Certificate of suitability EN 61000-6-2, EN 61000-6-4

Regulatory Compliance Mark (RCM)

Yes

• KC approval Yes

Standards, specifications, approvals / product conformity

MTBF 71 y

Further Information / Internet Links

Internet-Link

• to website: Selector SIMATIC NET http://www.siemens.com/snst

SELECTION TOOL

• to website: Industrial communication http://www.siemens.com/simatic-net

to website: Industry Mall

• to website: Information and Download Center http://www.siemens.com/industry/infocenter

• to website: Image database

to website: CAx Download Manager

• to website: Industry Online Support https://support.industry.siemens.com

Security information

https://mall.industry.siemens.com

http://www.siemens.com/cax

http://automation.siemens.com/bilddb

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Thirdparty products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)

last modified:

10/30/2018