

SCALANCE XRM334; managed layer 2; IE switch, 19" rack; 24x 100/1000 Mbps RJ45 port; 2x 1G/2.5G/5G/10 Gbps RJ45 8x 1G/10G SFP+ port; LED diagnostics; error signaling contact; select/set button; PROFINET IO device; network management; integrated redundancy manager; office features (RSTP, VLAN, IGMP,...); CLP included in scope of supply; power supply 230 V AC;



product type designation	
product brand name	SCALANCE
transfer rate	
transfer rate	10 Mbit/s, 100 Mbit/s, 1000 Mbit/s, 2.5 Gbit/s, 5 Gbit/s, 10 Gbit/s
interfaces / for communication / integrated	
number of electrical connections	
• for network components or terminal equipment	26; RJ45
number of 10/100/1000 Mbit/s RJ45 ports	
• with securing collar	26
number of 1000/2500/5000/10000 Mbps RJ45 ports / with securing collar	2
number of electrical connections	
• for SFP+	8; 1000 Mbps and 10000 Mbps SFP usable
interfaces / other	
number of electrical connections	
• for operator console	1
• for signaling contact	1
• for power supply	1
type of electrical connection	
• for operator console	USB (2.0 Port, Type B, serial via USB)
• for signaling contact	2-pole terminal block
• for power supply	IEC plug C14 AC supply or 2-pole terminal block for DC supply
design of the removable storage	
• CLP	Yes
operating voltage / of the signaling contacts	
• at AC / rated value	24 V
• at DC / rated value	24 V
operational current / of the signaling contacts	
• at DC / maximum	0.1 A
supply voltage, current consumption, power loss	
product component / connection for redundant voltage supply	No
type of voltage supply / redundant power supply unit	No
type of voltage / 1 / of the supply voltage	DC
• supply voltage / 1 / rated value	100V ... 250V DC
• power loss [W] / 1 / rated value	99 W
• supply voltage / 1 / rated value	77 ... 300 V
• consumed current / 1 / maximum	0.8 A
• type of electrical connection / 1 / for power supply	2-pole terminal block
• product component / 1 / fusing at power supply input	Yes
• fuse protection type / 1 / at input for supply voltage	F 4A / 250 V

<b>type of voltage / 2 / of the supply voltage</b>	AC (50 / 60Hz)
• supply voltage / 2 / rated value	240 V; 100V ... 240V AC
• power loss [W] / 2 / rated value	99 W
• supply voltage / 2 / rated value	85 ... 264 V
• consumed current / 2 / maximum	0.8 A
• type of electrical connection / 2 / for power supply	C14, IEC plug
• fuse protection type / 2 / at input for supply voltage	F 4A / 250 V
<b>ambient conditions</b>	
ambient temperature / in horizontal mounting position / during operation	-25 ... +60 °C; Starting at -25 °C; The maximum ambient temperature during operation depends on the operating height and the plug-in transceivers, see also manual.
installation altitude / at height above sea level / maximum	3000 m
relative humidity	
• at 25 °C / without condensation / during operation / maximum	95 %
operating condition / fanless operation	Yes
protection class IP	IP20
<b>design, dimensions and weights</b>	
design	19" rack
number of modular height units / relating to 19-inch cabinet	1
width	446 mm
height	43.6 mm
depth	374.8 mm
net weight	8.2 kg
material / of the enclosure	metal
fastening method	
• 19-inch installation	Yes
<b>product features, product functions, product components / general</b>	
cascading in cases of star topology	any (depending only on signal propagation time)
number of automatically learnable MAC addresses	16382
number of QoS queues / per port	8
product function	
• QoS according to IEEE 802.1Q	Yes
product feature	
• Store & Forward switching method	Yes
<b>product functions / management, configuration, engineering</b>	
product function	
• CLI	Yes
• web-based management	Yes
• MIB support	Yes
• TRAPs via email	Yes
• configuration with STEP 7	Yes
• RMON	No
• SMTP server	No
• port mirroring	Yes
• multiport mirroring	Yes
• Encapsulated Remote Traffic Mirroring (ERTM)	Yes
• CoS	Yes
• PROFINET IO diagnosis	Yes
• switch-managed	Yes
PROFINET conformity class	B
network load class / according to PROFINET	2
telegram length / for Ethernet / maximum	9194 byte
protocol / is supported	
• Telnet	No
• HTTP	Yes
• HTTPS	Yes
• TFTP	Yes
• FTP	Yes
• SFTP	Yes
• BOOTP	Yes

• NETCONF	Yes
• GMRP	Yes
• DCP	Yes
• LLDP	Yes
• EtherNet/IP	Yes
• SNMP v1	Yes
• SNMP v2	Yes
• SNMP v3	Yes
• IGMP (snooping/querier)	Yes
identification & maintenance function	
• I&M0 - device-specific information	Yes
• I&M1 - higher level designation/location designation	Yes
<b>product functions / diagnostics</b>	
product function	
• port diagnostics	Yes
• statistics Packet Size	Yes
• statistics packet type	Yes
• error statistics	Yes
• SysLog	Yes
<b>product functions / VLAN</b>	
product function	
• VLAN - port based	Yes
• VLAN - protocol-based	No
• VLAN - IP-based	No
• VLAN dynamic	Yes
number of VLANs / maximum	512
number of VLANs - dynamic / maximum	512
<b>product functions / DHCP</b>	
product function	
• DHCP server	No
• DHCP client	Yes
• DHCP Option 82	No
• DHCP Option 66	Yes
• DHCP Option 67	Yes
<b>product functions / redundancy</b>	
protocol / is supported / Media Redundancy Protocol (MRP)	Yes
product function	
• media redundancy protocol (MRP) with redundancy manager	Yes
• Media Redundancy Protocol Interconnection (MRP-I)	No
• ring redundancy	Yes
• high speed redundancy protocol (HRP) with redundancy manager	No
• high speed redundancy protocol (HRP) with standby redundancy	No
• redundancy procedure STP	Yes
• redundancy procedure RSTP	Yes
• redundancy procedure RSTP+	Yes
• redundancy procedure MSTP	Yes
• passive listening	No
• eRSTP	Yes
protocol / is supported	
• LACP	No
<b>system modification during operation</b>	
product function / configuration in RUN via CiR/H-CiR	No
<b>product functions / security</b>	
product conformity / according to IEEE 802.1x-port based Network Access Control	No
protocol / is supported	
• RADIUS	Yes
• SSH	Yes
• SSL	Yes

<b>product functions / time</b>	
product function	
• SICLOCK support	Yes
• NTP-client	Yes
• IEEE 1588 v2 transparent forwarding	Yes
protocol / is supported	
• NTP	Yes
• SNTP	Yes
• IEEE 1588 profile default	Yes
accuracy / at IEEE 1588 v2	
• not less than	100 µs
• typical	50 ns
<b>standards, specifications, approvals</b>	
certificate of suitability	
• CE marking	Yes
• UKCA marking	Yes
• cULus approval	Yes
• KC approval	Yes
• Regulatory Compliance Mark (RCM)	Yes
product conformity / according to EMC-guideline	2014/30/EU
standard	
• for EMC interference emission	EN 61000-6-4
• for immunity to EMC	EN 61000-6-2
<b>standards, specifications, approvals / other</b>	
certificate of suitability	
• railway application in accordance with EN 50121-4	Yes; use only in areas not accessible to the public
• railway application in accordance with EN 50125-3	Yes
IT security for industrial automation systems / according to IEC 62443-4-2:2019	Yes
<b>standards, specifications, approvals / Environmental Product Declaration</b>	
Environmental Product Declaration	Yes
Global Warming Potential [CO2 eq]	
• total	1274.81 kg
• during manufacturing	225.96 kg
• during operation	1048 kg
• after end of life	0.85 kg
<b>product functions / general</b>	
MTBF	8.6 a
reference temperature / for MTBF determination	40 °C
reference code	
• according to IEC 81346-2	KF
• according to IEC 81346-2:2019	KFE
Warranty period	5 a
<b>further information / internet links</b>	
internet link	
• to website: Selection guide for cables and connectors	<a href="https://support.industry.siemens.com/cs/ww/en/view/109766358">https://support.industry.siemens.com/cs/ww/en/view/109766358</a>
• to web page: selection aid TIA Selection Tool	<a href="https://www.siemens.com/tstcloud">https://www.siemens.com/tstcloud</a>
• to website: Industrial communication	<a href="https://www.siemens.com/simatic-net">https://www.siemens.com/simatic-net</a>
• to web page: SiePortal	<a href="https://sieportal.siemens.com/">https://sieportal.siemens.com/</a>
• to website: Image database	<a href="https://www.automation.siemens.com/bilddb">https://www.automation.siemens.com/bilddb</a>
• to website: CAx-Download-Manager	<a href="https://www.siemens.com/cax">https://www.siemens.com/cax</a>
• to website: Industry Online Support	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>
<b>security information</b>	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial

cybersecurity measures that may be implemented, please visit [www.siemens.com/cybersecurity-industry](https://www.siemens.com/cybersecurity-industry). Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <https://www.siemens.com/cert>. (V4.7)

Approvals / Certificates

General Product Approval	Radio Equipment Type Approval Certificate
--------------------------	--



[KC](#)

Test Certificates	Environment	Industrial Communication
-------------------	-------------	--------------------------

[Type Test Certificates/Test Report](#)



[PROFINET](#)

last modified:

9/18/2024