SIEMENS

Data sheet

6GK5761-1FC00-0AB0

product type designation



W761-1 RJ45 (USA)


IWLAN Access Point, SCALANCE W761-1 RJ45, 1 radio, 1 R-SMA antenna port, IEEE 802.11a/b/g/h/n, 2.4/5 GHz, gross data rate 150 Mbps, 1x RJ45 max. 100 Mbps, 24 V DC, joint block, IP20, 0... +55 °C, WPA2/802.11i/e, observe national approvals! CERT ID: ELN-W1-RJ-E1, FCC ID: LYHELN1V1 scope of delivery: manuals on CD-ROM German/English, 1x joint block; only for operation in the USA.

transfer rate	
transfer rate	
 with WLAN / maximum 	150 Mbit/s
 for Industrial Ethernet 	10, 100 Mbit/s
interfaces	
number of electrical connections	
 for network components or terminal equipment 	1
 for power supply 	1
for redundant voltage supply	0
type of electrical connection	
 for network components or terminal equipment 	RJ45 socket
for power supply	3-pole screw terminal
memory	
design of the removable storage	
• C-PLUG	No
• KEY-PLUG	No
interfaces / wireless	
number of radio cards / permanently installed	1
number of electrical connections / for external antenna(s)	1
type of electrical connection / for external antenna(s)	R-SMA (socket)
product feature / external antenna can be mounted directly on device	Yes
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
consumed current	
at DC / at 24 V / typical	0.15 A
power loss [W]	
at DC / at 24 V / typical	3.6 W
supply voltage / 1	
from terminal block	19.2 V
supply voltage / 2	
 from terminal block 	28.8 V
ambient conditions	
ambient temperature	
 during operation 	0 55 °C
during storage	-40 +85 °C
during transport	-40 +85 °C
relative humidity / at 25 °C / without condensation / during operation / maximum	95 %

ambient condition / for operation	When used under hazardous conditions (Zone 2), the SCALANCE W761-1 RJ45 or W72x-1 RJ45 product must be installed in an enclosure. To comply with EN 50021, this enclosure must meet the requirements of at least IP 54 in compliance with EN 60529.
protection class IP	IP20
design, dimensions and weights	
width	50 mm
height	114 mm
depth	74 mm
width / of the enclosure / without antenna	50 mm
height / of the enclosure / without antenna	114 mm
depth / of the enclosure / without antenna	74 mm
net weight	0.13 kg
fastening method	o. To lig
S7-300 rail mounting	No
S7-1500 rail mounting	No
35 mm DIN-rail mounting	Yes
wall mounting	No
radio frequencies	NO
operating frequency	2.44 2.49 CHz depending on the country apprecial
• for WLAN in 2.4 GHz frequency band	2.41 2.48 GHz; depending on the country approvals
• for WLAN in 5 GHz frequency band	4.9 5.8 GHz; depending on the country approvals
product features, product functions, product components / gen	
product function / Access Point Mode	Yes
product function / client Mode	Yes
number of SSIDs	1
product function	
• iPCF Access Point	No
• iPCF client	No
• iPCF-MC Access Point	No
• iPCF-MC client	No
product function / iREF	No No
product function / iPRP	No No
product functions / management, configuration, engineering	
number of manageable IP addresses / in client	4
product function	
• CLI	Yes
 web-based management 	Yes
 MIB support 	Yes
TRAPs via email	Yes
 configuration with STEP 7 	Yes
 configuration with STEP 7 in the TIA Portal 	Yes
operation with IWLAN controller	No
operation with Enterasys WLAN controller	No
forced roaming on IP down with IWLAN	Yes
forced roaming on link down with IWLAN	Yes
• WDS	Yes
protocol / is supported	
Address Resolution Protocol (ARP)	Yes
• ICMP	Yes
Telnet	Yes
• HTTP	Yes
• HTTPS	Yes
• TFTP	
	Yes
• DCP	Yes
• LLDP	Yes
identification & maintenance function	
I&M0 - device-specific information	Yes
 I&M1 - higher level designation/location designation 	Yes
product function / is supported / identification link product functions / diagnostics	Yes; acc. to IEC 61406-1:2022



product function	
PROFINET IO diagnosis	No
• link check	No
 connection monitoring IP-Alive 	No
localization via Aeroscout	No
SysLog	Yes
protocol / is supported	
• SNMP v1	Yes
• SNMP v2	Yes
• SNMP v3	Yes
product functions / VLAN	
product function	
 function VLAN with IWLAN 	Yes
product functions / DHCP	
product function	
DHCP client	Yes
DHCP server	Yes
DHCP Option 82	Yes
product functions / redundancy	
protocol / is supported	
STP/RSTP	Yes
• STP/RSTP • MSTP	Yes
• NSTP	Yes
product functions / security	165
product function	V
ACL - MAC-based	Yes
management security, ACL-IP based	Yes
• IEEE 802.1x (radius)	Yes
NAT/NAPT	Yes
 access protection according to IEEE802.11i 	Yes
WPA/WPA2	Yes
TKIP/AES	Yes
protocol / is supported	
• SSH	Yes
RADIUS	Yes
product functions / time	
protocol / is supported	
• NTP	Yes
• SNTP	Yes
 SIMATIC time synchronization (SIMATIC Time) 	Yes
standards, specifications, approvals	
standard	
• for FM	FM 3611: Class I, Division 2, Groups A,B,C,D, T4 / Class 1, Zone 2, Group IIC,
	T4, FM16US0205X
for safety / from CSA and UL	UL 60950-1 E115352, CSA C22.2 No. 60950-1
certificate of suitability	
 EC Declaration of Conformity 	Yes
CE marking	Yes
• C-Tick	Yes
• E1 approval	No
• railway application in accordance with EN 50155	No
,	140
 railway application in accordance with EN 50121-4 	No
railway application in accordance with EN 50121-4NEMA TS2	
* **	No
NEMA TS2IEC 61375	No No No
NEMA TS2IEC 61375IEC 61850-3	No No No
 NEMA TS2 IEC 61375 IEC 61850-3 NEMA4X 	No No No No
NEMA TS2IEC 61375IEC 61850-3	No No No
 NEMA TS2 IEC 61375 IEC 61850-3 NEMA4X Power-over-Ethernet according IEEE802.3at for type 1 	No No No No
 NEMA TS2 IEC 61375 IEC 61850-3 NEMA4X Power-over-Ethernet according IEEE802.3at for type 1 and IEEE802.3af 	No No No No No No



• IEEE 802.11b Yes • IEEE 802.11e Yes • IEEE 802.11g Yes • IEEE 802.11h Yes • IEEE 802.11i Yes • IEEE 802.11n wireless approval You will find the current list of countries at: www.siemens.de/funkzulassungen reference code • according to IEC 81346-2:2019 KFE standards, specifications, approvals / marine classification Marine classification association American Bureau of Shipping Europe Ltd. (ABS) No • French marine classification society (BV) No DNV GI Nο • Korean Register of Shipping (KRS) No • Lloyds Register of Shipping (LRS) No • Nippon Kaiji Kyokai (NK) No • Polski Rejestr Statkow (PRS) No • Royal Institution of Naval Architects (RINA) No standards, specifications, approvals / hazardous environments standard / for hazardous zone EN 60079-15:2005, EN 60079-0:2006, II 3 G Ex nA II T4 KEMA 07 ATEX ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, Cl. 1, div. 2, GP. A, • from CSA and UL B, C, D, T4 / Cl. 1, Zone 2, GP IIC E240480 certificate of suitability / CCC / for hazardous zone according to Yes; GB3836.1, GB3836.8 GB standard Ex nA IIC T4 Gc · as marking standards, specifications, approvals / Environmental Product Declaration global warming potential [CO2 eq] total 125.8 kg during manufacturing 12.97 kg during operation 112.66 ka • after end of life 0.17 kg accessories 24 V DC screw terminal included in scope of delivery further information / internet links • to website: Selection guide for cables and connectors https://support.industry.siemens.com/cs/ww/en/view/109766358 • to web page: selection aid TIA Selection Tool https://www.siemens.com/tstcloud • to web page: WLAN country approval https://www.siemens.com/wireless-approvals to the website: IWLAN https://www.siemens.com/iwlan • to website: Industrial communication https://www.siemens.com/simatic-net • to web page: SiePortal https://sieportal.siemens.com/ • to website: Image database https://www.automation.siemens.com/bilddb • to website: CAx-Download-Manager https://www.siemens.com/cax • to website: Industry Online Support https://support.industry.siemens.com security information security information Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible

that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates,

subscribe to the Siemens Industrial Cybersecurity RSS Feed under

https://www.siemens.com/cert. (V4.7)



General Product Approval





Declaration of Conformity



Manufacturer Declara-<u>tion</u>

China RoHS

General Product Approval

For use in hazardous locations

Radio Equipment Type Approval Certi-ficate

Environment







CCC-Ex

Miscellaneous



last modified:

4/9/2025



6/13/2025