

### product type designation



### W1788-1 M12

IWLAN access point, SCALANCE W1788-1 M12, 1 radio, 4 N-CON antenna port, iFeatures support via CLP, IEEE 802.11a/b/g/h/n/ac, 2.4/5GHz, gross 1733 Mbit/s per radio, 2x M12 max. 1 Gbit/s, PoE, redundant 24 V DC, M12 A-coded IP65, -20..+70°C, CLP slot, WPA2/802.11i/e, observe national approvals! CERT ID: RAPAC-W1-M12-E4, includes: MPCIE-R1-ABGNAC-U4, scope of delivery: M12 sealing caps, for operation outside of USA/Israel

### transfer rate

transfer rate	
<ul style="list-style-type: none"> <li>with WLAN / maximum</li> </ul>	1733 Mbit/s
<ul style="list-style-type: none"> <li>for Industrial Ethernet</li> </ul>	10, 100, 1000 Mbit/s
transfer rate / for Industrial Ethernet	
<ul style="list-style-type: none"> <li>minimum</li> </ul>	10 Mbit/s
<ul style="list-style-type: none"> <li>maximum</li> </ul>	1000 Mbit/s

### interfaces

number of electrical/optical connections / for network components or terminal equipment / maximum / note	2
number of electrical/optical connections / for gigabit Ethernet / maximum	2
number of electrical connections	
<ul style="list-style-type: none"> <li>for network components or terminal equipment</li> </ul>	2
<ul style="list-style-type: none"> <li>for power supply</li> </ul>	1
<ul style="list-style-type: none"> <li>for redundant voltage supply</li> </ul>	1
type of electrical connection	
<ul style="list-style-type: none"> <li>for network components or terminal equipment</li> </ul>	M12 interface (8-pole, X-coded), PoE
<ul style="list-style-type: none"> <li>for power supply</li> </ul>	M12 interface (4-pole, A-coded)

### memory

design of the removable storage	
<ul style="list-style-type: none"> <li>CLP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>CLP iFeatures</li> </ul>	Yes

### interfaces / wireless

number of radio cards / permanently installed	1
transmission mode / for multiple input multiple output (MIMO)	4x4
number of spatial streams	4
number of electrical connections / for external antenna(s)	4
type of electrical connection / for external antenna(s)	N-Connect (socket)
product feature / external antenna can be mounted directly on device	Yes

### supply voltage, current consumption, power loss

type of voltage / of the supply voltage	DC
supply voltage	
<ul style="list-style-type: none"> <li>from Power-over-Ethernet according to IEEE802.3at for type 2</li> </ul>	48 V
consumed current	
<ul style="list-style-type: none"> <li>at DC / at 24 V / typical</li> </ul>	0.375 A
<ul style="list-style-type: none"> <li>with Power-over-Ethernet according to IEEE802.3at for type 2 / typical</li> </ul>	0.21 A

power loss [W]	
<ul style="list-style-type: none"> <li>at DC / at 24 V / typical</li> <li>with Power-over-Ethernet according to IEEE802.3at for type 2 / typical</li> </ul>	10.1 W 9 W
<b>supply voltage / 1</b>	
<ul style="list-style-type: none"> <li>from M12 Power Connector (A-coded) for redundant power supply</li> </ul>	16.8 V
<b>supply voltage / 2</b>	
<ul style="list-style-type: none"> <li>from M12 Power Connector (A-coded) for redundant power supply</li> </ul>	31.2 V
<b>ambient conditions</b>	
ambient temperature	
<ul style="list-style-type: none"> <li>during operation</li> <li>during storage</li> <li>during transport</li> </ul>	-20 ... +70 °C -40 ... +85 °C -40 ... +85 °C
relative humidity / at 25 °C / without condensation / during operation / maximum	90 %
protection class IP	IP65
<b>design, dimensions and weights</b>	
width	258 mm
height	258 mm
depth	80 mm
width / of the enclosure / without antenna	258 mm
height / of the enclosure / without antenna	258 mm
depth / of the enclosure / without antenna	80 mm
net weight	2.7 kg
fastening method	Accessories are required for wall mounting and mounting on a mounting rail.
<ul style="list-style-type: none"> <li>S7-300 rail mounting</li> <li>S7-1500 rail mounting</li> <li>35 mm top hat DIN rail mounting</li> <li>wall mounting</li> </ul>	Yes Yes Yes Yes
<b>radio frequencies</b>	
operating frequency	
<ul style="list-style-type: none"> <li>for WLAN in 2.4 GHz frequency band</li> <li>for WLAN in 5 GHz frequency band</li> </ul>	2.41 ... 2.48 GHz; depending on the country approvals 4.9 ... 5.8 GHz; depending on the country approvals
<b>product features, product functions, product components / general</b>	
product function / Access Point Mode	Yes
product function / client Mode	Yes
number of SSIDs	8
product function	
<ul style="list-style-type: none"> <li>iPCF Access Point</li> <li>iPCF client</li> <li>iPCF-MC Access Point</li> <li>iPCF-MC client</li> </ul>	No No No No
product function / iREF	No
product function / iPRP	Yes
<b>product functions / management, configuration, engineering</b>	
product function	
<ul style="list-style-type: none"> <li>CLI</li> <li>web-based management</li> <li>MIB support</li> <li>TRAPs via email</li> <li>configuration with STEP 7</li> <li>configuration with STEP 7 in the TIA Portal</li> <li>operation with IWLAN controller</li> <li>forced roaming with IWLAN</li> <li>forced roaming on IP down with IWLAN</li> <li>forced roaming on link down with IWLAN</li> <li>WDS</li> </ul>	Yes Yes Yes Yes Yes Yes No Yes Yes No Yes
protocol / is supported	
<ul style="list-style-type: none"> <li>Address Resolution Protocol (ARP)</li> <li>ICMP</li> </ul>	Yes Yes

<ul style="list-style-type: none"> <li>• Telnet</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• HTTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• HTTPS</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• TFTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• DCP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• LLDP</li> </ul>	Yes
identification & maintenance function	
<ul style="list-style-type: none"> <li>• I&amp;M0 - device-specific information</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• I&amp;M1 - higher level designation/location designation</li> </ul>	Yes
<b>product functions / diagnostics</b>	
product function	
<ul style="list-style-type: none"> <li>• PROFINET IO diagnosis</li> </ul>	Yes
protocol / is supported	
<ul style="list-style-type: none"> <li>• SNMP v1</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• SNMP v2c</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• SNMP v3</li> </ul>	Yes
<b>product functions / VLAN</b>	
product function	
<ul style="list-style-type: none"> <li>• function VLAN with IWLAN</li> </ul>	Yes
<b>product functions / DHCP</b>	
product function	
<ul style="list-style-type: none"> <li>• DHCP client</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• DHCP server</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• DHCP Option 82</li> </ul>	Yes
<b>product functions / redundancy</b>	
protocol / is supported	
<ul style="list-style-type: none"> <li>• STP/RSTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• MSTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• RSTP</li> </ul>	Yes
<b>product functions / security</b>	
product function	
<ul style="list-style-type: none"> <li>• ACL - MAC-based</li> </ul>	No
<ul style="list-style-type: none"> <li>• management security, ACL-IP based</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• IEEE 802.1x (radius)</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• NAT/NAPT</li> </ul>	No
<ul style="list-style-type: none"> <li>• access protection according to IEEE802.11i</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• WPA/WPA2</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• TKIP/AES</li> </ul>	Yes
protocol / is supported	
<ul style="list-style-type: none"> <li>• SSH</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• RADIUS</li> </ul>	Yes
<b>product functions / time</b>	
protocol / is supported	
<ul style="list-style-type: none"> <li>• NTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• SNTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• SIMATIC time synchronization (SIMATIC Time)</li> </ul>	Yes
<b>standards, specifications, approvals</b>	
standard	
<ul style="list-style-type: none"> <li>• for FM</li> </ul>	FM 3611: Class I, Division 2, Groups A,B,C,D, T4 / Class 1, Zone 2, Group IIC, T4, FM16US0205X
certificate of suitability	
<ul style="list-style-type: none"> <li>• EC Declaration of Conformity</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• CE marking</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• C-Tick</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• E1 approval</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• IEC 61850-3</li> </ul>	No
<ul style="list-style-type: none"> <li>• Power-over-Ethernet according to IEEE802.3at for type 2</li> </ul>	Yes
standard for wireless communication	
<ul style="list-style-type: none"> <li>• IEEE 802.11a</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• IEEE 802.11b</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• IEEE 802.11e</li> </ul>	Yes

<ul style="list-style-type: none"> <li>• IEEE 802.11g</li> <li>• IEEE 802.11h</li> <li>• IEEE 802.11i</li> <li>• IEEE 802.11n</li> <li>• IEEE 802.11ac</li> </ul>	<p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p>
wireless approval	You will find the current list of countries at: <a href="http://www.siemens.de/funkzulassungen">www.siemens.de/funkzulassungen</a>
<b>standards, specifications, approvals / hazardous environments</b>	
standard / for hazardous zone <ul style="list-style-type: none"> <li>• from CSA and UL</li> </ul>	EN IEC 60079-0 : 2018, EN60079-7:2015 + A1 : 2018; II 3 G Ex ec IIC T4 Gc UL121201, CAN/CSA C22.2 No.213, Cl. 1, div. 2, GP. A, B, C, D, T4 / Cl. 1, Zone 2, GP IIC T4, E240480
certificate of suitability / CCC / for hazardous zone according to GB standard <ul style="list-style-type: none"> <li>• as marking</li> </ul>	<p>Yes; GB3836.1, GB3836.8</p> <p>Ex nA IIC T4 Gc</p>
<b>accessories</b>	
accessories	pre-assembled holder for attachment to a DIN rail
<b>further information / internet links</b>	
internet link <ul style="list-style-type: none"> <li>• to website: TIA Selection Tool</li> <li>• to web page: selection aid TIA Selection Tool</li> <li>• to the website: IWLAN</li> <li>• to website: Industry Mall</li> <li>• to website: Information and Download Center</li> <li>• to website: Image database</li> <li>• to website: CAx-Download-Manager</li> <li>• to website: Industry Online Support</li> </ul>	<p><a href="http://www.siemens.com/tia-selection-tool">http://www.siemens.com/tia-selection-tool</a></p> <p><a href="http://www.siemens.com/tia-selection-tool">http://www.siemens.com/tia-selection-tool</a></p> <p><a href="http://www.siemens.com/iwlan">http://www.siemens.com/iwlan</a></p> <p><a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a></p> <p><a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a></p> <p><a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a></p> <p><a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a></p> <p><a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a></p>
<b>security information</b>	
security information	<p>Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <a href="http://www.siemens.com/industrialsecurity">http://www.siemens.com/industrialsecurity</a>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <a href="http://support.automation.siemens.com">http://support.automation.siemens.com</a>. (V3.4)</p>

last modified:

11/9/2023 