



SCALANCE MUM856-1 (A1) 5G router, release 16, IP65, for wireless IP communication from Ethernet-based applications via public 3/4/5G mobile radio networks and private 5G networks, VPN, firewall, NAT, IPv6, connection to SINEMA RC via CLP, 4 N- Connect connections, 1x micro SIM slot, eSIM, 1x10/100/1000 Mbps M12 socket, redundant DC 24 V, M12 L-encoded, PoE, -30...+70 °C, CLP slot, 1x DI and 1x DO, A-encoded, observe national approvals: [siemens.com/mobile-approvals](https://www.siemens.com/mobile-approvals) CERT ID: MS5G16R-65-M1-M12-E4-1

transfer rate	
transfer rate / for Industrial Ethernet	10, 100, 1000 Mbit/s
transfer rate	
• with UMTS transmission / with downlink / maximum	42 Mbit/s
• with UMTS transmission / with uplink / maximum	5.76 Mbit/s
• for LTE transmission / with downlink / maximum	1000 Mbit/s
• for LTE transmission / with uplink / maximum	200 Mbit/s
• for 5G transmission / with downlink / maximum	1000 Mbit/s
• for 5G transmission / with uplink / maximum	500 Mbit/s
interfaces	
number of electrical/optical connections / for network components or terminal equipment / maximum	1
number of electrical/optical connections / for gigabit Ethernet / maximum	1
number of electrical connections	
• for network components or terminal equipment	1
number of electrical connections	
• for external antenna(s)	4
• for power supply	1
• for redundant voltage supply	1
type of electrical connection	
• for network components or terminal equipment	M12 (8-pin, X-coded), PoE
• for external antenna(s)	N-Connect (socket)
• for redundant voltage supply	M12 (4-pin, L-coded)
memory	
number of slots / for Micro-SIM card	1
product component / eSIM integrated	Yes
design of the removable storage / CLP	Yes
signal inputs/outputs	
number of digital inputs	1
number of digital outputs	1
type of electrical connection / at the digital inputs/outputs	M12 (4-pin, A-coded)
input voltage / at digital input / at DC	-30 ... +30 V
output voltage / at digital output / at DC / maximum	24 V; 0,5 A
operational current / of the signaling contacts / at DC / at 30 V / maximum	0.008 A
WAN connection	
type of wireless network / is supported	5G public networks, 5G private networks, LTE, UMTS
type of mobile wireless service / is supported	HSDPA, HSUPA, HSPA+
frequency band / is supported	
• 5G Standalone (SA)	n1, n2, n3, n5, n7, n8, n20, n25, n28, n30, n38, n40, n41, n48, n66, n71,

<ul style="list-style-type: none"> <li>• 5G Non-Standalone (NSA)</li> <li>• LTE</li> <li>• UMTS</li> </ul>	n75(DL), n77, n78, n79 n1, n2, n3, n5, n7, n8, n20, n25, n28, n30, n38, n40, n41, n66, n71, n77, n78, n79 B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B29(DL), B30, B32(DL), B34, B38, B39, B40, B41, B42, B43, B46(DL), B48, B66, B71 B1, B2, B4, B5, B6, B8, B19
<b>supply voltage, current consumption, power loss</b>	
supply voltage / from Power-over-Ethernet according to IEEE802.3at for type 1 and IEEE802.3af	48 V
consumed current	
<ul style="list-style-type: none"> <li>• at DC / at 24 V</li> </ul>	0.55 A
<ul style="list-style-type: none"> <li>• at DC / at 24 V / sleep mode / maximum</li> </ul>	0.013 A
<ul style="list-style-type: none"> <li>• with Power-over-Ethernet according to IEEE802.3at for type 1 and IEEE802.3af / typical</li> </ul>	0.27 A
power loss [W]	
<ul style="list-style-type: none"> <li>• at DC / at 24 V / typical</li> </ul>	13.2 W
<ul style="list-style-type: none"> <li>• with Power-over-Ethernet according to IEEE802.3at for type 1 and IEEE802.3af / typical</li> </ul>	12.96 W
<b>supply voltage / 1 / rated value</b>	24 V
<ul style="list-style-type: none"> <li>• type of voltage</li> </ul>	redundant 24 V DC power supply, M12, L-coded
<ul style="list-style-type: none"> <li>• type of voltage / 1 / of the supply voltage</li> </ul>	DC
<b>supply voltage / 2 / rated value</b>	24 V
<ul style="list-style-type: none"> <li>• type of voltage / 2 / of the supply voltage</li> </ul>	DC
<b>supply voltage / 3 / rated value</b>	48 V
<ul style="list-style-type: none"> <li>• type of voltage / 3 / of the supply voltage</li> </ul>	DC, PoE
<b>ambient conditions</b>	
ambient temperature	
<ul style="list-style-type: none"> <li>• during operation</li> </ul>	-30 ... +70 °C
<ul style="list-style-type: none"> <li>• during storage</li> </ul>	-40 ... +85 °C
relative humidity / at 25 °C / during operation / maximum	95 %
protection class IP	IP65
<b>design, dimensions and weights</b>	
depth	45 mm
height	179 mm
width	166 mm
net weight	1300 g
fastening method	Wall mounting, mounting on a DIN rail with a separate mounting adapter
<ul style="list-style-type: none"> <li>• 35 mm DIN-rail mounting</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• wall mounting</li> </ul>	Yes
<b>product features, product functions, product components / general</b>	
product function	
<ul style="list-style-type: none"> <li>• DynDNS client</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• no-ip.com client</li> </ul>	Yes
<b>product functions / management, configuration, engineering</b>	
product function	
<ul style="list-style-type: none"> <li>• CLI</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• web-based management</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• MIB support</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• TRAPs via email</li> </ul>	Yes
protocol / is supported	
<ul style="list-style-type: none"> <li>• Telnet</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• HTTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• HTTPS</li> </ul>	Yes
type of configuration	Web-based management
product function / is supported / identification link	Yes; acc. to IEC 61406-1:2022
<b>product functions / diagnostics</b>	
protocol / is supported	
<ul style="list-style-type: none"> <li>• SNMP v1</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• SNMP v2</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• SNMP v2c</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• SNMP v3</li> </ul>	Yes

product function	
• statistics Packet Size	No
• statistics packet type	No
• error statistics	No
• SysLog	Yes
• packet filter log	Yes
<b>product functions / DHCP</b>	
product function	
• DHCP client	Yes
• DHCP server - internal network	Yes
<b>product functions / routing</b>	
router function	
• NAT (IP masquerading)	Yes
• port forwarding	Yes
• NAT traversal	Yes
• 1:1 NAT	Yes
• DNS cache	Yes
<b>product functions / security</b>	
suitability for operation / Virtual Private Network	Yes
firewall version	Statefull Inspection
product function	
• password protection	Yes
• packet filter	Yes
• broadcast/multicast/unicast limiter	No
product function	
• broadcast blocking	No
• with VPN connection	IPsec, OpenVPN (as Client)
number of possible connections / with VPN connection	20
type of authentication / with Virtual Private Network / PSK	Yes
protocol / is supported	
• IPsec tunnel and transport mode	Yes
key length	
• 1 / with IPsec AES / with Virtual Private Network	128 bit
• 2 / with IPsec AES / with Virtual Private Network	192 bit
• 3 / with IPsec AES / with Virtual Private Network	256 bit
• with IPsec 3DES / with Virtual Private Network	168 bit
type of Internet key exchange / with Virtual Private Network	
• main mode	Yes
• quick mode	Yes
type of packet authentication / with Virtual Private Network	MD5, SHA-1, SHA-256, SHA-384, SHA-512
IETF profile / with Virtual Private Network / X.509v3 certificate	Yes
<b>product functions / time</b>	
protocol / is supported	
• NTP	Yes
• SNTP	Yes
<b>standards, specifications, approvals</b>	
standard	
• for EMC	ETSI EN 301 489-1, ETSI EN 301 489-19, ETSI EN 301 489-52, EN 55011, NAMUR NE21
• for emitted interference	CISPR 32, ETSI EN 55032 Class A / Class B, EN IEC 61000-6-3, EN IEC 61000-6-4
• for interference immunity	CISPR 35, EN 55035, EN IEC 61000-6-1, EN IEC 61000-6-2
certificate of suitability	
• EC Declaration of Conformity	Yes
• CE marking	Yes
• Power-over-Ethernet according IEEE802.3at for type 1 and IEEE802.3af	Yes
• railway application in accordance with EN 50121-3-2	Yes
• railway application in accordance with EN 50121-4	Yes
• railway application in accordance with EN 50155	Yes; no coated printed-circuit boards, EMC: trackside unit/vehicle unit, climate: use in the vehicle within equipment boxes/cabinets, mechanical system: class B: in equipment housing

<ul style="list-style-type: none"> <li>• fire protection in accordance with EN 45545-2</li> </ul>	Yes								
reference code									
<ul style="list-style-type: none"> <li>• according to IEC 81346-2:2019</li> </ul>	KED								
<b>standards, specifications, approvals / Environmental Product Declaration</b>									
Environmental Product Declaration	Yes								
global warming potential [CO2 eq]									
<ul style="list-style-type: none"> <li>• total</li> </ul>	394.89 kg								
<ul style="list-style-type: none"> <li>• during manufacturing</li> </ul>	33.7 kg								
<ul style="list-style-type: none"> <li>• during operation</li> </ul>	361 kg								
<ul style="list-style-type: none"> <li>• after end of life</li> </ul>	0.19 kg								
<b>further information / internet links</b>									
internet link									
<ul style="list-style-type: none"> <li>• to website: Selection guide for cables and connectors</li> <li>• to web page: selection aid TIA Selection Tool</li> <li>• to website: Mobile radio national approval</li> <li>• to website: Industrial communication</li> <li>• to web page: SiePortal</li> <li>• to website: Image database</li> <li>• to website: CAX-Download-Manager</li> <li>• to website: Industry Online Support</li> </ul>	<a href="https://support.industry.siemens.com/cs/ww/en/view/109766358">https://support.industry.siemens.com/cs/ww/en/view/109766358</a> <a href="https://www.siemens.com/tstcloud">https://www.siemens.com/tstcloud</a> <a href="https://www.siemens.com/mobile-approvals">https://www.siemens.com/mobile-approvals</a> <a href="https://www.siemens.com/simatic-net">https://www.siemens.com/simatic-net</a> <a href="https://sieportal.siemens.com/">https://sieportal.siemens.com/</a> <a href="https://www.automation.siemens.com/bilddb">https://www.automation.siemens.com/bilddb</a> <a href="https://www.siemens.com/cax">https://www.siemens.com/cax</a> <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>								
<b>security information</b>									
security information	<p>Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit <a href="http://www.siemens.com/cybersecurity-industry">www.siemens.com/cybersecurity-industry</a>. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <a href="https://www.siemens.com/cert">https://www.siemens.com/cert</a>. (V4.7)</p>								
<b>Approvals / Certificates</b>									
<table> <tr> <th>General Product Approval</th><th>For use in hazardous locations</th></tr> <tr> <td>   EG-Konf. </td><td>  </td></tr> <tr> <td>   UL </td><td>   RCM </td></tr> <tr> <td></td><td>   ATEX </td></tr> </table>		General Product Approval	For use in hazardous locations	 EG-Konf.		 UL	 RCM		 ATEX
General Product Approval	For use in hazardous locations								
 EG-Konf.									
 UL	 RCM								
	 ATEX								
Radio Equipment Type Approval Certificate	Environment								
<a href="#">Miscellaneous</a>									

last modified:

4/3/2025 