

SIMATIC ET 200SP, TM SIWAREX WP351 HF, verifiable weighing module for automatic dosing-, filling-, checking- and totalizing scales, 3xDI, 3xDQ, 1xCI, 1xRS485, 1xEthernet, 1x LC (1-4mV/V) Calibration certificates in preparation



General information

Product type designation	TM SIWAREX WP351 HF
HW functional status	1
Firmware version	V1.0
• FW update possible	Yes
usable BaseUnits	BU type C0
Color code for module-specific color identification plate	CC00
Product function	
• I&M data	Yes; I&M0 to I&M3
• Isochronous mode	No
• Adjustment of measuring range	Yes; $\pm 0 \dots 4 \text{ mV/V}$

Engineering with

• STEP 7 TIA Portal configurable/integrated from version	V15.1
• STEP 7 configurable/integrated from version	- / -
• PROFIBUS from GSD version/GSD revision	GSD as of Revision 5
• PROFINET from GSD version/GSD revision	GSDML V2.34

Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
• permissible range, lower limit (DC)	19.2 V
• permissible range, upper limit (DC)	28.8 V
• Short-circuit protection	Yes
• Reverse polarity protection	Yes
Input current	
Current consumption, max.	140 mA; Without DQ
Power	
Power available from the backplane bus	94.5 mW
Power loss	
Power loss, typ.	1.7 W
Address area	
Address space per module	
• Inputs	32 byte
• Outputs	32 byte
Digital inputs	
Number of digital inputs	3
Digital inputs, parameterizable	Yes
Input characteristic curve in accordance with IEC 61131, type 3	Yes
Input voltage	
• Type of input voltage	24 V DC
• Rated value (DC)	24 V
• for signal "0"	< 5 V DC
• for signal "1"	+11 to +30V
• permissible voltage at input, min.	-30 V
• permissible voltage at input, max.	30 V
Input current	
• for signal "1", typ.	1.6 mA
Input delay (for rated value of input voltage)	
for technological functions	
— parameterizable	Yes
Cable length	
• shielded, max.	500 m
• unshielded, max.	150 m
Digital outputs	
Number of digital outputs	3
Current-sourcing	Yes

Digital outputs, parameterizable	Yes
Short-circuit protection	Yes
Digital output functions, parameterizable	
• Freely usable digital output	Yes
Switching capacity of the outputs	
• with resistive load, max.	0.5 A
Output voltage	
• Type of output voltage	DC
Output delay with resistive load	
• "0" to "1", typ.	20 µs
• "1" to "0", typ.	30 µs
Parallel switching of two outputs	
• for uprating	No
Switching frequency	
• with resistive load, max.	500 Hz
Total current of the outputs	
• Current per channel, max.	0.5 A; the total current of all outputs \geq 0.6 A, the ambient temperature is reduced by -1 °C per 100 mA
• Current per module, max.	1.5 A; Observe derating
Cable length	
• shielded, max.	500 m
• unshielded, max.	150 m
Encoder	
Connection of signal encoders	
• For strain gauges (full bridges) with 4-conductor connection	Yes
• For strain gauges (full bridges) with 6-conductor connection	Yes
• Resistance of full bridge, min.	56 Ω; when using SIWAREX IS 87 ohm for 7MH4710-5BA; 180 ohm when using 7MH4710-5CA
• Resistance of full bridge, max.	4 100 Ω
Errors/accuracies	
Linearity error (relative to input range), (+/-)	0.001 %
Error limit according to DIN 1319-1	0.002 %; of full-scale value
Accuracy class	III
Temperature coefficient, zero point	$\leq \pm 0.015 \mu\text{V/K}$
Temperature coefficient, span	$\leq \pm 5 \text{ ppm/K}$
1. Interface	
Interface types	
• RS 485	Yes; Terminated internally with 390 Ω / 220 Ω / 390 Ω
2. Interface	

Interface types	
• Number of ports • RJ 45 (Ethernet)	1 Yes; 10/100 Mbit/s
Protocols	
• IP protocol	Yes; IPv4
• Web server	Yes
Interface types	
RJ 45 (Ethernet)	
• Autonegotiation	Yes
• Autocrossing	Yes
RS 485	
• Transmission rate, max.	115.2 kbit/s
• Cable length, max.	1 000 m; ≤ 115 kbps, shielded cable
Protocols	
Web server	
• HTTP	Yes
• HTTPS	No
Interrupts/diagnostics/status information	
Diagnostics function	Yes; Diagnostic alarm
Substitute values connectable	No
Alarms	
• Diagnostic alarm	Yes; Parameterizable
• Hardware interrupt	Yes; Parameterizable
Diagnostic messages	
• Monitoring the supply voltage	Yes
• Wire-break	Yes
• Short-circuit	Yes
• Group error	Yes; green/red DIAG LED
Diagnostics indication LED	
• ERROR LED	Yes; green/red DIAG LED
• Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
Integrated Functions	
Load cell	
• Automatic weighing instrument	SWA/AGFI; SWE/ACI; SKW/SCW; SWT/DTAWI
• Non-automatic weighing instrument	NAWI
• fraction of the error limit pi	0.4
• Number of verification intervals, max.	3x 6 000 d (d=e)
• permissible input signal per verification interval, min.	0.5 µV/d (d=e)
• Sampling rate	1 024 Hz

• Resolution of input signal	$\pm 20\,000\,000$ parts at 0 ... 4 mV/V
• Common mode voltage, min.	2.8 V
• Common mode voltage, max.	7.7 V
• input resistance of signal line, typ.	8 M Ω
• input resistance of sense line, typ.	300 M Ω
• Cable length, max.	500 m; when using the SIWAREX 7MH4702-8AG cable
Measuring functions	
Measuring range	
— -1 mV/V to +1 mV/V	Yes
— -2 mV/V to +2 mV/V	Yes
— -4 mV/V to +4 mV/V	Yes
Isolation	
Isolation tested with	707 V DC (type test)
Ambient conditions	
Ambient temperature during operation	
• horizontal installation, min.	-30 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	-30 °C
• vertical installation, max.	50 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	5 000 m; more than 2 000 m above sea level, the ambient temperature is reduced by -1 °C per 100 m
• Ambient air temperature-barometric pressure-altitude	1 080 ... 533 hPa (-1 000 ... 5 000 m above sea level)
Decentralized operation	
to SIMATIC S7-300	Yes
to SIMATIC S7-400	Yes
to SIMATIC S7-1200	Yes
to SIMATIC S7-1500	Yes
to standard PROFIBUS master	Yes
to standard PROFINET controller	Yes
Dimensions	
Width	20 mm
Height	57 mm
Depth	72 mm
Weights	
Weight, approx.	50 g
last modified:	07/13/2020